MILITARY SPECIFICATION SHEET


CONNECTORS, COAXIAL, RADIO FREQUENCY, (SERIES MHV (CABLED) - RECEPTACLES, SOCKET CONTACT, FLANGE MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connector described herein shall consist of this document and the latest issue of Specification MIL-C-39012.

INACTIVE FOR NEW DESIGN


INCHES	MM
.085	2.16
.095	2.41
.099	2.51
.245	6.22
.255	6.48
.328	8.59
.348	8.84
.496	12.60
.504	12.80
.568	14.43
.680	17.27
.700	17.78
.755	19.18
.790	20.07
1.500	38.10



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Dimension .568 is the largest overall diameter of the connector, less the flange.
4. Wrench flats are to accommodate standard wrench openings per H-28, app. 10.
5. Receptacle not recommended for use on panels with greater than .078 (1.98 mm) maximum thickness.
6. All undimensioned pictorial representations are for reference purposes only.
7. Bayonet studs and edges of flange shall be within 3° of the orientation shown.

FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:14Z
Check the source to verify that this is the current version before use.



LTR	Dimensions in inches with metric equivalents (mm) in parentheses. Minimum	Maximum
A	.432 (10.97)	.436 (11.07)
B	.378 (9.60)	.382 (9.70)
C	.319(8.10)	.321 (8.15)
D		.186 (4.72)
E	.327 (8.31)	.335 (8.51)
F	.289 (7.34)	.311 (7.90)
G	.253 (6.43)	.280 (7.11)
H	.075 (1.91)	.081 (2.06)
J	.270 (6.86)	
K	.081 (2.06)	.091 (2.31)
L	.346 (8.79)	.356 (9.04)
M	.327 (8.31)	.333 (8.46)
N	.015 (.38)	.030 (.76)
P	.284 (7.21)	.290 (7.37)
R	.086 (2.18)	




FIGURE 2. Mating dimensions for socket termination.

Source: https://assist.dla.mil -- Downloaded: 202610-21T17:14Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: Nonconstant.

Frequency range: Not applicable.

Voltage rating:
1600 volts rms, maximum working voltage at sea level.
375 volts rms, maximum at 70,000 feet.

Temperature rating: -65° to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:
Longitudinal force - 3 pounds, maximum.
Torque - 2-1/2 inch-pounds, maximum.

Mating characteristics:
See figure 2 for dimensions.
Outer contact:
Test ring ID - .319 maximum, 16 microinch finish.
Insertion force - 5 pounds, maximum when inserted a minimum of .093.
Contacts with slotted members: Shall contact a .324 minimum diameter ring within .031 of their tip ends.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: Method 302, test condition B, MIL-STD-202. 5,000 megohms, minimum.

Contact resistance: In milliohms, maximum.

	Initial	After environment
Center contact	2.0	2.5
Outer contact	.2	Not applicable
Braid to body	.1	Not applicable

Corrosion (salt spray): Method 101, test condition B, MIL-STD-202.

Dielectric withstanding voltage: Method 301 of MIL-STD-202. 5,000 volts rms, minimum at sea level.

Corona level:
Voltage - 1245 volts rms.
Altitude - 70,000 feet.

RF high potential withstanding voltage: Not applicable.

Connector durability:
500 cycles minimum at 12 cycles/min maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.
Initial - 5 pounds, maximum.
Final - 5 pounds maximum; 1 pound minimum.

Vibration, high frequency: Method 204, test condition B, MIL-STD-202. No discontinuities.

Shock (specified pulse): Method 213 of MIL-STD-202, test condition I.
Acceleration - 50 G's at 7 milliseconds. No discontinuities.

Source: https://assist.dla.mil -- Downloaded: 202640-21T17:14Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number, cross reference and dimensions.

Dash No.	Applicable cable number
CATEGORY A - FIELD SERVICEABLE (NO SPECIAL TOOLS REQUIRED)	
0001	M17/29-RG59 M17/30-RG62 M17/90-RG71 M17/97-RG210

Thermal shock: Method 107, test condition B, MIL-STD-202, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200°C cable (see table I).

Moisture resistance: Method 106 of MIL-STD-202. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Cable retention force:
Noncrimp assemblies - 40 pounds, minimum.

Coupling mechanism retention force: Not applicable.

Part numbers: M39012/102-0001

TABLE II. Supersession and cross reference.

Part number	Superseded numbers			
	FSCM 74868	FSCM 91836	FSCM 77820	Type designation
M39012/102-0001	28175	3050-1	KV-54-08	UG961A

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy -
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AM, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 5935-3065-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:14Z
Check the source to verify that this is the current version before use.