MIL-A-45898(AR)
7 July 1977
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

ADAPTER, WARHEAD SECTION: H4252A

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of adapter entitled Adapter, Warhead Section: H4252A which is used with the Sprint warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168	- Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8889034	- Ring, Forward Adapter.
8889035	- Link, Support.
9248916	- Pin Locating.
9248936	- Adapter Warhead Section: H4252A.
9260288	- Box, Fiberboard, Packing, Ammunition for Adapter, Warhead Section (Forward): H4252A.
9276691	- Bolt Captive.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The adapter shall comply with all requirements specified on the drawing (dwg) 9248936, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Lot number. The contractor shall affix the lot number to each adapter in the space illustrated on the drawing. There shall be no indication of order or size of production in the lot designation.

3.5 Proof load. The adapter shall withstand an approved load of 790 plus (+) 20 pounds applies for 6 + 1 minutes without damage. Testing shall be as described in 4.4.1.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 2 complete assemblies (see dwg 9248936) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics		X
2. Proof load (see 3.5)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Ring, forward adapter (see dwg 8889034).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Mislocation of mounting hole (8)	Gage
102.	Incorrect inside diameter	Gage
103.	Incorrect diameter - base taper	Gage
104.	Incorrect outside diameter	Gage
105.	Mislocation of small mounting hole (8)	Gage
106.	Mislocation of locating pin hole	Gage
107.	Counterbore missing, incomplete (8)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

108.	Missing or improper thread (see note on dwg) in mounting hole (8)	Visual
109.	Incorrect angel (see Detail A)	Gage
110.	Evidence of poor workmanship (see 3.6)	Visual
111.	Height of ring	Gage
112.	Incorrect distance between flats on periphery	Gage
→113.	Mislocation of moungint holes (4) for brackets	Gage
114.	Incorrect location of notch (2) on periphery	Gage
115.	Location of through holes incorrect (4 places) (see View A-A)	Gage
→116.	Diameter of thorugh holes incorrect (4 places) (see View A-A)	Gage
117.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Minor:

201.	Improper finish	Visual

4.3.2.1.2 Link, support (see dwg 8889035).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect width	Gage
102.	Mislocation of center diameter	Gage
103.	Evidence of poor workmanship (see 3.6)	Visual
104.	Incorrect pitch diameter (max.) (4 holes)	Gage
105.	Incorrect minor diameter (max.) (4 holes)	Gage
106.	Incorrect depth of thread (4 holes)	Gage
107.	Incorrect pitch diameter (max.) (1 hole)	Gage
108.	Incorrect minor diameter (max.) (1 hole)	Gage
109.	Incorrect depth of thread (1 hole)	Gage
110.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

Minor:
201. Marking missing, improper, illegible or misplaced.....Visual

4.3.2.1.3 Adapter warhead section: H4252A (see dwg 9248936).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Component missing, improper damaged, misplaced or improperly assembled	Visual
102.	Insert (8) not installed as specified in note on dwg	Visual
103.	Evidence of poor workmanship (see 3.6)	Visual
104.	Captive bolt (8) does not rotate freely (do not use tool)	Manual/Visual
105.	Areas described in note of dwg not free of protective finish	Visual
106.	Improper torque applied to bolt (4) (see note in dwg)	Visual
107.	Incorrect diameter of shackle in lifting area	Gage
108.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective finish improper, or damaged exposing base metal	Visual
202.	Marking missing, improper, illegible, or misplaced	Visual

4.3.2.1.4 Bolt captive (see dwg 9276691).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of thread incorrect (min)	Gage
102.	Major diameter of thread incorrect (max)	Gage
103.	Length of full thread incorrect	Gage
104.	Incorrect shank length plug thread section	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

105. Diameter of bolt shank incorrect.....Gage
106. Evidence of poor workmanship (see 3.6).....Visual
107. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor: None defined.

4.3.2.1.5 Pin, locating (see dwg 9248916).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Diameter of pin chank incorrect	Gage
102.	Overall length incorrect	Gage
103.	Diameter of head incorrect	Gage
104.	Material incorrect	Visual
105.	Evidence of poor workmanship (see 3.6)	Visual
106.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor: None defined.		

4.3.2.1.6 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Preservation, packing, and packaging not in accordance with dwg 9260288	Visual
102.	Marking no in accordance with dwg 9260288	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Proof load	Major

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

This test is not considered destructive and samples so tested may be returned to the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major and Minor characteristics and tests. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Proof load. The adapter, suitably suspended from its anchor shackel shall be capable of supporting an approved load of 790 ± 20 pounds. The load shall possess the identical mounting feature of a warhead section Sprint. The load shall be attached to the adapter by its 9 captive bolts and suspended above the floor, therby simulating the in-use-condition. After the load remains suspended for 6 ± 1 minute is shall be removed and the adapter examined for damage (see 6.4).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The adapter shall be packaged in accordance with dwg 9260288 using the specified moisture barrier.

5.1.2 Level C. The adapter shall be packaged in accordance with dwg 9260288 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The adapter shall be packed in accordance with dwg 9260288.

5.3 Marking. Marking shall be as specified in accordance with dwg 9260288.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 *Damage. A defect that is detectable by visual examination. Typical defects are as follows: Crack in weldment, damaged threads, deformed structural member, cracked structural member, damaged finish exposing base metal; marking obliterated.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2311, dated 4 April 1972 and PA-PD-2311A dated 12 October 1972.

*A 5X magnifying glass may be used while examining for damages.

Custodian:
Army - AR

Preparing activity:
Army - AR

Project No. 1190-A105

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL	OMB Approval No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers (vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

a. GIVE PARAGRAPH NUMBER AND WORDING.

b. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

YES NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.