MILITARY SPECIFICATION

CABLE ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL BRANCHED: 5W5

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of special purpose electrical cable assembly entitled Cable Assembly, Special Purpose, Electrical Branched: 5W5 which is used with the Sprint warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-W-60904	- Wire and Cable, Polymide Insulated Electrical.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810	- Evironmental Test Methods.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:07Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

9272713	- Cable Assembly, Special Purpose, Electrical Branched: 5W5.
9278841	- Jig, Electrical Cable, Special Purpose (Modified).
9287510	- Packing and Marking for Box, Fiberboard, for Cable Assembly 5W5 and 5W5 Training.
EL-9272713	- Equipment List.

PUBLICATIONS

PICATINNY ARSENAL

QAI-PA-1	- Quality Assurance Instructions for Reporting Data on Nuclear Weapons.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The cable assembly shall comply with all requirements specified on the drawing (dwg) 9272713, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. A serial number shall be assigned to the item. Serial numbers required on these items shall be obtained by means of a letter addressed to: Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTENTION: SARPA-QA-T-M. The letter of request shall include:

a. Exact nomenclature of the item as specified on the applicable drawing.
b. Name of the contractor.
c. Contract number or procurement request order number.
d. Number of serial numbers required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.

3.5 Coded serialization requirements (see 6.1.2). The contractor shall supply feedback data on punch cards for any item for which coding is required in section 3. The feedback data shall be in accordance with QAI-PA-1.

3.6 Mating assembly. The cable assembly shall be capable of being assembled to the functional gage P/N 9289581 and connectors mated without the use of tools when assembled as specified in 4.4.1.

3.7 Fabrication. The cable assembly shall be fabricated in accordance with the method specified in 4.4.7.

3.8 Circuit Resistance.

3.8.1 Shield terminations (prior to completion of shield terminations on connector P3). The circuit resistance between the points listed in Table I shall not exceed 100 milliohms when tested as specified in 4.4.2.1.

Table I

Item	From	To
1	P2-R	Shield Group P3-H and P3-D
2	P2-R	Shield Group P3-F and P3-K
3	P2-S	Shield Group P3-L and P3-X
4	P2-S	Shield Group P3-T and P3-P
5	P2-S	Shield Group P3-R and P3-B

3.8.2 Shield terminations (Prior to taping and braiding). After shield terminations are made, all wires on connectors P2, P3 and P4 shall be suitably marked to preclude intermixing of shield groups. The circuit resistance between the points listed in Table II shall not exceed 100 milliohms when tested as specified in 4.4.2.2.

Table II

Item	From	To
1	P2-H	Shield Group J1-J and J1-K
2	P2-G	Shield Group J1-F and J1-b
3	P2-G	Shield Group J1-a and J1-E
4	P2-G	Shield Group J1-Z and J1-C
5	P2-R	P3-V
6	P2-S	P3-Y
7	P4-Y	Shield Group J1-N and J1-a

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the currentversion before use.

Table II (Cont.)

Item	From	To
8	P4-Y	Shield Group J1-f and J1-P
9	P4-U	Shield Group J1-T and J1-g
10	P4-U	Shield Group J1-h and J1-U
11	P4-U	Shield Group J1-V and J1-i

3.8.3 Circuit resistance. The circuit resistance between the points shown in Table III shall be within the limits specified when tested in accordance with 4.4.2.3.

Table III

Item	From	To	Ohms Resistance	Test Code* (See 3.5 and Table IV)
1	P2-K	J1-K	.100 max	0801--
2	P2-J	J1-J	.100 max	0802--
3	P2-F	J1-F	.100 max	0803--
4	P2-b	J1-b	.100 max	0804--
5	P2-a	J1-a	.100 max	0805--
6	P2-E	J1-E	.100 max	0806--
7	P2-Z	J1-Z	.100 max	0807--
8	P2-C	J1-C	.100 max	0808--
9	P2-N	P3-H	.100 max	0809--
10	P2-e	P3-D	.100 max	0810--
11	P2-R	P3-V	.100 max	0811--
12	P2-f	P3-F	.100 max	0812--
13	P2-P	P3-K	.100 max	0813--
14	P2-T	P3-L	.100 max	0814--
15	P2-g	P3-X	.100 max	0815--
16	P2-S	P3-Y	.100 max	0816--

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:07Z
Check the source to verify that this is the current version before use.

Table III (Cont.)

Item	From	To	Ohms Resistance	Test Code* (See 3.5 and Table IV)
17	P2-h	P3-T	.100 max	0817--
18	P2-U	P3-P	.100 max	0818--
19	P2-V	P3-R	.100 max	0819--
20	P2-i	P3-B	.100 max	0820--
21	P4-R	J1-N	.100 max	0821--
22	P4-L	J1-e	.100 max	0822--
23	P4-N	J1-f	.100 max	0823--
24	P4-B	J1-P	.100 max	0824--
25	P4-C	J1-T	.100 max	0825--
26	P4-T	J1-g	.100 max	0826--
27	P4-V	J1-h	.100 max	0827--
28	P4-F	J1-U	.100 max	0828--
29	P4-G	J1-V	.100 max	0829--
30	P4-J	J1-i	.100 max	0830--

Table IV

Test Conditions	Last Two Digits
Ambient	00
Mech Shock (After)	01
Temp Shock (After)	02
Random Vibration (After)	03

*The last two digits of the test code numbers are derived from the test conditions and associated digits shown in Table IV.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

3.9 Insulation resistance. The insulation resistance between the points specified in 3.9.1 and 3.9.2 shall be not less than 50 megohms when subjected to 500 ± 50 volts direct current, 10 milliamperes maximum. Testing shall be as specified in 4.4.3.

3.9.1 Cable circuits. The insulation resistance shall be tested between the following listed points.

From	To
P2-K	All other pins of P2 (including unused pins), connector shells, and unused pins of P3, P4, and J1 all shorted together.
P2-J	"
P2-F	"
P2-b	"
P2-a	"
P2-E	"
P2-Z	"
P2-C	"
P2-N	"
P2-e	"
P2-f	"
P2-P	"
P2-T	"
P2-g	"
P2-h	"
P2-U	"
P2-V	"
P2-i	"

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

From	To
P4-R	All other pins of P4 (including unused pins) connector shells, and unused pins of P3, P2, and J1 all shorted together.
P4-L	"
P4-N	"
P4-B	"
P4-C	"
P4-T	"
P4-V	"
P4-F	"
P4-G	"
P4-J	"

3.9.2 Shielding. The insulation resistance shall be tested between the following listed pins:

From	To
P2-H	All other pins of P2, P3, P4, J1 (including unused pins) shorted together
P2-6	"
P2-R	" except P3V
P2-S	" except P3Y
P4-Y	"
P4-U	"

3.10 Environmental testing. The cable assemblies shall be capable of withstanding the following environments when mounted in approved fixtures that simulate actual use.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:07Z
Check the source to verify that this is the current version before use.

3.10.1 Mechanical shock. The cable assemblies shall show no evidence of damage (see 6.5) or deterioration when tested as specified in 4.4.4, and shall comply with the requirements of 3.6, 3.8 and 3.9 upon completion of testing.

3.10.2 Temperature shock. The cable assemblies shall withstand without evidence of damage (see 6.5) three temperature cycles having a temperature range of -40 + 5°F to 110 + 5°F. Transfer between temperature extremes shall be accomplished within a 5 minute interval. Testing shall be as specified in 4.4.5. After this test, the cable assemblies shall comply with the requirements of 3.6, 3.8 and 3.9.

3.10.3 Random vibration. The cable assemblies shall withstand the random vibration defined in Table V for each of the major axis Y, Z and X (see dwg 9272713 for axis orientation) for a test time of one minute without evidence of damage see 6.5). Testing shall be as specified in 4.4.6. After this test the cable assemblies shall comply with requirements of 3.6, 3.8 and 3.9.

Table V

Random Vibration Environment

Frequency Range (Hertz)	Power Level (g units)^2
50-750	0.1125
751-2500	0.135
2501-3000	0.45

Total rms value of 22.25 (g rms)

3.11 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.12 Workmanship.

3.12.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.12.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.12.3 Burrs. Parts shall be free from burrs.

3.12.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.12.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

3.12.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 2 complete assemblies (see dwg 9272713) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table VI. Tests shall be conducted in order specified in Table VI.

Table VI

First article inspection and tests.

Inspections or Test	Dest	Non-Dest
1. Classification of Characteristics/Defects (see 4.3.2.1)		X
2. Mating (see 3.6)		X
3. Circuit resistance (see 3.8)		X
4. Insulation resistance (see 3.9)		X
5. Mechanical shock (see 3.10.1)	X	
6. Temperature shock (see 3.10.2)	X	
7. Random vibration (see 3.10.3)	X	

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 20260-22T04:07Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor defects/characteristics table (see Table VII and Table VIII), and inspected for all defects/characteristics in the applicable classification. Any defects/characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of defects/characteristics in each classification need not be followed as long as all defects/characteristics inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

Table VII
Major Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table VIII
Minor Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of defects/characteristics (see 3.2). Critical, major and minor defects/characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Cable assembly 5W5 (see dwg 9272713).

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
	101. Incorrect connector	Visual
	102. Keyways improperly oriented	Visual
	103. Connector insert cracked, chipped or damaged	Visual
	104. Missing contacts (pin or socket)	Visual
	105. Contacts nicked, cracked, gouged, bent or flattened	Visual
	106. Shell or coupling ring deformed	Visual
	107. Insulation damaged	Visual
	108. Any component missing	Visual
	109. Wire size incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

Categories	Characteristics/Defects	Method of Inspection
110.	Wire type incorrect (MIL-W-60904)	Visual
111.	Soldering inadequate (MIL-STD-1460)	Visual
112.	Sleeving improper	Visual
*113.	Height of pins, pins of the same diameter must all appear to be within 1/32 inch in height relative to adjacent pins	Visual/Gage
**114.	Depth of sockets, sockets of the same diameter must all appear to be within 1/32 inch in depth relative to adjacent sockets	Visual/Gage
115.	Objective evidence that all material (see 3.1) and the manufacturing jig (see 3.7) comply with applicable drawing requirements (see 6.2)	Visual

Minor:

201.	Marking missing, improper or illegible	Visual
202.	Jacket or molding damaged	Visual
203.	Protective cap missing	Visual
204.	Evidence of poor workmanship (see 3.12)	Visual

*In the event pins do not appear to be within 1/32 inch in height relative to adjacent pins, gaging shall be used to determine the variations from the normal height. Reject any pin that varies by more than .031 inch, maximum, from normal pin height of individual connector. The normal height of the individual pins shall be determined by calculating the average height from measurements taken of pins adjacent to the pin that appears to be defective.

**In the event sockets do not appear to be within 1/32 inch in depth relative to adjacent sockets, gaging shall be used to determine the variations from the normal depth. Reject any socket that varies by more than .031 inch, maximum, from normal socket depth of individual connector. The normal depth of the individual sockets shall be determined by calculating the average depth from measurements taken of sockets adjacent to the socket that appears to be defective.

Source: https://assist.dla.mil -- Downloaded: 20260-22T04:07Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics/Defects	Method of Inspection
Critical:	None defined.	
Major:		
	101. Preservation, packing and marking not in accordance with applicable drawing (see dwg 9287510)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.12)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test classification
a. Mating	Major
b. Circuit resistance	Major
c. Insulation resistance	Major
d. Random vibration	Major

Of these tests, (d) is considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

4.3.3.1 Mating, circuit resistance and insulation resistance. All cable assemblies in the lot shall be tested in accordance with 4.4.1, 4.4.2 and 4.4.3. If any item fails to comply with 3.6, 3.8 and 3.9, the item shall be rejected and removed from the lot.

4.3.3.2 Random vibration. One cable assembly shall be selected at random from each lot of 50 units or portion thereof and tested in accordance with 4.4.6. If any item fails to comply with 3.10.3, the lot shall be rejected.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major defects/characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-9272713). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor defects/characteristics and tests. Acceptance inspection equipment for minor defects/characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Mating (see 3.6). The cable assembly and cable connectors J1, P2, P3 and P4 shall be assembled to the functional gage in accordance with associated Operational Instructions.

4.4.2 Circuit Resistance (see 3.8).

4.4.2.1 Shield terminations (Prior to completion of shield terminations on connector P3). The circuit resistance of the cable assembly shall be measured in accordance with Table I and MIL-STD-202, Method 303.

4.4.2.2 Shield terminations (Prior to taping and braiding). The circuit resistance of the cable assembly shall be measured in accordance with Table II and MIL-STD-202, Method 303.

4.4.2.3 Cable assembly (complete). The circuit resistance of the cable assembly shall be measured in accordance with Table III and MIL-STD-202, Method 303.

4.4.3 Insulation resistance (see 3.9). The insulation resistance of the cable assembly shall be measured in accordance with 3.9.1 and 3.9.2 and MIL-STD-202, Method 302.

4.4.4 Mechanical shock. The cable assemblies shall be mounted onto a fixture which simulates jig mounting (except J-1 branch may be coiled) and is capable of orienting the cable assemblies along each of the three perpendicular axes relative to the shock source. The cable assemblies and the fixture shall be secured to an approved shock machine and tested in accordance with MIL-STD-810, Method 516, Procedure IV, Figure 516-1, (Flight Vehicle Equipment). After this test, the cable assemblies shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 20260-22T04:07Z
Check the source to verify that this is the current version before use.

4.4.5 Temperature shock. The cable assemblies with dust covers over the connectors and mounted to a fixture shall be placed in a test chamber stabilized (see 6.4) at 110 + 5°F and maintained for a minimum of 4 hours. The cable assemblies shall then be removed from the high temperature chamber and within 5 minutes placed in a test chamber stabilized (see 6.4) at -40 + 5°F, maintained for a minimum of 4 hours. This sequence constitutes one cycle. Within 5 minutes, return the cable assemblies to the high temperature chamber. Three cycles shall be executed. Upon completion of the third cycle allow the cable assemblies to return to ambient temperature without forced heating and test in accordance with 4.4.1, 4.4.2 and 4.4.3.

4.4.6 Random vibration. The cable assemblies shall be rigidly mounted to a fixture which simulates jig mounting (except J1-1 branch which may be coiled) and is capable of being positioned readily in each of three mutually perpendicular axes and vibrated over the frequency ranges of random conditions as specified in 3.10.3. After this test, the cable assemblies shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

4.4.7 Fabrication. Each cable assembly shall be fabricated on Jig, Electrical Cable, Special Purpose Electrical Cable, Special Purpose (Modified) (dwg 9278841).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. The cable shall be packed and packaged in accordance with dwg 9287510.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 3.5 and 4.3.4.1). Data specified in 3.5 and 4.3.4.1 will be delivered as identified on numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 20260 0-22T04:07Z
Check the source to verify that this is the current version before use.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Physical damage. Physical damage shall include bent or loose pins, split or cracked insulation, damaged connectors or cracks in connector body.

6.6 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2241 dated 12 July 1972 and SCN #5 dated 3 December 1974.

Custodian:
Army - (AR)

Preparing activity:
Army - (AR)

Project No. 1135-A217

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

[ ] DIRECT GOVERNMENT CONTRACT [ ] SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

[ ] YES [ ] NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:07Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAN-Q
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:07Z
Check the source to verify that this is the current version before use.