
INCH-POUND
MIL-DTL-45913/3C
20 May 2021
SUPERSEDING
MIL-DTL-45913/3B
14 June 2011

DETAIL SPECIFICATION SHEET

NUT, SELF-LOCKING, HEXAGON, NON-METALLIC LOCKING FEATURE, 250 °F, UNC/UNF-3B

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-45913.



(All dimensions are in inches.)

FIGURE 1. Nut, self-locking, hex, non-metallic locking feature UNC/UNF-3B.

Comments, suggestions, or questions on this document should be addressed to U.S. Army DEVCOM, Ground Vehicle Systems Center, ATTN: Standardization, FCDD-GVS-IES, MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000 or send email to usarmy.detroit.devcom-gvsc.mbx.standardization@mail.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 5310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

MATERIAL:

Steel and alloy steel shall be in accordance with SAE J995 grade 5 or 8, as specified in part-number.
Corrosion resisting steel (stainless steel) grades 303 and 316 or any alloy in accordance with ASTM F 594, Group 1 or Group 2, shall have a minimum ultimate tensile strength of 70 KSI and shall be non-magnetic.
Copper alloy (brass) shall be in accordance with SAE AMS4507, HR02 shall have a minimum ultimate tensile strength of 58 KSI and be of a half hard temper.
Aluminum alloy shall be 6061 in accordance with SAE AMS4117 and have a minimum ultimate tensile strength of 42 KSI or as specified in contract.

PLATING/FINISH:

Steel and alloy steel locknuts shall be:

Cadmium[1/] plated per SAE-AMS-QQ-P-416 Type II, Class 2 or 3, or
Zinc-Nickel plated per MIL-PRF-32647, Type K16, or Type K20 or
Zinc plated per ASTM B633 [/2] Type II, Fe/Zn 8, or
Black Oxide per MIL-DTL-13924, Class 1 or
Uncoated plain with a supplementary lubricant which is clean and dry to the touch.

Stainless steel locknuts shall be passivated SAE-AMS 2700 [/3], Method 1, Type 6 or 7, Class 1, or black oxide finish per MIL-DTL-13924.
Brass locknuts shall be black oxide finished per MIL-F-495, nickel plated per SAE-AMS-QQ-N-290, Class 2, or uncoated plain with a brite finish.
Aluminum locknuts shall be anodized clear, no color per MIL-PRF-8625 (see Table I).

[/1] Cadmium is an R1, R2, and D1 substance in the Aerospace and Defense Declarable Substance List. Zinc-Nickel plate per MIL-PRF-32647, Type K16 is the preferred alternate.
[/2] Type II passivation per ASTM B633 contains hexavalent chromium which is an R1, R2, and D1 substance in the Aerospace and Defense Declarable Substance List. Zinc with hex free passivation per ASTM F1941/F1941M Fe/Zn 12 or Zinc-Nickel plate per MIL-PRF-32647 Type K20 are the preferred alternates.
[/3] Passivation per ASM2700 contains sodium dichromate which is an R1, R2, and D1 substance in the Aerospace and Defense Declarable Substance List. Zinc with hex free passivation per ASTM F1941/F1941M Fe/Zn 12 or Zinc-Nickel plate per MIL-PRF-32647 Type K20 are the preferred alternates.

SURFACE TEXTURE. Shall be Ra 125 microinches in accordance with ASME B46.1.

THREADS. Shall be coarse or fine threaded, class 3B, as specified in part-number, in accordance with ASME B1.1.

WORKMANSHIP. Parts shall be manufactured and processed with a level of care and workmanship befitting this type of product intended for general purpose military application. Parts shall be free from dirt, grease, loose or deposited foreign materials, sharp edges, burrs, chips, physical malformations or anything that might prevent the part from reliably performing its intended function.

PART NUMBER. The part number shall consist of the basic number of this specification sheet followed by a dash, a dash number from Table I, a material code from Table II, and a finish/plate code (when required) from Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:12Z
Check the source to verify that this is the current version before use.

EXAMPLE OF PART NUMBER:

M45913/3- 4C G5 QX

- QX — Finish Code (see Table III)
- G5 — Material Code (see Table II)
- 4C — Dash number from Table I to indicate size and thread.
- M45913/3- — "M" plus the Basic Specification Sheet Number followed by "-"

M45913/3-4CG5QX = Nut Self-Locking Hexagon, non-metallic locking feature, .250-20 thread, Grade 5 steel, Zinc-Nickel, Type K16 plated.

TABLE I. Dash numbers and dimensions.

Dash No.	Thread Size	A		B	C		D
		Width Across Flats		Corners	Thickness		
		MAX	MIN	REF	MAX	MIN	REF
00F	.060-80 UNF-3B	.111	.104	.116	.055	.080	.045
01C	.073-64 UNC-3B	.251	.243	.268	.153	.133	.081
01F	.073-72 UNF-3B	.251	.243	.268	.153	.133	.081
02C	.086-56 UNC-3B	.251	.243	.268	.153	.133	.081
02F	.086-64 UNF-3B	.251	.243	.268	.153	.133	.081
03C	.099-48 UNC-3B	.251	.243	.268	.153	.133	.081
03F	.099-56 UNF-3B	.251	.243	.268	.153	.133	.081
04C	.112-40 UNC-3B	.251	.243	.268	.153	.133	.081
04F	.112-48 UNF-3B	.251	.243	.268	.153	.133	.081
05C	.125-40 UNC-3B	.251	.243	.268	.153	.133	.081
05F	.125-44 UNF-3B	.251	.243	.268	.153	.133	.081
06C	.138-32 UNC-3B	.313	.305	.339	.188	.168	.103
06F	.138-40 UNF-3B	.313	.305	.339	.188	.168	.103
08C	.164-32 UNC-3B	.345	.336	.374	.239	.219	.140
08F	.164-36 UNF-3B	.345	.336	.374	.239	.219	.140
010C	.190-24 UNC-3B	.376	.367	.410	.249	.229	.140
010F	.190-32 UNF-3B	.376	.367	.410	.249	.229	.140
012C	.216-24 UNC-3B	.439	.430	.482	.328	.298	.225
012F	.216-28 UNF-3B	.439	.430	.482	.328	.298	.225
4C	.250-20 UNC-3B	.439	.428	.482	.328	.298	.225
4F	.250-28 UNF-3B	.439	.428	.482	.328	.298	.225
5C	.312-18 UNC-3B	.502	.489	.552	.359	.329	.250
5F	.312-24 UNF-3B	.502	.489	.552	.359	.329	.250
6C	.375-16 UNC-3B	.564	.551	.622	.468	.438	.335
6F	.375-24 UNF-3B	.564	.551	.622	.468	.438	.335
7C	.437-14 UNC-3B	.627	.616	.698	.468	.438	.324
7F	.437-20 UNF-3B	.627	.616	.698	.468	.438	.324
8C	.500-13 UNC-3B	.752	.736	.837	.609	.579	.464
8F	.500-20 UNF-3B	.752	.736	.837	.609	.579	.464
9C	.562-12 UNC-3B	.877	.861	.978	.656	.626	.469
9F	.562-18 UNF-3B	.877	.861	.978	.656	.626	.469
10C	.625-11 UNC-3B	.940	.922	1.051	.765	.735	.593
10F	.625-18 UNF-3B	.940	.922	1.051	.765	.735	.593
12C	.750-10 UNC-3B	1.064	1.052	1.191	.890	.860	.742
12F	.750-16 UNF-3B	1.064	1.052	1.191	.890	.860	.742
14C	.875-9UNC-3B	1.252	1.239	1.403	.999	.969	.790
14F	.875-14 UNF-3B	1.252	1.239	1.403	.999	.969	.790
16C	1.000-8UNC-3B	1.440	1.427	1.615	1.078	1.016	.825
16F	1.000-12 UNF-3B	1.440	1.427	1.615	1.078	1.016	.825

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:12Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and dimensions – Continued.

18C	1.125-7UNC-3B	1.627	1.614	1.826	1.203	1.141	.930
18F	1.125-12 UNF-3B	1.627	1.614	1.826	1.203	1.141	.930
20C	1.250-7UNC-3B	1.815	1.801	2.038	1.422	1.360	1.125
20F	1.250-12 UNF-3B	1.815	1.801	2.038	1.422	1.360	1.125
22C	1.375-6UNC-3B	2.008	1.973	2.232	1.609	1.547	1.282
22F	1.375-12 UNF-3B	2.008	1.973	2.232	1.609	1.547	1.282
24C	1.500-6UNC-3B	2.197	2.159	2.444	1.640	1.578	1.313
24F	1.500-12 UNF-3B	2.197	2.159	2.444	1.640	1.578	1.313

TABLE II. Material coding.

MATERIAL CODE	
Steel Grade 5	G5
Steel Grade 8	G8
Stainless Steel 303	S3
Stainless Steel 316	S6
Brass	BB
Aluminum	AA

TABLE III. Finish coding. 1/

Cadmium	C
Zinc	Z
Black Oxide	B
Nickel	N
Zinc-Nickel (Type K16)	QX
Zinc-Nickel (Type K20)	QW
Anodized	no code (aluminum only)
Passivate	no code (stainless only)
Uncoated	no code

1/See requirements above for material and finish precautions.

NOTES:

1. Dimensions in inches, unless specified, tolerance: ±.016.
2. Interpret drawing in accordance with ASME Y14.5.
3. Break all Sharp edged .003 to .005 and remove all burrs and slivers.
4. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.
5. Unless otherwise specified, issues of referenced documents are those in effect at the time of solicitation.
6. Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:12Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AT
Navy - OS
Air Force - 71

Preparing activity
AT

(Project 5310-2021-016)

Review activities:
Army - AV, CR4, EA, GL, MI
Navy - AS, MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:12Z
Check the source to verify that this is the current version before use.