MILITARY SPECIFICATION

Generator, Test, for T41-33 Test Set

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of generator entitled Generator, Test, which is used with the Honest John warhead.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8821487	- Generator, Test.
EL-8821487	- Equipment List.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The generator shall comply with all requirements specified on the drawing (dwg) 8821487, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Torque. The starting torque shall not exceed 20 inch pounds and the average of 5 trials shall not exceed 15 inch pounds when tested as specified in 4.4.1.

3.6 Polarity. The red lead shall be positive with respect to the black lead for clockwise rotation of the test generator when tested as specified in 4.4.2.

3.7 Output. The test generator when turned at a speed of 70 ± 5 revolutions per minute (rpm) shall have an output of 28 ± 3 volts direct current (vdc) across a 280 ohm load when tested as specified in 4.4.3.

3.8 Life test. The test generator shall meet the requirements of 3.5, 3.6 and 3.7 after being subjected to 10,000 starts (5,000 clockwise and 5,000 counterclockwise) when tested as specified in 4.4.4.

3.9 Environmental testing (see MIL-STD-202).

3.9.1 Low temperature. The test generator shall meet the requirements of 3.5 and 3.7 while at a temperature of -65 ± 5°F when tested as specified in 4.4.5.1.

3.9.2 High temperature. The test generator shall meet the requirements of 3.5 and 3.7 while at a temperature of 160 ± 5°F when tested as specified in 4.4.5.2.

3.9.3 Humidity. The test generator shall be subjected to a humidity of 95 percent for 240 hours and after a 1 hr wait the test shall comply with the requirements of 3.6 and 3.7 when tested as specified in 4.4.5.3.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:06Z
Check the source to verify that this is the current version before use.

3.9.4 Vibration. The generator shall be vibrated at the frequencies, gravitational units (g) accelerations, temperatures, and for the time specified in Table I, in each of three mutually perpendicular axes. The assembly shall show no evidence of damage such as cracks, chips, separations, or loose parts, and after vibration shall comply with the requirements of 3.5, 3.6 and 3.7 after being tested as specified in 4.4.5.4.

Table I

Frequency Range Hertz (Hz)	Double Displacement or Peak g Level ± 5% Tolerance	Cycle Time to Cover Frequency Range (Minutes)	Test Time in Minutes Minimum Time Per Axis 80 ± 20°F	160 ± 5°F	-65 ± 5°F
10-20-10	2 g	3 ± 0.5	15	10	10
20-75-20	0.036 inch	3 ± 0.5	15	10	10
75-100-75	5 g	3 ± 0.5	15	10	10

3.9.5 Shock. The test generator shall be capable of withstanding three shocks of 75 ± 8 g's peak amplitude with a half amplitude duration of 9 ± 3 milliseconds in each of three mutually perpendicular axes. The test generator shall comply with the requirements of 3.5 and 3.6 when tested as specified in 4.4.5.5.

3.10 Workmanship.

3.10.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.10.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.10.3 Burrs. Parts shall be free from burrs.

3.10.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.10.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:06Z
Check the source to verify that this is the current version before use.

or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 6 complete assemblies (see dwg 8821487) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table II. Tests shall be conducted in order specified in Table II.

Table II

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of defects/characteristics (see 4.3.2.1)		X
2. Torque (see 3.5)		X
3. Polarity (see 3.6)		X
4. Output (see 3.7)		X
5. *Life test (see 3.8)	X	
6. *Low temperature (see 3.9.1)		X
7. *High temperature (see 3.9.2)		X
8. *Humidity (see 3.9.3)	X	
9. *Vibration (see 3.9.4)	X	
10. *Shock (see 3.9.5)	X	

*If the same contractor is supplying the T4133 or T4162 Test Set, these tests may be deferred until tested as part of the T4133 or T4162.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor defects/characteristics table (see Table III and Table IV), and inspected for all defects/characteristics in the applicable classification. Any defects/characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of defects/characteristics in each classification need not be followed as long as all defects/characteristics inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:06Z
Check the source to verify that this is the currentversion before use.

Table III
Major Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

Table IV
Minor Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of defects/characteristics (see 3.2). Critical, major and minor defects/characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Generator test (see dwg 8821487).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Improper large outside diameter	Gage
	102. Improper width of mounting flange	Gage
	103. Improper length from flange to end of shaft	Gage
	104. Improper length from flange to shaft max. (0.645)	Gage
	105. Improper length from end of generator to flange, max (2.250)	Gage
	106. Improper length of squared portion of shaft	Gage
	107. Squared end of shaft improper	Gage
	108. Improper diameter of round portion of shaft	Gage
	109. Location of 4 mounting holes	Gage
	110. Improper diameter of mounting holes	Gage
	111. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
	201. Improper length of leads	Gage
	202. Color of leads improper	Visual
	203. Evidence of poor workmanship (see 3.10)	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:06Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packing, and packaging not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.10)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Torque	Major
b. Polarity	Major
c. Output	Major
d. High temperature	Major
e. Vibration	Major

Of these tests, e is considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

4.3.3.1 Torque, polarity, and output. Each test generator shall be tested in accordance with 4.4.1, 4.4.2, and 4.4.3. If any item fails to comply with 3.5, 3.6 and 3.7, the item shall be rejected and removed from the lot.

4.3.3.2 High temperature and vibration*. One sample test generator shall be selected from each 100 generators or portion thereof produced and tested in accordance with 4.4.5.2 and 4.4.5.4. If any test generator fails to comply with the requirements of 3.9.2 and 3.9.4, the lot shall be rejected.

*If the same supplier is supplying the T4133 or T4162 test sets these tests may be deferred until tested as part of the T4133 or T4162 test sets.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T04:06Z
Check the source to verify that this is the current version before use.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major defects/characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8821487). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor defects/characteristics and tests. Acceptance inspection equipment for minor defects/characteristic is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Torque. The assembly shall be mounted on a rigid fixture during this test. Measure the torque required to start this generator shaft turning. Record this torque required for each of five trials, making certain the shaft comes to rest after and before each trial.

4.4.2 Polarity. Rotate the shaft clockwise; clockwise rotation of the shaft shall be determined by looking into the shaft end of the generator, and the potential of the red lead shall be positive with respect to the black lead.

4.4.3 Output. Using a variable speed motor and a suitable coupling device the test generator shall be driven at 70 ± 5 rpm. While rotating at this speed the output shall be measured across a 280 ohm load.

4.4.4 Life test. The test generator shall be started 10,000 times, 5,000 clockwise and 5,000 counterclockwise, and after this test the test generator shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

4.4.5 Environmental testing (see 3.9).

4.4.5.1 Low temperature. The test generator shall be placed in a container and the container sealed. The container shall then be placed in the test chamber and the temperature lowered to -65 ± 5°F and stabilized (see 6.4). The container and the test generator shall soak at this temperature for a minimum of 4 hours. While at this temperature

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:06Z
Check the source to verify that this is the current version before use.

the test generator shall be tested as specified in 4.4.1 and 4.4.3. After these tests the test generator shall be removed from the test chamber and allowed to return to room temperature.

4.4.5.2 High temperature. The test generator shall be placed in a test chamber and the temperature of the chamber raised to 160 + 5°F and stabilized (see 6.4). The test generator shall soak at this temperature for four hours. While at this temperature the generator shall be tested as specified in 4.4.1 and 4.4.3. After these tests the test generator shall be removed from the chamber and allowed to return to room temperature.

4.4.5.3 Humidity. The test generator shall be tested as specified in MIL-E-5272, paragraph 4.4.1 except for the last two sentences of the paragraph, which shall be deleted. The generator shall then be tested as specified in 4.4.2 and 4.4.3 within one hour.

4.4.5.4 Vibration. The test generator shall be rigidly mounted to a fixture capable of being supported readily in each of three mutually perpendicular axes. Vibrate the generator at the frequencies, amplitudes, and for the times specified in 3.9.4 in each of the three major mutually perpendicular axes. Following this test the assembly shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

4.4.5.5 Shock. The test generator shall be rigidly mounted to a fixture capable of being supported readily in each of three mutually perpendicular axes. The test generator and fixture shall be subjected to the test conditions specified in 3.9.5. Following the testing in each axes the test generator shall be tested as specified in 4.4.1, 4.4.2 and 4.4.3.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The test generator shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The test generator shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The test generator shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1784 dated 15 February 1965.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No.: NUOR-A057

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. *DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product* are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:06Z
Check the source to verify that this is the current version before use.