MIL-L-45884(PA)
30 May 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

LANCE HANDLING EQUIPMENT

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of handling equipment entitled Lance Handling Equipment used with the Lance warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

9209717 - Sling, Beam Type: H4263.
9209747 - Warhead Section Stand: H4243.
9209748 - Stand Section, Atomic Warhead Section Front, Lance H4243-3.
9209749 - Stand Section, Atomic Warhead Section Rear, Lance: H4243-2.
9209750 - Track, Atomic Warhead Section Stand, Rear, Lance H4243-5.
9209751 - Stand Section Rear Assembly.
9209752 - Track, Atomic Warhead Section Stand, Front Lance H4243-1.
9209753 - Track, Front Frame Assembly.
9209759 - Track, Forward Assembly.
9217516 - Adapter, Hoisting, Warhead H4248.
9220141 - Handling Device, Fuze H4246.
9220142 - Ring, Lifting.
9236848 - Bracket Hoist.
9237218 - Lance Handling Equipment.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

ET-9237218 - Equipment Tabulation.
9252046 - Track, Rear Frame Assembly.
9252047 - Right Track Plate Assembly.
9252050 - Track, Atomic Warhead Section Stand, Rear, Lance H4243-5.
9252057 - Stand, Adaption Kit Subassembly: H4247.
9252063 - Plate Track, Rear.
9252064 - Left Track Plate Assembly.
9252076 - Plate Identification.
9252077 - Locking Block Assembly.
9252684 - Adapter, Warhead Section, Lance: H4247.
9256529 - Ring Subassembly.
9256530 - Ring Assembly.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The Lance handling equipment shall comply with all requirements specified on the drawing (dwg) 9237218, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Lot formation. The formation of an inspection lot and related functions shall be in accordance with Section 5, MIL-STD-105. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.2.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.2.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Warhead section stand: H 4243 (9209747).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect alignment of forward base assembly track to rear base assembly track when jointed by cap screws and nuts.....	Gage/Manual
102.	Incorrect mating of rear face of simulated "D" section and mounting ring (9252684).....	Manual
103.	Misalignment of Locking Block Assembly (9252684) to prevent rotation and indexing or mounting ring (9252684).....	Manual
104.	Inability or undue effort required to pull quick release pins (8).....	Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

105.	Incorrect distance from roller sleeve (in "UP" position) to "C" and "D" interface of forward ballastic case "C" section on forward section stand	Gage
106.	Inability to achieve proper "C" section alignments and rotation with adjusting jacks	Manual
107.	Inability to rotate mated "C" and "D" sections with weight distributed on both forward and aft cart rollers	Manual
108.	The position lock brake on Forward Stand Section Assembly (9209748) does not engage properly (2)	Visual/Manual
109.	The position lock brakes on Rear Stand Section Assembly (9209749) does not engage properly (2)	Visual/Manual
110.	The Rear Stand Section support rollers do not make contact with the simulated case section ballistic rear	Visual
111.	Inability to rotate the simulated case section ballistic rear on the rear support rollers	Manual
112.	Any component, missing, damaged or incorrectly assembled	Visual
113.	Evidence of poor workmanship (see 3.4)	Visual
114.	Protective finish damage (scratches permitted on paint but not through to base metal)	Visual
115.	Stencil markings missing, misleading or unidentifiable	Visual
116.	Hardware loose or missing	Visual
117.	Inability to manually operate attached forward and rear stand sections using either hand crank	Manual
118.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Minor: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

*4.2.2.1.2 Track, atomic warhead section stand, front Lance: H4243-1 (9209752).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Mislocation of track assemblies (2)	Gage
102.	Mislocation of track assembly slots (12) (9209759)	Gage
103.	Mislocation of tapped holes (12)	Gage
104.	Incorrect pitch diameter of tapped holes (12)	Gage
105.	Incorrect overall length (9209753)	Gage
106.	Mislocation of modified gear rack mounting holes (5)	Gage
107.	Mislocation of cap screw holes (2)	Gage
108.	Incorrect diameter of cap screw holes (2)	Gage
109.	Any component missing or improperly assembled	Visual
110.	Protective finish damage exposing base metal (9209753)	Visual
111.	Marking missing, improper, illegible (9209753)	Visual
112.	Evidence of poor workmanship (see 3.4)	Visual
113.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor: None defined.		

*4.2.2.1.3 Stand section, atomic warhead section, rear, Lance: H4243-2 (9209747).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Mislocation of caster wheels (swivel and rigid)(see dwg 9209751) (4)	Gage

*Whenever the H4243 (dwg 9209747) is assembled at point of manufacture, defects for this component may be omitted from inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

102.	Mislocation of caster (grooved) wheels (see dwg 9209751) (4)	Gage
103.	Mislocation of brakes (see dwg 9209751) (2)	Gage
104.	Mislocation of support rollers (see dwg 9209751) (8)	Gage
105.	Misalignment of support rollers (see dwg 9209751) (8)	Gage
106.	Mislocation of plate (9209751-9)	Gage
107.	Incorrect diameter of pin holes in plate (2) (9209751-9)	Gage
108.	Mislocation of pin holes in plate (see dwg 9209751-9)	Gage
109.	Mislocation of locking ring block (see dwg 9209751)	Gage
110.	Inability to freely pull spring to provide return of indexing pin on locking block assembly	Manual
111.	Inability to remove quick release pin from hand crank	Manual
112.	Inability of support rollers to rotate freely (8)	Manual
113.	Undue effort required to turn the drive shaft using hand crank	Manual
114.	Incorrect overall length (see dwg 9209751)	Gage
115.	Incorrect overal width (see dwg 9209751)	Gage
116.	Inability to swivel aft casters	Manual
117.	Inability to operate brakes (2)	Manual
118.	Any component missing or improperly assembled	Visual
119.	Any hardware loose or missing	Visual/Manual
120.	Marking missing, improper or illegible (see dwg 9209751)	Visual
121.	Damage to protective finish exposing base metal (see dwg 9209751)	Visual
122.	Evidence of poor workmanship (see 3.4)	Visual
123.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Minor: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

*4.2.2.1.4 Stand section, atomic warhead section, front, Lance; H4243-3 (see dwg 9209748).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Mislocation of caster wheels (swivel and rigid)(see dwg 9209750) (4)	Gage
102.	Mislocation of caster wheels grooved (see dwg 9209750)(4)	Gage
103.	Mislocation of brakes (see dwg 9209750)(2)	Gage
104.	Undue effort required to turn the drive shaft using hand crank	Manual
105.	Incorrect location of jactuators assembly support channels (see dwg 9209750)	Gage
106.	Incorrect length (less extension support for aft jactuators (see dwg 9209750)	Gage
107.	Incorrect overall width (see dwg 9209750)	Gage
108.	Inability or undue effort required to pull quick release pins for Ballastic Front Tray Assembly, Coupling Block Assembly and Roller Stop Assembly	Manual
109.	Inability or undue effort required to slide front tray assembly forward and aft	Manual
110.	Inability to swivel front casters (2)	Manual
111.	Inability to operate brakes (2)	Manual
112.	Inability or undue effort required to operate jactuators up and down (4)	Manual
113.	Any component missing or improperly assembled	Visual
114.	Marking missing, improper or illegible (see dwg 9209750)	Viaual
115.	Rubber rests not cemented securely (2)	Visual/Manual
116.	Any hardware loose or missing	Visual/Manual

*Whenever the H4243 (dwg 9209747) is assembled at point of manufacture, defects for this component may be omitted from inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

117. Damage to protective finish exposing base metal (see dwg 9209750).....Visual
118. Evidence of poor workmanship (see 3.4).....Visual
119. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor: None defined.

*4.2.2.1.5 Adapter, warhead section, Lance: H4243-4 (see dwg 9252684).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Mislocation of mounting slots (4)	Gage
102.	Incorrect width of mounting slots (4)	Gage
103.	Mislocation of numbered positioning slots (4)	Gage
104.	Incorrect width of numbered position slots (4)	Gage
105.	Mislocation of alignment pin holes (2)	Gage
106.	Incorrect diameter of alignment pin holes (2)	Gage
107.	Incorrect inside diameter of ring lip	Gage
108.	Damage to protective finish exposing base metal	Visual
109.	Marking missing, incorrect or illegible	Visual
110.	Evidence of poor workmanship (see 3.4)	Visual
111.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

*Whenever the H4243 (dwg 9209747) is assembled at point of manufacture, defects for this component may be omitted from inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

*4.2.2.1.6 Track, atomic warhead section stand, rear, Lance: H4243-5 (see dwg 9252050).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Mislocation of track assemblies (left and right)	Gage
102.	Mislocation of track assembly slots (12) (see dwg 9252063)	Gage
103.	Mislocation of tapped holes (12)	Gage
104.	Incorrect pitch diameter of tapped holes (12)	Gage
105.	Mislocation of aft end cap screws (2) (see dwg 9252046)	Gage
106.	Incorrect overall length (see dwg 9252046)	Gage
107.	Mislocation of forward stop wheel bracket (2)(see dwg 9252064 and 9252047)	Gage
108.	Undue effort required to pull forward end cap screws (2)	Manual
109.	Any component missing or improperly assembled	Visual
110.	Any hardware loose or missing	Visual/Manual
111.	Protective finish damage exposing base metal (see dwg 9252064 and 9252047)	Visual
112.	Identification missing, improper, or illegible (see dwg 9252076)	Visual
113.	Evidence of poor workmanship (see 3.4)	Visual
114.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

*Whenever the H4243 (dwg 9209747) is assembled at point of manufacture, defects for this component may be omitted from inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

4.2.2.1.7 Stand, adaption kit sub-assembly: H4247 (see dwg 9252057).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Undue effort to rotate ring assembly through 8 index positions	Manual
102.	Inability to lock ring assembly at each of the 8 positions	Manual
103.	Incorrect position of collar	Gage
104.	Incorrect depth of counterbore holes (4) (see dwg 9256530)	Gage
105.	Incorrect length of shafts (2) (see dwg 9256530)	Gage
106.	Incorrect location of cover mounting holes (4) (see dwg 9256529)	Gage
107.	Protective finish damaged exposing base metal	Visual
108.	Marking missing, improper or illegible	Visual
109.	Evidence of poor workmanship (see 3.4)	Visual
110.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.2.2.1.8 Handling device, fuze: H4246 (see dwg 9220141).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect location of through holes (4) (see dwg 9220142)	Gage
102.	Component parts missing or loose	Visual/Manual
103.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

4.2.2.1.9 Sling, beam type: H4263 (see dwg 9209717).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect location of mounting holes (4)(see dwg 9236848)	Gage
102.	Component parts missing or loose	Visual
103.	Protective finish damaged or exposing base metal	Visual
104.	Evidence of poor workmanship (see 3.4)	Visual
105.	Marking missing, illegible or incorrect	Visual
106.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.2.2.1.10 Adapter, hoisting, warhead: H4248 (see dwg 9217516).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Inability to freely turn rods to adjust hook height up and down	Manual
102.	Inability to snap latch	Manual
103.	Component parts missing or loose	Visual
104.	Protective finish damaged or exposing base metal	Visual
105.	Evidence of poor workmanship (see 3.4)	Visual
106.	Marking missing, illegible or incorrect	Visual
107.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

4.2.2.1.11 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packing and packaging not in accordance with MIL-STD-1169(MU)	Visual
102.	Marking not in accordance with MIL-STD-1169(MU)	Visual
103.	Evidence of poor workmanship (see 3.4)	Visual
Minor:	None defined.	

4.3.1 Acceptance inspection equipment.

4.3.1.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). Els for assemblies are listed on the Equipment Tabulation, ET-9237218. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified onthe EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The Lance handling equipment shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The Lance handling equipment shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The Lance handling equipment shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.1.1). Data specified in 4.3.1.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.1.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1241 Amendment 2 dated 14 September 1972.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1190-A096

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. *Fold on lines on reverse side, staple in corner,* and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04Z
Check the source to verify that this is the current version before use.