MILITARY SPECIFICATION

MOUNT, SHIPPING CONTAINER, RESILIENT: SHOCK AND VIBRATION DAMPING

This amendment forms a part of Military Specification MIL-M-45907A(AT), dated 13 December 1984, and is approved for use within the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, add:

"FEDERAL

FED-STD-H28/2A - Screw-Thread Standards For Federal Services Section 2 Unified Inch Screw Threads - UN and UNR Thread Forms."

2.1.2, delete paragraph in its entirety.

PAGE 3

3.3.3, line 2, delete "NBS Handbook H28" and substitute: "FED-STD-H28/2A".

PAGE 4

3.4.2.3, lines 3 and 4, delete "12 gravity units" and substitute: "15 gravity units".

3.4.3.2, line 3, delete "25" and substitute: "35".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:08Z
Check the source to verify that this is the current version before use.

PAGE 9

4.6.3.1, line 2, after "3.4.2.2" delete "with".

4.6.3.1, line 2, after "mounts" add a comma.

4.6.4, line 7, delete "12" and substitute: "15".

PAGE 10

4.6.6.2, line 1, delete "with".

4.6.6.2, line 2, after "mounts" add a comma.

4.6.6.2, lines 5 and 6, delete "or within 30 seconds after removal therefrom" and substitute: "or immediately upon removal therefrom".

4.6.6.2, line 7, delete "25" and substitute: "35".

4.6.6.3, line 1, delete "with".

4.6.6.3, line 2, after "mounts" add a comma.

4.6.6.3, line 2, delete "prepare for test" and substitute: "prepared".

4.6.6.3, line 7, delete "12" and substitute: "15".

5.1, line 2, delete "desire" and substitute: "desired".

Add new paragraph 6.5:

"6.5 Subject term (key word) listing.

Shipping container, shock and vibration mount
Shock and vibration mount, shipping container for"

Custodian:
Army - AT

Review activity:
DLA - IS

Preparing activity:
Army - AT

(Project 5340-A039)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:08Z
Check the source to verify that this is the current version before use.