MILITARY SPECIFICATION

RELEASE, TWO POINTS - SINGLE PULL, PARACHUTIST'S EQUIPMENT PACK

This amendment forms a part of MIL-R-45906D(GL), dated 22 May 1984, and is approved for use within the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.4.1.1, line 1: Change "relazation" to "relaxation".

PAGE 6

4.4.2, line 1: Change "compoents" to "components".

Add the following new paragraph:

"4.4.2.1 Critical defect examination of end items. Prior to performing the end item sampling examination required in 4.4.3, the releases shall be 100 percent examined for the critical defect listed in table I. This 100 percent critical defect examination shall become a part of the contractor's inspection system or quality program. Any release found to contain a critical defect shall be rejected."

4.4.3, line 7: Add the following sentence. "During this examination, any sample unit found to contain the critical defect listed below shall be cause for rejection of the lot."

PAGE 7

4.4.3: Table I, in column headings under "Classification", add "Critical".

At end of Table I, add the following new entry:

"Release fastener assembly	End of pin housing not stacked or peened, or not stacked or peened to retain pin.	Critical"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:08Z
Check the source to verify that this is the current version before use.

5.3: Delete and substitute:

"5.3 Palletization. When specified (see 6.2) releases, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia, as applicable, of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K or L, or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer."

6.3, line 2: Change "DAR 7-104.55" to "FAR 52.209".

Custodian:

Army - GL

Review activity:

DLA - IS

Preparing activity:

Army - GL

Project No. 5340-A040

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:08Z
Check the source to verify that this is the current version before use.