INCH-POUND

MIL-S-45909C
SUPPLEMENT 1
27 March 1989

MILITARY SPECIFICATION

STUD, LOCKED IN, RING LOCKED, SERRATED, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-S-45909C, dated 27 March 1989.

MS STANDARDS

MS51497 - Stud, Locked in - Ring Locked, Serrated, High Strength, Oversize Replacer
MS51551 - Stud, Locked in - Ring Locked, Serrated, UNJF Thread Nut End, Increased Stud End Length
MS51989 - Stud, Locked in - Ring Locked, Serrated
MS51990 - Ring, Lock, Serrated
MS51992 - Stud, Locked in - Ring Locked, Serrated
MS51994 - Hole Preparation - Ring Locked Inserts and Studs, Standard Dimensions for
MS51995 - Fasteners, Ring Locked - Inserts and Studs, Installation of
MS51996 - Hole Preparation - Ring Locked Inserts and Studs, High Strength, Standard Dimensions for
MS51997 - Ring, Lock, Serrated - High Strength

Preparing activity:
Army - AR

AMSC N/A

FSC 5307

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.