MIL-T-45890A(AR)
4 February 1982
Superseding
MIL-T-45890(PA)
23 June 1975

MILITARY SPECIFICATION

TOOLS FOR PROJECTILE, M422

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions, and the preparation for delivery for tools used on 8 inch Projectile, M422.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.4), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

FEDERAL

Federal Test Method Standard No.151.	Metals: Test Method

MILITARY

MIL-STD-1188	Commercial Packaging of Supplies and Equipment

NO DELIVERABLE DATA
REQUIRED BY THIS DOCUMENT

NUOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

MIL-STD-1169 Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ARRADCOM

7231161	-	Wrench, Fuze T12E1 (M18)
8592962	-	Fuze Setter Assembly, H-4003
8787024	-	Fixture, Dashpot Assembling & Filling
8787025	-	Compressor, Ring
8787026	-	Base
8787043	-	Plate Bottom
8787175	-	Pin Filling
8787605	-	Wrench, Detent H-4115
8787614	-	Gage, Flush Pin T-4075-1
8787616	-	Case, Gage Installation T-4075-2
8787626	-	Wrench, Spanner H-4011
8787869	-	Creep Stop Setting Tool T-4076
8787870	-	Wrench Spanner H-4111
8787873	-	Tool Adjusting H-4113
8787874	-	Wrench Spanner H-4007
8787879	-	Handle Assembly
8787882	-	Sleeve
8787884	-	Wrench, Spanner H-4009
8787887	-	Wrench, Spanner H-4004
8787890	-	Wrench, Spanner H-4005
8787891	-	Wrench, Spanner H-4129
8787892	-	Handle
8787893	-	Pin
8787894	-	Wrench, Spanner H-4008
8787895	-	Wrench, Spanner H-4006
8794334	-	Inserter, Spring Pin H-4021
8794359	-	Maintenance Fixture Atomic Warhead H4001
8794385	-	Post Center
8794387	-	Spring
8794393	-	Post Assembly
8794598	-	Tool Insert Removal H4020
8795637	-	Tool Holding H4112
8848825	-	Test and Handling Equipment, Atomic Weapon
9253873	-	Plug

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Tools. The tools shall comply with all requirements specified on the drawings listed in paragraph 2.1 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 First Article Inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Spring distortion. The springs shall comply with all requirements on dwg 8794387 and shall withstand a tension load test as specified in 4.4.2.

3.5 Welds. The welds shall be complete, of uniform size, width, smoothness and reinforcement, and shall show no evidence of pock marks, slag pockets, gas pipes porosity, overlaps, or undercuts. There shall be no visible evidence of cracks or separations in the weld metal or base metal.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

herein or in the contract, the provisions of MIL-A-48078 shall apply and are thereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part description	Drawing no.	Quantity
Wrench, Fuze T12E1(M18)	7231161	1
Fuze Setter Assembly, H-4003	8592962	3
Fixture, Dashpot Assembling and Filling	8787024	3
Pin, Filling	8787175	1
Wrench, Detent H-4115	8787605	1
Gage, Flush Pin T-4075-1	8787614	3
Case, Flush Pin Gage T4075-2	8787616	1
Wrench Spanner H-4011	8787626	1
Creep Stop Setting Tool T4076	8787869	3
Wrench, Spanner H-4111	8787870	1
Tool, Adjusting H-4113	8787873	1
Wrench, Spanner H-4007	8787874	1
Wrench, Spanner H-4009	8787884	1
Wrench, Spanner H-4004	8787887	1
Wrench, Spanner H-4005	8787890	1
Wrench, Spanner H-4129	8787891	1
Wrench, Spanner H-4008	8787894	1
Wrench, Spanner H-4006	8787895	1
Inserter, Spring Pin H-4021	8794334	1
Maintenance Fixture, Atomic Warhead H-4001	8794359	3
Tool, Insert Removal H-4020	8794598	1
Tool, Handling H-4112	8795637	1
Plug	9253873	1

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Inspection equipment. The inspections and test specified in 4.4.2 shall be accomplished with the gages and test equipment specified in 4.4.4.

4.3.4 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

TABLE I.
FIRST ARTICLE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
	Tools for Projectile, M422		1 OF 4	See Below
				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Wrench, Fuze T12E1 (M18) (Dwg. 7231161) Examination for Defects	1	-	3.2	4.4.2.1
	Fuze Setter Assembly, M4003 (Dwg. 8592962) Examination for Defects	3	-	3.2	4.4.2.2
	Fixture, Dashpot Assembling and Filling (Dwg. 8787024) Examination for Defects	3	-	3.2	4.4.2.3 4.4.2.4 4.4.2.5
	Pin Filling (Dwg. 8787175) Examination for Defects	1	-	3.2	4.4.2.6
	Wrench Detent H-4115 (Dwg. 8787605) Examination for Defects	1	-	3.2	4.4.2.7
	Gage, Flush Pin T-4075-1 (Dwg. 8787614) Examination for Defects	3	-	3.2	4.4.2.8

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

TABLE I.

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Tools For Projectile, M422		SHEET 2 OF 4		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Case, Flush Pin Gage T4075-2 (Dwg. 878616) Examination for Defects	1	-	3.2	4.4.2.9
	Wrench Spanner H-4011 (Dwg. 8787626) Examination for Defects	1	-	3.2	4.4.2.10
	Creep Stop Setting Tool T4076 (Dwg. 8787869) Examination for Defects	3	-	3.2	4.4.2.11 4.4.2.15 4.4.2.16
	Wrench, Spanner H-4111 (Dwg. 8787870) Examination for Defects	1	-	3.2	4.4.2.12
	Tool, Adjusting H-4113 (Dwg. 8787873) Examination for Defects	1	-	3.2	4.4.2.13
	Wrench, Spanner H-4007 (Dwg. 8787874) Examination for Defects	1	-	3.2	4.4.2.14

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

TABLE I.
FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
	Tools For Projectile, M422		3 OF 4		See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Wrench, Spanner H-4009 (Dwg. 8787884) Examination for Defects	1	-	3.2	4.4.2.17
	Wrench, Spanner H-4004 (Dwg. 8787887) Examination for Defects	1	-	3.2	4.4.2.18
	Wrench, Spanner H-4005 (Dwg. 8787890) Examination for Defects	1	-	3.2	4.4.2.19
	Wrench, Spanner H-4129 (Dwg. 8787891) Examination for Defects	1	-	3.2	4.4.2.20 4.4.2.21 4.4.2.22
	Wrench, Spanner H-4008 (Dwg. 8787894) Examination for Defects	1	-	3.2	4.4.2.23
	Wrench, Spanner H-4006 (Dwg. 8787895)	1	-	3.2	4.4.2.24
	Inserter, Spring Pin H-4021 (Dwg. 8794334) Examination for Defects	1	-	3.2	4.4.2.25

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

TABLE I.
FIRST ARTICLE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
	Tools For Projectile, M422				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Maintenance Fixture, Atomic Warhead H-4001 (Dwg. 8794359) Examination for Defects	3	-	3.2	4.4.2.26 4.4.2.27 4.4.2.28 4.4.2.29
	Tool, Insert Removal H-4020 (Dwg. 8794598) Examination for Defects	1	-	3.2	4.4.2.30
	Tool, Holding H-4112 (Dwg. 8795637) Examination for Defects	1	-	3.2	4.4.2.31
	Plug (Dwg. 9253873) Examination for Defects	1	-	3.2	4.4.2.32

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lot shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078 and the Quality Conformance Inspection Tables herein.

a. Major defect sampling plans. Unless otherwise specified, inspection for major defects shall be sampled in accordance with Table II.

b. Minor defect sampling plans. Unless otherwise specified, inspection for minor defects shall be sampled in accordance with Table III.

Table II. Major Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III. Minor Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Wrench, Fuze, T12E1 (M18)		7231161
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Torque Test	(a)		3.2	Gage/8815262
102.	Profile of throat	(a)		3.2	Gage/8803623
103.	Length of point	(a)		3.2	Gage/8803624
104.	Width of point	(a)		3.2	Gage/8803624
105.	Thickness of point	(a)		3.2	Gage/8803624
106.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Profile of point	(b)		3.2	Gage/8803624
202.	Total length	(b)		3.2	Gage/5210-220-4560
203.	Width of handle	(b)		3.2	Gage/5210-222-4559
204.	Large outside width	(b)		3.2	Gage/5210-222-4559
205.	Protective finish damaged exposing base metal	(b)		3.2	Visual
206.	Marking illegible	(b)		3.2	Visual
207.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8592962
4.4.2.2	Fuze Setter Assembly, H-4003				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Any component missing, loose or damaged	(a)		3.2	Visual/Manual
Minor					
201.	Marking illegible	(b)		3.2	Visual
202.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Compressor, Ring	1 OF 1	8787025
			NEXT HIGHER ASSEMBLY: 8787024

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
Major					
101.	Inside diameter	(a)		3.2	Gage/7284907
102..	Outside diameter	(a)		3.2	Gage/5210-790-0239
103.	Angle of taper	(a)		3.2	Gage/8815315 & 8815410
104.	Interior finish improper	(a)		3.2	Visual
Minor					
201.	Length to tapered surface	(b)		3.2	Gage/8815316
202.	Length	(b)		3.2	Gage/5210-222-4559
203.	Profile of curved bottom	(b)		3.2	Gage/8815317
204.	Protective finish damaged exposing base metal	(b)		3.2	Visual
205.	Evidence of poor workmanship	(b)		3.6	Visual
206.	Marking illegible	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Base		8787026
			NEXT HIGHER ASSEMBLY 8787024

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Inside diameter	(a)		3.2	Gage/5210-790-2526
102.	Diameter of counterbore	(a)		3.2	Gage/5210-790-0368
103.	Depth of counterbore	(a)		3.2	Gage/5210-221-1961
104.	Length	(a)		3.2	Gage/5210-222-4559
Minor					
201.	Finish incorrect	(b)		3.2	Visual
202.	Protective finish damaged exposing base metal	(b)		3.2	Visual
203.	Marking illegible	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assistdocs.com - Downloaded: 2026-10-22T04:00Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8787043
4.4.2.5	Plate, Bottom				NEXT HIGHER ASSEMBLY 8787026
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Length to base	(a)		3.2	Gage/5210-274-2861
102.	Diameter of base	(a)		3.2	Gage/5210-222-4559
103.	Profile at end of shaft	(a)		3.2	Gage/8815318
104.	Diameter of shaft	(a)		3.2	Gage/8815318
Minor					
201.	Finish improper	(b)		3.2	Visual
202.	Protective finish damaged exposing base metal	(b)		3.2	Visual
203.	Evidence of poor workmanship	(b)		3.6	Visual
204.	Marking illegible	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-27T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Pin Filling	1 OF 1	8787175
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201.	Small outside diameter	(b)		3.2	Gage/5210-790-0238
202.	Large outside diameter	(b)		3.2	Gage/5210-790-0238
203.	Length to shoulder (max)	(b)		3.2	Gage/5210-274-2861
204.	Total length (min)	(b)		3.2	Gage/5210-790-0238
205.	Protective finish damaged exposing base metal	(b)		3.2	Visual
206.	Finish improper	(b)		3.2	Visual
207.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:

(b) Sample size see Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE			SHEET 1 OF 2	DRAWING NUMBER
4.4.2.7	Wrench, Detent H-4115				8787605
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Pitch diameter of small thread on handle assembly	(a)		3.2	Gage/5220-751-4644 5220-751-4645 5220-751-4646 5220-751-4647 5220-751-5448 5220-751-5449 5220-751-5450 5220-751-5451
102.	Major diameter of small thread on handle assembly	(a)		3.2	Gage/5220-747-9460
103.	Pitch diameter of large thread on handle assembly (min)	(a)		3.2	Gage/5220-751-5448 thru 5551
104.	Major diameter of large thread on handle assembly (min)	(a)		3.2	Gage/5220-747-9462
105.	Length to end of large thread on handle assembly (min)	(a)		3.2	Gage/8803593
106.	Length to start of large thread on handle assembly	(a)		3.2	Gage/5210-274-2861
107.	Pitch diameter of wing nut thread (max)	(a)		3.2	Gage/5220-751-4220

NOTES:

(a) Sample size per Table II

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-27T04:06Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.7 (cont)	Wrench, Detent H-4115				8787605
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major (cont)					
108.	Minor diameter of wing nut thread (max)	(a)		3.2	Gage/5220-746-0120
109.	Profile of bottom contour of wing nut	(a)		3.2	Gage/8803392
110.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Protective finish damaged exposing base metal	(b)		3.2	Visual
202.	Marking illegible	(b)		3.2	Visual
203.	Handle loose	(b)		3.2	Manual
204.	Pin loose	(b)		3.2	Manual
205.	Any operation missing	(b)		3.2	Visual
206.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.8	Gage Flush Pin T-4075-1				8787614
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Protrusion of pin with opposite end flush		100%	3.2	Gage/7284949 /5210-229-9518
2	Depth to face of holder flange with opposite end flush		100%	3.2	Gage/7284949
Major					
101.	Outside diameter of fingers	(a)		3.2	Gage/5210-220-1934 5210-221-2076
102.	Inside diameter of fingers	(a)		3.2	Gage (c)/5210-221-1934
103.	Depth of cavity inside fingers (min)	(a)		3.2	Gage (c)/5210-790-1836
104.	Thickness of holder flange (max)	(a)		3.2	Gage(c)/5210-222-4559
105.	Holder not free in body	(a)		3.2	Manual
106.	Pin not free in holder	(a)		3.2	Manual
Minor					
201.	Total length (max)	(b)		3.2	Gage/7284949 8815319

NOTES:
(a) Sample size per Table II, (b) Sample size per Table III, (c) To be checked after disassembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-29T04:40Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.8 (cont)	Gage Flush Pin T-4075-1				8787614
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor (cont)					
202.	Width of fingers	(b)		3.2	Gage/5210-222-4559
203.	Profile between fingers	(b)		3.2	Visual
204.	Protective finish damaged exposing base metal	(b)		3.2	Visual
205.	Finish incorrect	(b)		3.2	(c) Visual
206.	Marking illegible	(b)		3.2	Visual
207.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II, (b) Sample size per Table III, (c) To be checked after disassembly

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Case, Flush Pin Gage T-4075-2		8787616
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Inability of box to accept simulated gage (functional)	(a)		3.2	Gage/8815320
Minor					
201.	Height (max)	(b)		3.2	Gage/5210-222-4560
202.	Length over hardware	(b)		3.2	Gage/5210-222-4560
203.	Marking illegible	(b)		3.2	Visual
204.	Any component missing	(b)		3.2	Visual
205.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:

(a) Sample size per Table II

(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Wrench, Spanner H-4011				8287626
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Pitch diameter of nut thread (max)	(a)		3.2	Gage/8781653 8781654
102.	Major diameter of nut thread (min)	(a)		3.2	Gage/5220-747-9374
103.	Location of pins (functional)	(a)		3.2	Gage/8815321
104.	Protrusion of pins	(a)		3.2	Gage/5210-274-1961
105.	Length of nut thread pilot (max)	(a)		3.2	Gage/5210-274-2861
106.	Handle or plate weld insecure	(a)		3.2	Manual
107.	Knob and shaft assembly bound	(a)		3.2	Manual
108.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Length of handle	(b)		3.2	Gage/5210-222-4560
202.	Width of handle	(b)		3.2	Gage/5210-222-4560
203.	Length of plate	(b)		3.2	Gage/5210-222-4559
204.	Width of plate	(b)		3.2	Gage 5210-222-4559
205.	Marking illegible	(b)		3.2	Visual
206.	Protective finish damaged exposing base metal	(b)		3.2	Visual
207.	Any component missing	(b)		3.2	Visual
208.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22 04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.11	Creep Stop Setting Tool T-4076		8287869
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Small outside diameter of sleeve (max)	(a)		3.2	Gage/5210-250-0867
102.	Large outside diameter of sleeve (max)	(a)		3.2	Gage/5210-250-0867
103.	Concentricity of large outside diameter of sleeve with small outside diameter	(a)		3.2	Gage/8815322
104.	Length of sleeve (min)	(a)		3.2	Gage/5210-222-4560
105.	Length to large outside diameter of sleeve (max)	(a)		3.2	Gage/5210-224-2861
106.	Total length (max)	(a)		3.2	Gage/3460-529-1379 Gage/5210-239-8570 Gage/5210-790-2354
107.	Handle assembly loose in sleeve	(a)		3.2	Visual
Minor					
201.	Inside diameter of sleeve	(b)		3.2	Gage/5210-790-0368
202.	Protective finish damaged exposing base metal	(b)		3.2	Visual
203.	Stake missing	(b)		3.2	Visual
204.	Nut protrudes above sleeve	(b)		3.2	Visual
205.	Any operation missing	(b)		3.2	Visual
206.	Marking illegible	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.11 (cont)	Creep Stop Setting Tool T-4076				8287869
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
207.	Finish incorrect	(b)		3.2	Visual
208.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Wrench, Spanner H-4111	1 OF 1	8787870
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter of hole	(a)		3.2	Gage/5210-790-2546 /5210-221-1930
102.	Concentricity of hole with outside diameter of pin (functional)	(a)		3.2	Gage/8815323
103.	Diameter of pin (max)	(a)		3.2	Gage/5210-790-0238
104.	Length of pin (min)	(a)		3.2	Gage/5210-274-2861
105.	Protrusion of lip on pin	(a)		3.2	Gage/5210-274-2861
106.	Width of lip on pin	(a)		3.2	Gage/5210-222-4559
107.	Location of lip	(a)		3.2	Gage/8815324
108.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Length of handle	(b)		3.2	Gage/5210-222-4560
202.	Angle of handle wings (functional)	(b)		3.2	Gage/5210-273-9869
203.	Marking illegible	(b)		3.2	Visual
204.	Any operation missing	(b)		3.2	Visual
205.	Finish incorrect	(b)		3.2	Visual
206.	Evidence of poor workmanship (see 3.6)	(b)		3.2	Visual
207.	Protective finish damged exposing base metal	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Tool, Adjusting, H-4113				8787873
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Profile of angle at point	(a)		3.2	Gage/8815325
102.	Width of blade	(a)		3.2	Gage/8815325
103.	Diameter of shank	(a)		3.2	Gage/5210-790-0238
104.	Length of blade (min)	(a)		3.2	Gage/8815325
105.	Length of shank (min)	(a)		3.2	Gage/5210-274-2861
106.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Marking illegible	(b)		3.2	Visual
202.	Evidence of poor workmanship (see 3.6)	(b)		3.2	Visual
203.	Protective finish damaged exposing base metal	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Wrench, Spanner H-4007	1 OF 1	8287874
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Location of pins (functional)	(a)		3.2	Gage/8815493
102.	Protrusion of pins	(a)		3.2	Gage/5210-221-1961
103.	Diameter of pins (max)	(a)		3.2	Gage/5210-790-0238
104.	Weld inadequate	(a)		3.5	Visual
105.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Width of pin plate	(b)		3.2	Gage/5210-222-4559
202.	Length of pin plate	(b)		3.2	Gage/5210-222-4559
203.	Length of handle	(b)		3.2	Gage/5210-222-4559
204.	Any operation missing	(b)		3.2	Visual
205.	Protective finish damaged exposing base metal	(b)		3.2	Visual
206.	Marking illegible	(b)		3.2	Visual
207.	Evidence of poor workmanship	(b)		3.6	Visual
208.	Any component loose	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Handle Assembly	1 OF 1	8287879
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Pitch diameter of thread (min)	(a)		3.2	Gage/5220-751-6248 5220-751-6249
102.	Major diameter of thread (min)	(a)		3.2	Gage/5220-747-9398
Minor					
201.	Thickness of nut	(b)		3.2	Gage/5210-790-0238
202.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.16	Sleeve		8287882
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Pitch diameter of thread (max)	(a)		3.2	Gage/5220-751-4552
102.	Minor diameter of thread (max)	(a)		3.2	Gage/5220-751-6753
103.	Depth of thread (min)	(a)		3.2	Gage/8828852
Minor					
201.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Wrench, Spanner H-4009	1 OF 1	8787884
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Protrusion of pins	(a)		3.2	Gage/5210-221-1961
102.	Location of pins (functional)	(a)		3.2	Gage/8815326
103.	Diameter of pins	(a)		3.2	Gage/5210-221-1930
104.	Pin loose	(a)		3.2	Manual
105.	Weld inadequate	(a)		3.5	Visual
106.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Protective finish damaged exposing base metal	(b)		3.2	Visual
202.	Any operation missing	(b)		3.2	Visual
203.	Marking illegible	(b)		3.2	Visual
204.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample per size Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.18	TITLE Wrench, Spanner H-4004		SHEET 1 OF 1		DRAWING NUMBER 8287887 / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Length of pin protrusion	(a)		3.2	Gage/5210-221-1961
102.	Location of pins (functional)	(a)		3.2	Gage/8815328
103.	Component or operation missing	(a)		3.2	Visual
104.	Weld inadequate	(a)		3.5	Visual
105.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Length of handle	(b)		3.2	Gage/5210-222-4560
202.	Marking illegible	(b)		3.2	Visual
203.	Protective finish damaged exposing base metal	(b)		3.2	Visual
204.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.19	TITLE Wrench, Spanner H-4005		SHEET 1 OF 1		DRAWING NUMBER 8787890
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Inside radius of jaws	(a)		3.2	Gage/5210-222-4559
102.	Thickness of lip	(a)		3.2	Gage/5210-790-0238
103.	Opening between jaw (min)	(a)		3.2	Gage/8815329
104.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Profile of handle (functional)	(b)		3.2	Gage/5210-239-0490
202.	Overall length	(b)		3.2	Gage/5210-790-2494
203.	Protective finish damaged exposing base metal	(b)		3.2	Visual
204.	Marking illegible	(b)		3.2	Visual
205.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Wrench, Spanner H-4129	1 OF 1	8787891
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Protrusion of pin	(a)		3.2	Gage/5210-221-1961
102.	Profile between jaws	(a)		3.2	Gage/8815333
103.	Location of pins (functional)	(a)		3.2	Gage/8815331
104.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Thickness of handle (min)	(b)		3.2	Gage/5210-222-4559
202.	Profile of handle (functional)	(b)		3.2	Gage/5210-239-0490
203.	Evidence of poor workmanship	(b)		3.6	Visual
204.	Any operation missing	(b)		3.2	Visual
205.	Marking illegible	(b)		3.2	Visual
206.	Protective finish damaged exposing base metal	(b)		3.2	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Handle	1 OF 1	8787892
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter of holes (max)	(a)		3.2	Gage/8815332
Minor					
201.	None defined				

NOTES: (a) Sample size per Table II

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.22	Pin	1 OF 1	8787893
			NEXT HIGHER ASSEMBLY 8787891

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter (min)	(a)		3.2	Gage/5210-221-1930
102.	Length (min)	(a)		3.2	Gage/5210-790-0238
Minor	None defined				

NOTES:
(a) Sample size per Table II

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.23	Wrench, Spanner H-4008				8787894
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Length of lug (max)	(a)		3.2	Gage/5210-274-2861
102.	Location of lugs (functional)	(a)		3.2	Gage/8815334
103.	Outside diameter of body	(a)		3.2	Gage/5210-790-0239
104.	Inside diameter of body	(a)		3.2	Gage/5210-221-2087
105.	Width of lug	(a)		3.2	Gage/5210-790-0239
106.	Depth of body cavity (min)	(a)		3.2	Gage/5210-790-0238
107.	Width across flats of nut (functional)	(a)		3.5	Gage/5210-274-2861
108.	Weld inadequate	(a)		3.2	Gage/8815349
109.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Total length (max)	(b)		3.2	Gage/5210-222-4559
202.	Protective finish damaged exposing base metal	(b)		3.2	Visual
203.	Marking illegible	(b)		3.2	Visual
204.	Evidence of poor workmanship	(b)		3.5	Visual
205.	Nut insecure	(b)		3.2	Manual

NOTES:

(a) Sample size per Table II

(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8787895
4.4.2.24	Wrench, Spanner H-4006				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Outside diameter of disc	(a)		3.2	Gage/5210-233-9167
102.	Width of lug (functional)	(a)		3.2	Gage/8815335
103.	Length of lug	(a)		3.2	Gage/5210-790-0238
104.	Protrusion of lug (functional)	(a)		3.2	Gage/8815335
105.	Height of disc	(a)		3.2	Gage/5210-790-0230
106.	Weld inadequate	(a)		3.5	Visual
107.	Hardness	(a)		3.2	4.5.1
Minor					
201.	Length of handle	(b)		3.2	Gage/5210-222-4560
202.	Protective finish damaged exposing base metal	(b)		3.2	Visual
203.	Marking illegible	(b)		3.2	Visual
204.	Any component or operation missing	(b)		3.2	Visual
205.	Any component loose	(b)		3.2	Manual
206.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Inserter, Spring Pin H-4021	1 OF 1	8794334
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter of hole	(a)		3.2	Gage/5220-742-0412 Gage/5220-745-8334
102.	Depth of hole	(a)		3.2	Gage/8815336
103.	Location of hole	(a)		3.2	Gage/8815537
104.	Outside diameter	(a)		3.2	Gage/5210-790-0238
Minor					
201.	Total length (min)	(b)		3.2	Gage/5210-222-4559
202.	Marking illegible	(b)		3.2	Visual
203.	Protective finish damaged exposing base metal	(b)		3.2	Visual
204.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Maintenance Fixture Atomic Warhead H-4001	1 OF 2	8794359
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Outside diameter of cylinder	(a)		3.2	Gage/5210-223-9166
102.	Inside diameter of cylinder (min)	(a)		3.2	Gage/5210-790-0368
103.	Outside diameter of center post guide	(a)		3.2	Gage/5210-223-9167
104.	Diameter of base end of post (min)	(a)		3.2	Gage/5210-790-0238
105.	Length of cylinder	(a)		3.2	Gage/5210-267-4899
106.	Diameter of large cavity in base	(a)		3.2	Gage/8815347
107.	Ball on depressor assembly bound	(a)		3.2	Manual
Minor					
201.	Pitch diameter of thread on positioning screw (min)	(b)		3.2	Gage/5220-751-5632 Gage/5220-751-5633
202.	Major diameter of thread on positioning screw (min)	(b)		3.2	Gage/5220-747-9464
203.	Diameter of small cavity in base	(b)		3.2	Gage/8815348
204.	Thickness through bottom of large cavity	(b)		3.2	Gage/7152985
205.	Depth of small cavity	(b)		3.2	Gage/5210-221-1961
206.	Pitch diameter of positioning screw thread in positioning plate (max)	(b)		3.2	Gage/5220-751-4244
207.	Minor diameter of positioning screw thread in positioning plate (max)	(b)		3.2	Gage/5220-746-1810

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.26 (cont)	Maintenance Fixture Atomic Warhead H-4001				8794359
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor (cont)					
208.	Positioning handle loose	(b)		3.2	Manual
209.	Protective finish damaged exposing base metal	(b)		3.2	Visual
210.	Marking illegible	(b)		3.2	Visual
211.	Any component or operation missing	(b)		3.2	Visual
212.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil - Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8794385
4.4.2.27	Post Center				NEXT HIGHER ASSEMBLY 8794359
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Location of collar pin hole	(a)		3.2	Gage/8815342
102.	Location of guide pin holes	(a)		3.2	Gage/8815343
103.	Location of base pin hole	(a)		3.2	Gage/8815344
Minor					
201.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.28	Spring	1 OF 2	8794387
			NEXT HIGHER ASSEMBLY 8794359

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Lot Size — Sample Size 2-8 — 1 9-15 — 2 16-25 — 3 26-40 — 5 41-65 — 8 66-110 — 13 111-180 — 22 181-300 — 36 301 and over — MIL-STD-105 (AQL 0.25 percent)				
Critical	None defined				
Major					
101.	Test load at height of 0.81 inches (min)	(a)		3.4	4.5.2/6510948
102.	Load at 0.61 inches (max)	(a)		3.4	4.5.2/8829086
103.	Solid height (max)	(b)		3.2	Gage/8829087
104.	Outside diameter (max)	(b)		3.2	Gage/5210-790-0239
105.	Inside diameter (min)	(b)		3.2	Gage/5220-743-7276

NOTES: (a) Sample size shall be selected in accordance with lot size table listed in Examination or Test column.
(b) Sample size per Table II

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.28 (cont)	Spring				8794387
					NEXT HIGHER ASSEMBLY
					8794359
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201.	Spring ends not squared and ground	(c)		3.2	Visual
202.	Protective finish damaged exposing base metal	(c)		3.2	Visual
203.	Evidence of poor workmanship	(c)		3.6	Visual

NOTES:

(c) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.29	Post Assembly		8794393
			NEXT HIGHER ASSEMBLY
			8794359

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Burr on cylinder		100%	3.2	Visual
Major					
101.	Minor diameter of post thread in depressor (max)	(a)		3.2	Gage/8815346
102.	Pitch diameter of post thread in depressor (max)	(a)		3.2	Gage/8815345
103.	Major diameter of depressor thread on post	(a)		3.2	Gage/5220-747-9366
104.	Pitch diameter of depressor thread on post	(a)		3.2	Gage/8815338 Thru 8815341
105.	Length of depressor thread on post (min)	(a)		3.2	Gage/8815415
106.	Total length of center post (min)	(a)		3.2	Gage/5210-222-4564
Minor					
201.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-04-22T10:47:54
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8794598
4.4.2.30	Tool Insert Removal H-4020				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201.	Handle cracked or split	(b)		3.2	Visual
202.	Suction cup torn or perforated	(b)		3.2	Visual
203.	Coating missing	(b)		3.2	Visual
204.	Marking illegible	(b)		3.2	Visual
205.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(b) Sample size per Table II

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: http://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-45890A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.31	Tool, Holding H-4112	1 OF 1	8795637
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter of tip (min)	(a)		3.2	Gage/5210-790-0238
102.	Length of tip (min)	(a)		3.2	Gage/5210-221-1961
Minor					
201.	Total length (min)	(b)		3.2	Gage/5210-222-4559
202.	Marking illegible	(b)		3.2	Visual
203.	Protective finish damaged exposing base metal	(b)		3.2	Visual
204.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.32	Plug				9253873
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101.	Diameter around eye section (min)	(a)		3.2	Gage/5210-790-0239
102.	Length to shoulder (min)	(a)		3.2	Gage/5210-222-4559
103.	Pitch diameter of thread	(a)		3.2	Gage/5210-751-6248 /5210-751-6249
104.	Major diameter of thread	(a)		3.2	Gage/5220-747-9398
105.	Wall thickness of threaded portion (min)	(a)		3.2	Gage/5210-222-4859
106.	Number of threads below min.	(a)		3.2	Gage
Minor					
201.	Eye hole diameter (min)	(b)		3.2	Gage/7284907
202.	Depth of core (max)	(b)		3.2	Gage/5210-221-1961
203.	Any operation missing	(b)		3.2	Visual
204.	Protective finish damaged exposing base metal	(b)		3.2	Visual
205.	Evidence of poor workmanship	(b)		3.6	Visual

NOTES:
(a) Sample size per Table II
(b) Sample size per Table III

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Hardness. The tools shall be tested as specfied in Federal Test Method Standard No. 151.

4.5.2 Spring distortion. The sample spring shall be subjected to a tension test load of 68 lbs by placing one end of the spring in a suitable fixture so that the spring is hanging in a vertical position. The required weight shall then be attached to the opposite end of the spring allowing the weight to be slowly applied until the spring has been fully extended. Springs so tested for embrittlement shall be scrapped.

5. PACKAGING

5.1 Package

5.1.1 Maximum military packaging (Level A) - The Tools shall be packaged in accordance with MIL-STD 1169.

5.1.2 Commercial packaging - The Tools shall be packaged in accordance with MIL-STD-1188 unless otherwise specified in the contract.

5.2 Packing

5.2.1 Maximum military packing (Level A) - The Tools packaged in accordance with 5.1 above shall be packed in accordance with MIL-STD-1169.

5.2.2 Commercial packing - The Tools shall be packed in accordance with MIL-STD-1188, unless otherwise specified in the contract.

5.3 Marking

5.3.1 Maximum military packaging (Level A) - Packaging marking shall be in accordance with MIL-STD-129. Packing marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.

5.3.2 Commercial packaging marking shall be in accordance with MIL-STD-1188, unless otherwise specified in the contract. Commercial packing marking shall be in accordance with MIL-STD-1188, unless otherwise specified in the contract.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the M422, 8 inch projectile.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, NJ 07801.

Custodian:

Army - AR

Preparing activity:

Army - AR

(Project NUOR-A100)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:06Z
Check the source to verify that this is the current version before use.