INCH-POUND
MIL-L-17331H(SH)
AMENDMENT 2
31 December 1992
SUPERSEDING
AMENDMENT 1
19 November 1985

MILITARY SPECIFICATION

LUBRICATING OIL, STEAM TURBINE
AND GEAR, MODERATE SERVICE

This amendment forms a part of MIL-L-17331H(SH), dated 23 January 1984, and is approved by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

* PAGE 1

Add new paragraph 1.2:

"1.2 This specification specifically prohibits the addition of 2,6-Di-t-butylphenol in any lubricating oil produced under the military symbol 2190 and NATO symbol O-250, and applies to both surface ships and submarine use."

2.1.1: Delete and substitute:

"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2)."

PAGE 2

2.1.1, "STANDARDS, FEDERAL": Add the following:

"FED-STD-313 - Material Safety Data Sheets Preparation and the Submission of"

AMSC N/A FSC 9150
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:58Z
Check the source to verify that this is the current version before use.

PAGE 3

2.2, ASTM: Add the following:

"D-4057 - Manual Sampling of Petroleum and Petroleum Products, Practice for.
D-4177 - Automatic Sampling of Petroleum and Petroleum Product, Method for. (DoD adopted)

2.3: Delete and substitute:

"2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained."

3.2: Add: "If Tricresyl phosphate (TCP) is used as an antiwear additive, not more than 1.0 percent of the additive shall be the ortho isomer. The antioxidant 2,6-Di-t-butylphenol (DTBP) shall not be intentionally added to the oil and the level of DTBP, if detected shall not exceed 10 ppm (see 4.3.1).

PAGE 5

Table I, under "Foam Characteristics": Delete "Tendency/Stability" and substitute "After blowing/after 10 minutes".

PAGE 7

3.8: Add as new paragraph:

"3.8 Toxicity. The lubricating oil shall have no adverse effect on the health of personnel when used for its intended purpose. The fluid shall contain no components which produce noxious vapors in such concentrations as to be an annoyance to personnel during formulation or normal use under the conditions of adequate ventilation while exercising caution to avoid prolonged contact with the skin and while observing Occupational Safety and Health Administration (OSHA) guidelines. Questions pertaining to the toxic effects shall be referred by the contracting activity to the Naval Medical Command (NAVMEDCOM), Washington, DC, who will act as a medical advisor to the contracting activity."

Source: https://assist.dla.mil -- Downloaded: 202640-18T09:58Z
Check the source to verify that this is the current version before use.

3.8.1: Add as new paragraph"

"3.8.1 Material safety data sheets. A material safety data sheet (MSDS) shall be furnished to the Naval Sea Systems Command, SEA 05Q22, the activity responsible for the Qualified Products List, and to the contracting activity for each qualified product or each product submitted for qualification. The Naval Sea Systems Command and contracting activity shall also be provided a MSDS on the qualified products either at the time of bid submission or contract award in accordance with FED-STD-313 for each solicitation or award."

4.3.1: Add as new paragraph:

"4.3.1 Qualification test reports. A qualification test report and a MSDS shall be prepared and submitted to the qualifying activity in accordance with FED-STD-313 (see 6.3)." Data from a NAVSEA approved and certified laboratory shall be submitted to prove relative absence of 2,6-di-t-butylphenol and if detected shall not exceed 10 ppm for the lubricant.

4.4.2: Delete "ASTM D 270" and substitute "ASTM D 4057".

PAGE 8

4.4.4.2: Delete "ASTM D 270" and substitute "ASTM D 4177".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 9150-N811)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:58Z
Check the source to verify that this is the current version before use.