FED. SUP CLASS
3455



DASH NO.	Diameter of Cutter (D)	Included Angle, Deg (A)	Width of Face (W)	Diameter of Hole (H)
-1	2 3/4	45	1/2	1
-2	2 3/4	60	1/2	1
-3	2 3/4	90	1/2	1

NOTES:
1. Referenced documents shall be of the issue in effect on date of invitations for bids or request for proposal, except that referenced adopted industry documents shall give the date of the issue adopted.
2. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
3. The part number consists of the MS number, plus the dash number.
Example: MS15696-2.

© CANCELED after 31 March 1981. For procurement use American National Standards Institute ANSI B94.19.

☆U.S. GOVERNMENT PRINTING OFFICE: 1981 — 703-023/2090

APPROVED 27 Sep 54 REVISED (A) 9 Apr 57 (B) 30 Mar 77 (C) 31 Mar 81

Review activity:
DSA-GS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection of all new engineering and design applications and for repetitive use shall be made from this document, when applicable.

P.A. AL	TITLE	MILITARY STANDARD
Other Cust 99	CUTTERS, MILLING, ANGLE, DOUBLE	MS15696
Procurement Specification GGG-C-755	SUPERSEDES:	SHEET 1 OF 1

DD FORM 672 (Coordinated) EDITION OF 1 SEP 65 IS OBSOLETE

Project No. 3455-0069

Source: https://assist.dla.mil -- Downloaded: 20261-23T13:50Z
Check to retrieve to verify that this is the current version before use.