METRIC
MIL-PRF-55342/7D
AMENDMENT 2
27 February 2001
SUPERSEDING
AMENDMENT 1
22 October 1997

PERFORMANCE SPECIFICATION

RESISTORS, FIXED, FILM, CHIP,
NONESTABLISHED RELIABILITY, ESTABLISHED RELIABILITY, SPACE LEVEL,
STYLE RM1206

This amendment forms a part of MIL-PRF-55342/7D, dated 3 July 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.3, second sentence, delete characteristic "Y".

PAGE 3

TABLE I, delete and substitute:

"

| Resistance tolerance | Minimum Resistance | Maximum Resistance |
|---|---|---|
| percent (±) | | |
| 0.1 | 100 ohms | 1.0 megohm |
| 1.0 | 5.62 ohms | 5.62 megohms |
| 2.0 | 5.6 ohms | 5.6 megohms |
| 5.0 | 5.6 ohms | 5.6 megohms |
| 10.0 | 5.6 ohms | 5.6 megohms |

"

* 6.2, delete and substitute:

"6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, date of this specification, the applicable associated specification, and the complete PIN (see 1.2).

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1).

c. Packaging requirements (e.g., Electrostatic discharge (ESD) sensitivity) (see 5.1).

d. Allowable substitution (see MIL-PRF-55342).

e. If marking is required (see MIL-PRF-55342)."


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.

PAGE 5

* Add the following new paragraph:

"6.5 Electrostatic charge effects. Under relatively low humidity conditions, some types of film resistors, particularly those with small dimensions and high sheet resistivity materials, are prone to sudden significant changes in resistance (usually reductions in value) and to changes in temperature coefficient of resistance as a result of discharge of static charges built up on associated objects during handling, packaging, or shipping. Substitution of more suitable implements and materials can help minimize this problem. For example, use of cotton gloves, static eliminator devices, air humidifiers, and operator and workbench grounding systems can reduce static buildup during handling. Means of alleviating static problems during shipment include elimination of loose packaging of resistors and use of metal foil (conductive) and static dissipation packaging materials. Direct shipments to the government is controlled by MIL-DTL-39032 which specifies a preventive packaging procedure."

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC
NASA - NA

Review activities:
Army - AR, AT, AV, CR4
Navy - AS, CG, MC, OS
Air Force - 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5905-1613-07)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:12Z
Check the source to verify that this is the current version before use.