METRIC

MIL-PRF-55365/8D
AMENDMENT 3
31 July 2001
SUPERCEEDING
AMENDMENT 2
9 November 2000

PERFORMANCE SPECIFICATION

CAPACITOR, CHIP, FIXED, TANTALUM, ESTABLISHED RELIABILITY,
STYLE CWR11 (METRIC)

This amendment forms a part of MIL-PRF-55365/8D, dated 3 July 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

In the Dimensions table, under H_2 for case codes A and B, change from (0.28) to (0.028).

Under NOTES: delete note 7 in its entirety and replace with the following. “7. For solder coated terminations, add an additional 0.38 mm (.015 inch) to the tolerances for “L”, “W”, “H”, “P”, “W_2”, and “H_2” for each case size.

PAGE 3

Delete in its entirety: “Surge current (optional): This test, when applicable, shall be performed on a 100 percent basis following voltage conditioning of the qualification and group A tests. Capacitors shall be subjected to ten consecutive cycles under the following conditions:”

Replace with: “Surge current (optional): This test when applicable, shall be performed on a 100 percent basis following voltage conditioning for qualification and group A tests. If option A, B, or C is requested, the test sequence and temperature shall be as described in Table I. In all cases the capacitors shall be subjected to 10 consecutive cycles under the following conditions:”

Insert the following at the bottom of page 3.

TABLE I. Optional surge current testing

	Following Voltage Aging Exponential	Before Weibull Grading (Life accelerated FR)	After Weibull Grading (Life accelerated FR)
Option A (+25°C ± 5°C)	X	N/A	X
Option B (-55°C +5°C, -0°C and +85°C ±5°C)	X	N/A	X
Option C (-55°C +5°C, -0°C and +85°C ±5°C)	N/A	X	N/A

MIL-PRF-55365/8, Page 3, following Temperature: delete in its entirety and replace with Option A: (+25°C ±5°C) or Option B: (-55°C +5°C, -0°C and +85°C ±5°C) or Option C: (-55°C +5°C, -0°C and +85°C ±5°C).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.

PAGE 4 and 5

Change TABLE I. Style CWR11 characteristics to TABLE II. Style CWR11 characteristics.

Table II following CWR11 and prior to the first letter delete the first dash.

PAGE 5

In TABLE II for CWR11-K-684--- change case size from A to B.

In TABLE II for CWR11-K-225--- change case size from B to C.

PAGE 6

Change the references after DCL and DF from “TABLE I” to “TABLE II”.

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - AR, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA - NA

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2108)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:17Z
Check the source to verify that this is the current version before use.