MIL-P-60649B(AR)
AMENDMENT 5
15 August 1979
SUPERSEDING
AMENDMENT 4
16 May 1977

MILITARY SPECIFICATION

PERISCOPES, TANK: XM44E1 AND XM44E2
WITH ASSOCIATED EQUIPMENT

This amendment forms a part of Military Specification MIL-P-60649B(MU), dated 30 September 1969.

Paragraph 2.1, “DRAWINGS”: Delete "F10542200-2 Periscope, Tank, XM44E2" and substitute “Fl1731100 Periscope, Tank, XM44E2”.

Paragraph 2.1, “DRAWINGS”: Add the following:

F11738174 Gage- interchangeability - Body Maximum
F11738175 Gage - interchangeability - Body Maximum
F11738176 Gage - interchangeability - Head Minimum
F11738177 Gage - interchangeability - Head Maximum
F11738178 Gage - interchangeability - Mount Maximum
Fl1738179 Gage- interchangeability - Mount Minimum

Paragraph 3.10.1.1 Change “JI-J” to “JI-H”
Change “JI-K” to “JI-J”

Paragraph 3.10.2.2: Delete last sentence and substitute "Primary power shall be applied as follows: +30 Vdc to J1-H, GRD to J1-J".

Paragraph 3.10.2.3 Change: “Primary Power” to “Battery Power”

TABLE III, Change: “primary power” to “Battery Power”
Change: "5.6 + .4" to "5.6 ± .4"
Change: "1.7 + .2"" to "1.7 ± .2"

Paragraph 3.13.1: Delete sub-paragraph "b" and substitute "b". The 2-1/4” x 2.499" mounting surface located by the 0.250 inch dimension (shown on Drawing F10542O37) horizontal within 30 minutes of arc.”

Paragraph 3.13.1.c: Delete "2-1/4" by 1-1/4" mounting urfaces" and substitute “2-1/4 inches x 2.449 inches mounting surface”.

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:52Z
Check the source to verify that this is the currentversion before use.

Paragraph 3.13.2: Add the follwing:

.3.13.2 Interchangeability.

Paragraph 3.13.2: Add the following:

"3.13.2. Interchangeability.

3.13.2.1 The Mount Assembly (10513360) shall be capable of accepting all Head Assemblies (10542204) and Body Assemblies (10542201, 11731101) and shall meet the requirements of 3.12.4. a.

3.13.2.2 The Head Assembly 10542204 shall be capable of accepting all Body Assemblies (10542204) and Mount Assemblies 10513360 and shall meet the requirements of para. 3.12.4a.

3.13.2.3 The Body Assembly 10542201, 11731101 shall be capable of accepting all the Head Assemblies (10542204) and Mount Assemblies 10513360 and shall meet the requirements of para. 3.12.4.a"

Paragraph 4.4.2.1: Delete and substitute

"4.4.2.1 Panel assembly. - Three panel assemblies shall be selected at random as samples from each 50 produced, or from each month's production whichever, occurs first. Each sample shall meet the requirements and tests in Table XII, and shall then meet the requirements and tests in Table VII."

Paragraph 4.4.2.6: Add the following:

"4.4 .2.6 Periscope, Tank, XM44E1 and XM44E2. - Three periscopes shall be selected at random as samples from the first month's production and at 25%, 50%, and 75% completion of the contract production. Each sample shall meet the interchangeability requirements of 3.13.2 when tested in accordance with test method specified in 4.6.10.13."

Paragraph 4.5.2.3.3.b: Delete "2-1/4 by 1-1/4" mounting surfaces" and substitute "2-1/4 inches x 2.400 inches mounting surfaces".

Paragraph 4.5.3: Add the following:

"Oscilloscope Accuracy: ± 1% of reading
(peak-to-peak)"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.10.13, Add the following:

"4.6.10.13 Interchangeability. - Each samples periscope (See 4.4.2.6) shall be disassembled to permit interchange of the Head, Mount, and Body Assemblies.

Each component part (head, mount, and body assemblies) shall be inserted into their respective minimum and maximum interchangeability gages (See 2.1) and shall be capable of being firmly secured and REmoved without interference.

After each component part has been gaged and found acceptable, the components shall be identified and assembled as shown in TABLE XVI.

TABLE XVI

Original Component Positions

Periscope No. 1 - Head No. 1 Mount No. 1 Body No. 1
Periscope No. 2 - Head No. 2 Mount No. 2 Body No. 2
Periscope No. 3 - Head No. 3 Mount No. 3 Body No. 3

Interchanged Component Positions

Periscope No. 4 - Head No. 1 Mount No. 3 Body No. 2
Periscope No. 5 - Head No. 3 Mount No. 2 Body No. 1
Periscope No. 6 - Head No. 2 Mount No. 1 Body No. 3

Upon reassembly of the three interchanged periscopes, each periscope shall be subjected to the sealing test specified in 4.6.10.8 and meet the requirements of 3.12.4a.

Custodian:

Army - AR

Preparing activity:

Army - AR

Project No. 1240-A732

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.