FED. SUP CLASS
2640

DASH NO.	MARKING CODE	NUMBER OF PLIES TO EACH PATCH	TIRE TO BE REPAIRED		OVER-ALL PATCH DIMENSIONS (4)
			INJURY SIZE MAX	PLY RATING	
-1	0-A	MESH	NAIL	ALL	1-5/8 X 1-5/8
-2	0-A	MESH	NAIL	ALL	2-3/8 X 2-3/8
-3	0-A	MESH	NAIL	ALL	3-1/8 X 3-1/8
-4	0-A	MESH	NAIL	ALL	4-5/8 X 4-5/8
-5	2-1/4-6	2	1/4	6	3 X 3
-6	2-3/4-6	2	3/4	6	4 X 4
-7	2-1/2-10	2	/2	10	5 X 5
-8	3-3/4-10	3	3/4	10	6 X 6
-9	3-1/2-14	3	1/2	14	7 X 7
-10	4-3/4-14	4	3/4	14	8 X 8
-11	4-1-14	4	1	14	10 X 10
-12	6-1-1/2-14	6	1-1/2	14	10 X 10
-13	6-2-1/2-14	6	2-1/2	14	12 X 12
-14	6-3-14	6	3	14	14 X 14
-15	8-2-18	8	2	18	14 X 14
-16	8-3-18	8	3	18	17 X 17
-17	8-3-1/2-18	8	3-1/2	18	19 X 19
-18	10-3-24	10	3	24	22 X 22
-19	12-6-28	12	6	28	24 X 24
-20	14-5-32	14	5	32	26 X 26
-21	16-5-36	16	5	36	28 X 28
-22	18-7-36	18	7	36	30 X 30
-23	4-3-T	4	3	TRACTOR	12 X 12
-24	4-4-T	4	4	TRACTOR	14 X 14
-25	6-5-1/2-T	6	5-1/2	TRACTOR	19 X 19

NOTES:

1. PATCHES SHALL CONFORM TO TYPE III, CLASS C, STYLE N OF PROCUREMENT SPECIFICATION; AND SHALL BE USED WITH CORRESPONDING CHEMICAL VULCANIZING FLUID OF THE PATCH MANUFACTURER.
2. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
4. DIMENSIONS ARE IN INCHES. TOLERANCES ARE ±.25 ON SIZES UNDER 7 X 7; ±.50 ON SIZES 7 X 7 AND OVER.
5. "O" INDICATES NAIL HOLE.
6. "A" INDICATES USE WITH ALL PLY RATINGS.
7. "T" INDICATES TRACTOR TIRES.
8. MARKING CODE DENOTES THE NUMBER OF PLIES IN THE PATCH, THE MAXIMUM INJURY SIZE IN INCHES AND THE PLY RATING OF THE TIRE FOR WHICH THE PATCH IS INTENDED.
9. MARKING SHALL CONSIST OF THE MS PART NUMBER, MANUFACTURER'S IDENTIFICATION AND MARKING CODE IN ACCORDANCE WITH MIL-STD-130.

APPROVED 22 SEP 1972 REVISED

REVIEW ACTIVITIES: NAVY-YD
USER ACTIVITIES: NAVY-MC, ; AF-84

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. ARMY-AT Other Cust NAVY-YD AF-84	PATCH, PNEUMATIC TIRE REPAIR: CHEMICAL CURED NYLON AND VULCANIZING FLUID	MILITARY STANDARD MS 52123
PROCUREMENT SPECIFICATION ZZ-T-416	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:20Z
Check the source to verify that this is the current version before use.