The documentation and process conversion measures necessary to comply with this revision shall be completed by 2 January 2002.

INCH-POUND
MIL-PRF-19500/375E
2 October 2001
SUPERSEDING
MIL-PRF-19500/375D
17 May 2000

PERFORMANCE SPECIFICATION

* SEMICONDUCTOR DEVICE, TRANSISTOR, FIELD-EFFECT, N-CHANNEL, DEPLETION MODE, SILICON, TYPES 2N3821, 2N3822, 2N3823 JAN, JANTX, JANTXV, JANS, AND UB

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers the performance requirements for N-channel, junction, silicon, field-effect depletion mode transistors. Five levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

* 1.2 Physical dimensions. See figure 1 (similar to TO-72) and figure 2.

1.3 Maximum ratings.

P_T (1)	V_{DG} and V_{DS}			V_{GSR}			I_{GF}	T_{op} and T_{STG}
T_A = +25°C	2N3821	2N3822	2N3823	2N3821	2N3822	2N3823		
mW	V dc	V dc	V dc	V dc	V dc	V dc	mA dc	°C
300	50	50	30	50	50	30	10	-55 to +200

(1) Derate linearly, 1.7 mW/°C for $T_A \geq$ +25°C.

1.4 Primary electrical characteristics.

	I_{DSS} (1) V_{DS} = 15 V dc V_{GS} = 0			$V_{GS(off)}$ V_{DS} = 15 V dc I_D = 0.5 nA dc			N_F V_{DS} = 15 V dc V_{GS} = 0, R_G = 1 MΩ f = 10 Hz		N_F V_{DS} = 15 V dc V_{GS} = 0, R_G = 1 MΩ f = 1 kHz	N_F V_{DS} = 15 V dc V_{GS} = 0, R_G = 1 MΩ f = 105 MHz
	2N3821	2N3822	2N3823	2N3821	2N3822	2N3823	2N3821	2N3822	All types	2N3823
	mA dc	mA dc	mA dc	V dc	V dc	V dc	dB		dB	dB
Min	0.5	2.0	4.0							
Max	2.5	10.0	20.0	4.0	6.0	8.0	5.0		2.5	2.5

(1) Pulsed (see 4.5.1).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAC, P. O. Box 3990, Columbus, OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics - Continued.

	$\|y_{fs}\|1$ (1) V_{DS} = 15 V dc f = 1 kHz V_{GS} = 0			$\|y_{fs}\|3$ V_{DS} = 15 V dc V_{GS} = 0			C_{iss} V_{DS} = 15 V dc V_{GS} = 0 100 kHz ≤ f ≤ 1 MHz	C_{rss} V_{DS} = 15 V dc V_{GS} = 0 100 kHz ≤ f ≤ 1 MHz		
				f = 100 MHz	f = 100 MHz	f = 200 MHz				
	2N3821	2N3822	2N3823	2N3821	2N3822	2N3823		2N3821	2N3822	2N3823
	µs	µs	µs	µs	µs	µs	pF	pF	pF	pF
Min	1,500	3,000	3,500	1,500	3,000	3,200				
Max	4,500	6,500	6,500				6	3	3	2

(1) Pulsed (see 4.5.1).

2 APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

DEPARTMENT OF DEFENSE


MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Services (DAPS), Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.


Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.178	.195	4.52	4.95	
CH	.170	.210	4.32	5.33	
HD	.209	.230	5.31	5.84	
L1		.050		1.27	
L2	.250		6.35		
LC	.100 TP		2.54 TP		
LD	.016	.021	0.41	0.53	2, 6
LL	.500	.750	12.70	19.05	6
LU	.016	.019	0.41	0.48	3, 6
Q		.040		1.02	
r		.007		0.18	
TL	.028	.048	0.71	1.22	8
TW	.036	.046	0.91	1.17	
α	45° TP				



NOTES:
1. Dimensions are in inches. Metric equivalents are given for general information only.
2. Measured in the zone beyond .250 (6.35 mm) from the seating plane.
3. Measured in the zone .050 (1.27 mm) and .250 (6.35 mm) from the seating plane.
4. When measured in a gauging plane .054 +.001, -.000 (1.37 +.3, -.00 mm) before the seating plane of the transistor, maximum diameter leads shall be within .007 (.18 mm) of their true location relative to a maximum width tab. Smaller diameter leads shall fall within the outline of the maximum diameter lead tolerance.
5. The active elements are electrically insulated from the case.
6. All 4 leads.
7. Lead 1 is the source, lead 2 is the drain, lead 3 is the gate, and lead 4 is the case.
8. Symbol TL is measured from HD maximum.

FIGURE 1. Physical dimensions (similar to T0-72).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.046	.056	1.17	1.42
A1	.017	.035	0.43	0.89
B1	.016	.024	0.41	0.61
B2	.016	.024	0.41	0.61
B3	.016	.024	0.41	0.61
D	.085	.108	2.16	2.74
D1	.071	.079	1.80	2.01
D2	.035	.039	0.89	0.99
D3	.085	.108	2.16	2.74
E	.115	.128	2.92	3.25
E3		.128		3.25
L1	.022	.038	0.56	0.96
L2	.022	.038	0.56	0.96

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

* FIGURE 2. Physical dimensions, surface mount (UB version).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-19500.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows.

R_{ISO} ..... Insulation resistance, gate lead to case.

V_1 ..... rms value of the specified reference voltage in the specified circuit.

V_2 ..... rms value of the measured voltage between the specified points in the specified circuit.

$|y_{os}|$ ..... Magnitude of small-signal common-source short-circuit output admittance.

S ..... Unit of conductance or admittance (formerly mho).

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 and figure 2 herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in paragraph 1.3, 1.4, and table I.

3.6 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table 1.

3.7 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4 VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

4.3 Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with table IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
11	I_{GSSR1}, I_{DSS}, and $\|y_{fs}\|1$	I_{GSSR1}, I_{DSS}, and $\|y_{fs}\|1$
12	See 4.3.1	See 4.3.1
13	Subgroups 2 and 3 of table I herein; ΔI_{DSS} = ±10 percent of initial value; $\Delta\|y_{fs}\|1$ = ±20 percent initial value.	Subgroup 2 of table I herein; ΔI_{DSS} = ±10 percent of initial value; $\Delta\|y_{fs}\|1$ = ±20 percent of initial value.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:

2N3821 and 2N3822: V_{GS} = 40 V dc; V_{DS} = 0; T_A = +150°C.

2N3823: V_{GS} = 24 V dc; V_{DS} = 0; T_A = +150°C.

NOTE: No heat sink or forced air cooling on the devices shall be permitted.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in tables VIa (JANS) and VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and 4.4.2.1 and 4.4.2.2 herein. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B4	1037	2N3821 and 2N3822: V_{DS} = 30 V dc, V_{GS} = 0; 2N3823: V_{DS} = 15 V dc, V_{GS} = 0; at T_A = +30°C ±5°C. t_{on} = t_{off} = 3 minutes minimum for 2,000 cycles. No heat sink or forced-air cooling on the devices shall be permitted.
B5	1027	V_{DS} = 0; 2N3821 and 2N3822: V_{GS} = 40 V dc; 2N3823: VGS = 24 V dc; at T_A = +225°C for 168 hours or T_A = +200°C for 260 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

4.4.2.2 Group B inspection, table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1027	2N3821 and 2N3822: V_{GS} = 40 V dc, V_{DS} = 0; 2N3823: V_{DS} = 0, V_{GS} = 24; at T_A = +150°C ±5°C.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500, and as follows. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition
C2	2036	Test condition E.
C6	1026	2N3821 and 2N3822: V_{GS} = 40 V dc, V_{DS} = 0; 2N3823: V_{DS} = 0, V_{GS} = 24; at T_A = +150°C ±5°C.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Disposition of case lead during electrical measurements. All electrical measurements (except for case insulation test) operating life test shall be performed with the case lead connected to the source.

4.5.2.1 Case insulation resistance test. Case insulation resistance test shall be measured between the case and gate lead.

4.5.3 Small-signal common-source short-circuit input (or output) conductance. These tests shall be conducted with a General Radio transfer function and admittance bridge model 1607A (or suitable equivalent) in accordance with the portion of its accompanying handbook which is applicable to this measurement. A Hewlett-Packard generator model 608D and a Nems-Clarke receiver model 1502A (or suitable equivalents) shall be used with the transfer function and admittance bridge.

4.5.4 10 Hz and 1 kHz spot noise figure tests. These tests shall be conducted with a model 2173C Quan Tech Laboratories test set, or equivalent. Conditions shall be as specified in table I.

4.5.5 105 MHz spot noise figure test. This test shall be conducted with the equipment and circuit shown on figures 3 and 4, or suitable equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection .

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Gate - source breakdown voltage	3401	Bias condition C; I_G = 1.0 µA dc; V_{DS} = 0	$V_{(BR)GSSR}$			
2N3821, 2N3822				50		V dc
2N3823				30		V dc
Gate reverse current	3411	Bias condition C;	I_{GSSR1}			
2N3821, 2N3822		V_{GS} = 30 V dc; V_{DS} = 0			0.1	nA dc
2N3823		V_{GS} = 20 V dc; V_{DS} = 0			0.5	nA dc
Zero-gate-voltage drain current	3413	Bias condition C; V_{DS} = 15 V dc; V_{GS} = 0; pulsed (see 4.5.1)	I_{DSS}			
2N3821				0.5	2.5	mA dc
2N3822				2.0	10.0	mA dc
2N3823				4.0	20.0	mA dc
Gate - source voltage	3403	V_{DS} = 15 V dc;	V_{GS}			
2N3821		I_D = 50 µA dc		0.5	2.0	V dc
2N3822		I_D = 200 µA dc		1.0	4.0	V dc
2N3823		I_D = 400 µA dc		1.0	7.5	V dc
Gate - source cutoff voltage	3403	V_{DS} = 15 V dc; I_D = 0.5 nA dc	$V_{GS(off)}$			
2N3821					4.0	V dc
2N3822					6.0	V dc
2N3823					8.0	V dc
Case insulation resistance	1016	Test condition A; (see 4.5.2.1)	R_{ISO}	10^{10}		Ω
Small-signal, common-source, short-circuit, forward transadmittance	3455	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz; pulsed (see 4.5.1)	$\|y_{fs}\|1$			
2N3821				1,500	4,500	µs
2N3822				3,000	6,500	µs
2N3823				3,500	6,500	µs
Subgroup 3						
High-temperature operation:		T_A = +150°C				
Gate reverse current	3411	Bias condition C;	I_{GSSR2}			
2N3821, 2N3822		V_{GS} = 30 V dc; V_{DS} = 0			0.1	µA dc
2N3823		V_{GS} = 20 V dc; V_{DS} = 0			0.5	µA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3 - Continued						
Low-temperature operation:		T_A = -55°C				
Small-signal, common-source, short-circuit, forward transadmittance	3455	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz; pulsed (see 4.5.1)	$\|y_{fs}\|2$			
2N3821					6,750	µs
2N3822					9,750	µs
2N3823					9,750	µs
Subgroup 4						
Small-signal common-source, short-circuit, output admittance	3453	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz; pulsed (see 4.5.1)	$\|y_{os}\|$			
2N3821					10	µs
2N3822					20	µs
2N3823					35	µs
Small-signal common-source, short-circuit, input capacitance	3431	V_{DS} = 15 V dc; V_{GS} = 0; 100 kHz ≤ f ≤ 1 MHz	C_{iss}		6	pF
Small-signal common-source, short-circuit, reverse-transfer capacitance	3453	V_{DS} = 15 V dc; V_{GS} = 0; 100 kHz ≤ f ≤ 1 MHz	C_{rss}			
2N3821, 2N3822					3	pF
2N3823					2	pF
Small-signal common-source, short-circuit, forward transadmittance	3455	V_{DS} = 15 V dc; V_{GS} = 0	$\|y_{fs}\|3$			
2N3821		f = 100 MHz		1,500		µs
2N3822		f = 100 MHz		3,000		µs
2N3823		f = 200 MHz		3,200		µs
Small-signal common-source, short-circuit, input conductance		V_{DS} = 15 V dc; V_{GS} = 0; f = 200 MHz; (see 4.5.3)	g_{is}			
2N3823 only					800	µs

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Small-signal common-source, short-circuit, output conductance		V_{DS} = 15 V dc; V_{GS} = 0; f = 200 MHz; (see 4.5.3)	g_{os}			
2N3823 only					200	µs
Common-source spot noise figure		V_{DS} = 15 V dc; V_{GS} = 0; R_G = 1 MΩ; (see 4.5.4)	NF_1			
2N3821, 2N3822 only		f = 10 Hz			5.0	dB
All three types		f = 1 kHz			2.5	dB
Common-source spot noise figure		V_{DS} = 15 V dc; V_{GS} = 0; R_G = 1 kΩ; f = 105 MHz; (see 4.5.5)	NF_2			
2N3823 only					2.5	dB
Subgroups 5, 6, and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

TABLE II. Groups B and C delta measurements. 1/ 2/ 3/


Step	Inspection	MIL-STD-750		Symbol	Limit	Unit
		Method	Conditions			
1.	Gate - source voltage 2N3821 2N3822 2N3823	3403	V_{DS} = 15 V dc I_D = 50 µA dc I_D = 200 µA dc I_D = 400 µA dc	ΔV_{GS}	±50 mV change from previously measured value	
2.	Zero-gate-voltage drain current	3413	Bias condition C; V_{DS} = 15 V dc; V_{GS} = 0; pulsed (see 4.5.1)	ΔI_{DSS}	±15 percent change from previously measured value.	
3.	Small-signal, common-source short-circuit, forward transadmittance	3455	V_{DS} = 15 V dc; V_{GS} = 0; f = 1 kHz; pulsed (see 4.5.1)	$\Delta\|y_{fs}\|1$	±25 percent change from previously measured value.	

1/ The delta measurements for table VIa (JANS) of MIL-PRF-19500 are as follows:
   a. Subgroup 3, see table II herein, steps 2 and 3.
   b. Subgroup 4, see table II herein, steps 1, 2, and 3.
   c. Subgroup 5, see table II herein, steps 2 and 3.

2/ The delta measurements for table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500 are as follows:
   Subgroup 3, see table II herein, step 3.


3/ The delta measurements for table VII of MIL-PRF-19500 are as follows:
   a. Subgroups 2 and 3, table II herein, steps 1, 2, and 3 (for JANS only).
   b. Subgroup 6, see table II herein, steps 1, 2, and 3, (for JANS) and step 3 (for JAN, JANTX, and JANTXV).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.



NOTES:
1. The test fixture and procedure shall be in accordance with figure 2.
2. The post amplifier shall contain suitable biasing circuits and shall be constructed utilizing very high frequency design technique.

FIGURE 3. Block diagram for 105 MHz spot noise figure test.



CIRCUIT-COMPONENT INFORMATION:

L_1: Approximately 8.5 turns of No. 16 tinned copper; diameter approximately .375 inch; length approximately .9 inch; tapped at approximately 2.5 turns (adjust to give R_{G1} = 100 Ω); parallel resistance = 40 kΩ; tunes at approximately 8 pF.

L_2: Approximately 13.5 turns of No. 16 tinned copper; diameter approximately .375 inch; length approximately 1.2 inch; tapped at approximately 5 turns; parallel resistance = 40 kΩ; tunes at approximately 4 pF.

L_3: Approximately 15 turns of No. 20 tinned copper.

TEST PROCEDURE:

1. Neutralization shall be accomplished as follows:
   a. Insert a typical device from the units to be tested.
   b. Using a sweep generator and an oscilloscope adjust the input (C_1) and output (C_2) for maximum gain at 105 MHz.
   c. Reverse the input and output of the test jig and tune L_3 for a null.
   d. Return the input and output of the test jig to normal.
2. Once neutralization has been obtained, the devices may be tested by inserting them in the test jig and adjusting C_1 and C_2 to obtain minimum noise figure for each device.

FIGURE 4. 105 MHz spot noise figure test fixture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

5 PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6 NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

c. Lead finish (see 3.4.1).

d. Type designation and product assurance level.

e. Packaging requirements (see 5.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List QML-19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC-VQE, P.O. Box 3990, Columbus, OH 43216-5000.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - NW
Air Force - 11
NASA - NA
DLA - CC

Review activities:
Army - AR, AV, MI, SM
Navy - AS, MC
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5961-2487)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-PRF-19500/375E	**2. DOCUMENT DATE (YYMMDD)** 2 October 2001

DOCUMENT TITLE SEMICONDUCTOR DEVICE, TRANSISTOR, FIELD-EFFECT, N-CHANNEL, DEPLETION MODE, SILICON, TYPES 2N3821, 2N3822, 2N3823, JAN, JANTX, JANTXV, JANS, AND UB.

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) Commercial DSN FAX EMAIL	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. Point of contact: Alan Barone	b. TELEPHONE Commercial: 614-692-0510 DSN: 850-0510 FAX: 614-692-6939 EMAIL: alan.barone@dscc.dla.mil
c. ADDRESS Defense Supply Center Columbus ATTN: DSCC-VAC P.O. Box 3990 Columbus, OH 43216-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533 Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:26Z
Check the source to verify that this is the current version before use.