The documentation and process conversion measures necessary to comply with this revision shall be completed by 15 March 1993

INCH-POUND

MIL-S-19500/379D
15 December 1992
SUPERSEDING
MIL-S-19500/379C
12 October 1979

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, HIGH-POWER
TYPES 2N3791, 2N3792 JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for PNP silicon, high-power transistors. Three levels of product assurance are provided for each device type as specified in MIL-S-19500.

1.2 Physical dimensions. See figure 1.

1.3 Maximum ratings.

	P_T 1/ T_A = 25°C	P_T 2/ T_C = 100°C	V_{CBO}	V_{CEO}	V_{EBO}	I_B	I_C	T_J and T_{STG}	$R_{\theta JC}$
	W	W	V dc	V dc	V dc	A dc	A dc	°C	°C/W max
2N3791	5.0	85.7	60	60	7.0	4.0	10	-65 to +200	1.17
2N3792	5.0	85.7	80	80	7.0	4.0	10	-65 to +200	1.17

1/ Derate linearly 28.57 mW/°C above T_A = 25°C.
2/ Derate linearly 0.857 W/°C above T_C = 100°C.

1.4 Primary electrical characteristics at T_C = 25°C ±3°C.

	h_{FE2} 1/	h_{FE4} 1/	$V_{BE(SAT)1}$ 1/	$V_{CE(SAT)1}$ 1/	C_{obo}	$\|h_{fe}\|$
	V_{CE} = 2.0 V dc, I_C = 3.0 A dc	V_{CE} = 4.0 V dc, I_C = 10 A dc	I_C = 5.0 A dc, I_B = 0.5 A dc	I_C = 5.0 A dc, I_B = 0.5 A dc	V_{CB} = 10 V dc, I_E = 0, f = 1 MHz	V_{CE} = 10 V dc, I_C = 0.5 A dc, f = 1 MHz
			V dc	V dc	pF	
Min	30	5.0	---	---	---	4.0
Max	120	---	1.5	1.0	500	20

1/ Pulsed (see 4.5.1).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Laboratory Command, ATTN: SLCET-R-S, Fort Monmouth, NJ 07703-5601 by using the Standardization Document Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 5961

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T15:35Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

MILITARY

MIL-S-19500 - Semiconductor Devices, General Specification for.

STANDARD

MILITARY

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Associated detail specification. The individual item requirements shall be in accordance with MIL-S-19500 and as specified herein.

3.2 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-S-19500.

3.3 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-S-19500 and figure 1 herein.

3.3.1 Lead finish. Lead finish shall be solderable in accordance with MIL-STD-750, MIL-S-19500, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).


3.4 Marking. Marking shall be in accordance with MIL-S-19500 except at the option of the manufacturer, the country of origin marking may be omitted from the body of the transistor.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-S-19500 and as specified herein.

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-S-19500 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A	.270	.380	6.86	9.65	
ϕb	.038	.043	0.97	1.09	
ϕD		.875		22.22	6
c	.420	.440	10.67	11.18	3, 4
c_1	.205	.225	5.21	5.72	3, 4
F	.060	.135	1.52	3.43	
L	.312	.500	7.92	12.70	
L_1		.050		1.27	
ϕp	.151	.161	3.84	4.09	
q	1.177	1.197	29.90	30.40	
R	.495	.525	12.57	13.34	
R_1	.131	.188	3.33	4.78	
s	.655	.675	16.64	17.15	

NOTES:
1. Dimensions are in inches.
2. Terminal 1, base; terminal 2, emitter; case, collector.
3. These dimensions should be measured at points .050-.055 (1.27-1.40 mm) below seating plane. When gauge is not used, measurement will be made at the seating plane.
4. The seating plane of the header shall be flat within .001 (0.03 mm) concave to .004 (0.10 mm) convex inside a .930 (23.62 mm) diameter circle on the center of the header and flat within .001 (0.03 mm) concave to .006 (0.15 mm) convex overall.
5. Collector shall be electrically connected to the case.
6. ϕb applies between L_1 and L. Diameter is uncontrolled in L_1.

FIGURE 1. Physical dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

4.3 Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with MIL-S-19500 (table II) and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table II of MIL-S-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
9	I_{CES1} and h_{FE2}	I_{CES1}
11	I_{CES1} and h_{FE2}; ΔI_{CES1} = 100 percent of initial value or 1 μA dc, whichever is greater. Δh_{FE2} = ±15 percent of initial value.	I_{CES1} and h_{FE2}; ΔI_{CES1} = 100 percent of initial value or 1 μA dc, whichever is greater.
12	See 4.3.1	See 4.3.1
13	ΔI_{CES1} = 100 percent of initial value or 1 μA dc, whichever is greater; Δh_{FE2} = ±15 percent of initial value; subgroups 2 and 3 of table I herein.	ΔI_{CES1} = 100 percent of initial value or 1 μA dc, whichever is greater; Δh_{FE2} = ±15 percent of initial value; subgroup 2 of table I herein.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:

T_J = 187.5 ±12.5°C; V_{CB} = 35 ±5 V dc; $T_A \leq$ 100°C.

4.4 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-S-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-S-19500 and table I herein. Electrical measurements (endpoint) and delta requirements shall be in accordance with the applicable steps in table II herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table IVa (JANS) and table IVb (JANTX and JANTXV) of MIL-S-19500, and as follows. Electrical measurements (endpoints) and delta requirements shall be in accordance with the applicable steps in table II herein.

4.4.2.1 Group B inspection, table IVa of MIL-S-19500.

a. Subgroup 3:

Bond strength; method 2037; test condition A; All internal wires for each device shall be pulled separately.

b. Subgroup 4:

Intermittent operation life; method 1037; conditions: V_{CB} = 30 V dc; P_T = 5 W at T_A = 25°C ±3°C, t_{on} = t_{off} = 3 minutes minimum for 2,000 cycles. No heat sink nor forced air on the device shall be permitted.

c. Subgroup 5:

Accelerated steady-state operation life; method 1027; conditions: V_{CB} = 30 V dc; T_A = 125°C ±25°C for 96 hours; P_T = 5 W at T_A = 112°C or adjusted as required by the chosen T_A to give an average lot T_J = 275°C. Marking legibility requirements shall not apply.

d. Subgroup 6:

Thermal resistance; method 3131; conditions; see 4.5.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

4.4.2.2 Group B inspection, table IVb of MIL-S-19500.

a. Subgroup 3:

Steady-state operation life; method 1027; conditions: T_J = 187.5°C ±12.5°C; V_{CB} = 35 V dc ±5 V dc; $T_A \leq$ 100°C.

b. Subgroup 5:

Thermal resistance; method 3131; conditions: see 4.5.2.

c. Subgroup 6:

High-temperature life (nonoperating); method 1032; T_A = 200°C.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table V of MIL-S-19500, and as follows. Electrical measurements (endpoints) and delta requirements shall be in accordance with the applicable steps in table II herein.

4.4.3.1 Group C inspection, table V of MIL-S-19500.

a. Subgroup 2:

Terminal strength (lead fatigue); method 2036; test condition A; weight = 10 lbs., t = 15 s.

b. Subgroup 6:

Steady-state operation life; method 1026; conditions: T_C = 187.5°C ±12.5°C; V_{CE} = 25 V dc ±5 V dc; $T_A \leq$ 100°C.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in MIL-STD-750.

4.5.2 Thermal resistance. Thermal resistance measurements shall be conducted in accordance with test method 3131 of MIL-STD-750. The following details shall apply:

a. Collector current magnitude during power application shall be 1.0 A dc minimum.

b. Collector to emitter voltage magnitude shall be 10 V dc minimum.

c. Reference temperature measuring point shall be the case.

d. Reference point temperature shall be 25°C ≤ T_R ≤ 75°C and recorded before the test is started.

e. Mounting arrangement shall be with heat sink to header.

f. Maximum limit of $R_{\theta JC}$ shall be 1.17°C/W.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Collector-emitter breakdown voltage	3011	Bias cond. D; I_C = 10 mA dc; pulsed (see 4.5.1)	$V_{(BR)CEO}$			
2N3791				60	---	V dc
2N3792				80	---	V dc
Emitter-base cutoff current	3061	Bias cond. D; V_{EB} = 7 V dc	I_{EBO}	---	5.0	mA dc
Collector-base cutoff current	3036	Bias cond. D;	I_{CBO}			
2N3791		V_{CB} = 60 V dc		---	5.0	mA dc
2N3792		V_{CB} = 80 V dc		---	5.0	mA dc
Collector-emitter cutoff current	3041	Bias cond. A; V_{BE} = 1.5 V dc	I_{CEX}			
2N3791		V_{CE} = 60 V dc		---	5.0	mA dc
2N3792		V_{CE} = 80 V dc		---	5.0	mA dc
Collector-emitter cutoff current	3041	Bias cond. C;	I_{CES1}			
2N3791		V_{CE} = 50 V dc		---	5.0	mA dc
2N3792		V_{CE} = 70 V dc		---	5.0	mA dc
Base-emitter saturated voltage	3066	Test cond. A; I_C = 5 A dc; I_B = 0.5 A dc; pulsed (see 4.5.1)	$V_{BE(SAT)1}$	---	1.5	V dc
Base-emitter saturated voltage	3066	Test cond. A; I_C = 10 A dc; I_B = 2 A dc; pulsed (see 4.5.1)	$V_{BE(SAT)2}$	---	3.0	V dc
Collector-emitter saturated voltage	3071	I_C = 5 A dc; I_B = 0.5 A dc; pulsed (see 4.5.1)	$V_{CE(sat)1}$	---	1.0	V dc
Collector-emitter saturated voltage	3071	I_C = 10 A dc; I_B = 2 A dc; pulsed (see 4.5.1)	$V_{CE(sat)2}$	---	2.5	V dc
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 1.0 A dc; pulsed (see 4.5.1)	h_{FE1}	50	150	---
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 3.0 A dc; pulsed (see 4.5.1)	h_{FE2}	30	120	---

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Cont'd						
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 5 A dc; pulsed (see 4.5.1)	h_{FE3}	10	---	---
Forward-current transfer ratio	3076	V_{CE} = 4.0 V dc; I_C = 10 A dc; pulsed (see 4.5.1)	h_{FE4}	5	---	---
Subgroup 3						
High-temperature operation		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias cond. C;	I_{CES2}			
2N3791		V_{CE} = 50 V dc		---	5.0	mA dc
2N3792		V_{CE} = 70 V dc		---	5.0	mA dc
Low-temperature operation		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 3.0 A dc; pulsed (see 4.5.1)	h_{FE5}	12	---	---
Subgroup 4						
Switching parameters						
Pulse delay time		See figure 2.	t_d	---	0.2	µs
Pulse rise time		See figure 2.	t_r	---	1.3	µs
Pulse storage time		See figure 2.	t_s	---	1.4	µs
Pulse fall time		See figure 2.	t_f	---	1.0	µs
t_{off}		$t_s + t_f$	t_{off}	---	2.0	µs
Small-signal short-circuit forward-current transfer ratio	3206	V_{CE} = 10 V dc; I_C = 0.5 A dc	h_{fe}	30	300	---
Magnitude of small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 0.5 A dc; f = 1 MHz	$\|h_{fe}\|$	4.0	20	---
Open circuit output capacitance	3236	V_{CB} = 10 V dc; I_E = 0; f = 1 MHz	C_{obo}	---	500	pf

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 202610-18T15:35Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (continuous dc)	3051	T_C = 25°C; t ≥ 1 s; 1 cycle; (see figure 3)				
Test 1		V_{CE} = 15 V dc; I_C = 10 A dc				
Test 2		V_{CE} = 40 V dc; I_C = 3.75 A dc				
Test 3						
2N3791		V_{CE} = 55 V dc; I_C = 0.9 A dc				
2N3792		V_{CE} = 65 V dc; I_C = 0.9 A dc				
Safe operating area (clamped inductive)	3053	T_A = 25°C; I_C = 10 A dc; V_{CC} = 15 V dc; (see figures 5 and 6)				
2N3791		Clamp voltage = 60 V dc				
2N3792		Clamp voltage = 80 V dc				
Safe operating area (switching)	3053	(Unclamped inductive load) Load cond. C (see fig. 4); T_A = 25°C; duty cycle ≤ 10 percent				
Test 1		t_p approx 1.0 ms (Vary to obtain I_C); R_{BB1} = 5Ω; V_{BB1} = 8 V dc; R_{BB2} = ∞; V_{BB2} = 0; V_{CC} = 20 V dc; I_C = 5 A dc; L = 4 mH; Q ≥ 100 at 1 kHz; .05 ohms, 20 A dc; (Stanford Miller CK-20 or equivalent)				
Test 2		t_p approx 2.2 ms (Vary to obtain I_C); R_{BB1} = 5Ω; V_{BB1} = 8 V dc; R_{BB2} = ∞; V_{BB2} = 0; V_{CC} = 20 V dc; I_C = 2.2 A dc; L = 20 mH; Q ≥ 6000 at 10 kHz; 0.22 ohms, 12.5 A dc; (Two Stancor C-2688 in series or equivalent)				
Safe operating area (clamped inductive) (destructive)	3053	T_A = 25°C; I_C = 10 A dc; V_{CC} = 55 V dc; (see figures 5 and 6)				
2N3791		Clamp voltage = 60 V dc				
2N3792		Clamp voltage = 80 V dc				
Electrical measurements		See table II, steps 1 and 4.				
Subgroups 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-S-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

TABLE II. Groups A, B, and C electrical measurements. 1/ 2/ 3/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Collector-emitter cutoff current 2N3791 2N3792	3041	Bias condition C; V_{CE} = 50 V dc V_{CE} = 70 V dc	I_{CES1}		5 5	mA dc mA dc
2.	Collector-emitter (voltage saturated)	3071	I_C = 5 A dc; I_B = 0.5 A dc; pulsed (see 4.5.1)	$V_{CE(SAT)1}$		1.0	V dc
3.	Base-emitter voltage saturated	3066	Bias condition A; I_C = 5.0 A dc I_B = 0.5 A dc pulsed (see 4.5.1)	$V_{BE(SAT)1}$		1.5	V dc
4.	Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 3.0 A dc; pulsed (see 4.5.1)	h_{FE2}	30	120	
5.	Collector-emitter cutoff current 2N3791 2N3792	3041	Bias condition C; V_{CE} = 50 V dc V_{CE} = 70 V dc	ΔI_{CES1} 4/	100% of initial value or 1 µA dc; whichever is greater.		
6.	Forward-current transfer ratio	3076	V_{CE} = 2.0 V dc; I_C = 3.0 A dc; pulsed (see 4.5.1)	Δh_{FE2} 4/	±25% change from initial value		
7.	Collector-emitter (voltage saturated)	3071	I_C = 5 A dc; I_B = 0.5 A dc; pulsed (see 4.5.1)	$\Delta V_{CE(SAT)1}$ 4/	±50 mV dc change from previously measured value		

1/ The electrical measurements for table IVa (JANS) of MIL-S-19500 are as follows:

a. Subgroup 3, see table II herein, steps 1, 2, 3, and 4.

b. Subgroup 4, see table II herein, steps 1, 2, 3, 4, and 7.

c. Subgroup 5, see table II herein, steps 1, 2, 3, 4, 5, 6, and 7.

2/ The electrical measurements for table IVb (JANTX and JANTXV) of MIL-S-19500 are as follows:

a. Subgroup 2, see table II herein, steps 1 and 4.

b. Subgroup 3, see table II herein, steps 1, 4, 5, and 6.

c. Subgroup 6, see table II herein, steps 1, 4, 5, and 6.

3/ The electrical measurements for table V of MIL-S-19500 are as follows:


a. Subgroup 2, see table II herein, steps 1, 2, 3, and 4 (JANS); 1 and 4 (JANTX and JANTXV).

b. Subgroup 3, see table II herein, steps 1, 2, 3, and 4 (JANS); 1 and 4 (JANTX and JANTXV).


c. Subgroup 6, see table II herein, steps 1, 2, 3, 4, 5, 6, and 7 (JANS); 1, 4, 5, and 6 (JANTX and JANTXV).

4/ Devices which exceed the group A limits for this test shall not be acceptable.

Source: https://assist.dla.mil -- Downloaded: 202640-18T15:35Z
Check the source to verify that this is the current version before use.



TEST CIRCUIT A



TEST CIRCUIT B

NOTES:
1. The input waveform is supplied by a pulse generator with the following characteristics: $t_r \leq 2.0$ ns, $t_f \leq 1$ μs, 10 μs ≤ PW ≤ 100 μs, $Z_{OUT} = 50\Omega$, duty cycle ≤ 2%.
2. Output waveforms are monitored on an oscilloscope with the following characteristics: $t_r \leq 5$ ns, $Z_{in} \geq 100$ kΩ, $C_{in} \leq 12$ pF.
3. Test circuit A for t_d and t_r; test circuit B for t_s and t_f.

FIGURE 2. Pulse response test circuits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.




FIGURE 3. Maximum safe operating graph (dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.




FIGURE 4. Safe operating area for switching between saturation and cutoff (unclamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.





FIGURE 5. Safe operating area for switching between saturation and cutoff (clamped inductive load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.



* L = 4 mH, .05Ω, 20 A
Q ≥ 100 at 1 kHz
(Stanford Miller CK-20 or equivalent)

Procedure:
1. With switch S_1 closed, set the specified test conditions.
2. Open S_1. Device fails if clamp voltage not reached.
3. Perform specified end point tests.

FIGURE 6. Clamped inductive sweep test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-S-19500.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-S-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Issue of DODISS to be cited in the solicitation.

b. Lead finish may be specified (see 3.3.1).

c. Type designation and product assurance level.

6.3 Application guidance. Transistor types 2N3789 and 2N3790 were deleted by MIL-S-19500/379A(ER). The following show the replacement types:

Deleted transistors	Replaced by
2N3789	2N3791
2N3790	2N3792

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue because of the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Air Force - 17
Army - ER
NASA - NA
Navy - EC

Review activities:
Air Force - 19, 85, 99
Army - AR, MI
DLA - ES

User activities:
Air Force - 13
Army - AV, SM
Navy - AS, CG, MC, OS, SH

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5961-1312)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-S-19500/379D	2. DOCUMENT DATE (YYMMDD)

3. DOCUMENT TITLE: SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, HIGH_POWER, TYPES 2N3791, 2N3792 JANTX, JANTXV, AND JANS

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*)	d. TELEPHONE (*Include Area Code*) (1) Commercial (2) AUTOVON (*If applicable*)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Army Research Laboratory / EPSD	b. TELEPHONE (*Include Area Code*) (1) Commercial: 908-544-2414 (2) AUTOVON: 995-2414
c. ADDRESS (*Include Zip Code*) AMSRL-EP-RD Fort Monmouth, NJ 07703-2000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 — *Previous editions are obsolete.*

Source: https://assist.dla.mil -- Downloaded: 202610-18T15:35Z
Check the source to verify that this is the current version before use.