The documentation and process conversion measures necessary to comply with this amendment shall be completed by 15 July 2000.

INCH-POUND

MIL-PRF-19500/383B
AMENDMENT 1
15 April 2000

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE-VARIABLE CAPACITOR
TYPES 1N5139A THROUGH 1N5148A
JAN, JANTX AND JANTXV

This amendment forms a part of MIL-PRF-19500/383B, dated 6 August 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.3 Screening table, delete and substitute as follows:

"

Screen (see table IV of MIL-PRF-19500)	Measurements
	JANTX, JANTXV levels
2	T_A = +200°C, 48 hours
10	Not applicable
11	$I_{R;}$
12	See 4.3.1
13	Subgroup 2 of table I herein; ΔI_R = 100 percent of initial value or 5 nA dc whichever is greater.

"

4.3.1 delete and substitute as follows:

"4.3.1 h_{TRB} burn-in conditions. h_{TRB} burn-in conditions are as follows:

T_A = 175°C; V_R = 60 V dc, 96 hours."

PAGE 6

TABLE I, subgroup 2; delete entire Capacitance test.

TABLE I, subgroup 4; add the following test:

"

Capacitance 3/	4001	V_R = 4 V dc; f = 1 MHZ	C	Column 3	Column 4	pF

"

AMSC N/A FSC 5961
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:41Z
Check the source to verify that this is the current version before use.

Custodians:
Navy - EC
Air Force – 11
DLA – CC

Review activities:
Navy – AS, CG, MC, SH
Air Force – 99

Preparing activity:
DLA – CC

(Project 5961-2278)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:41Z
Check the source to verify that this is the current version before use.