MIL-S-0019500/381A(USAF)
14 January 1972
USED IN LIEU OF
MIL-S-19500/381(EL)
18 September 1968

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON
JAN, JAN TX AND JAN TXV TYPES
2N2034, 2N2858, 2N2859 AND 2N2911

This limited military specification has been prepared by the Department of the Air Force, but it has not been approved for promulgation as a coordinated revision of Military Specification Sheet MIL-S-19500/381(EL). This specification is subject to modification. However, pending its promulgation as a coordinated military specification, it may be used for procurement. The complete requirements for procuring the transistors described herein shall consist of this document, MIL-S-19500/381(EL) and the latest issue of MIL-S-19500.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for silicon, NPN transistors for particular use in amplifier and switching electronic-circuit applications. The prefix "TX" is used on devices meeting the special process-conditioning, testing, and screening specified in 4.4 of MIL-S-19500/381(EL). The prefix"TXV" will be used on devices submitted to and passing the Internal Visual (Precap) Inspection in accordance with Test Method 2072 of MIL-STD-750 and also meeting the special process-conditioning, testing, and screening requirements in 4.4 of MIL-S-19500/381(EL).

2. NOT APPLICABLE

3. REQUIREMENTS

3.1 "TXV" Special Requirements

3.1.1 Internal Visual (Precap) Inspection and Process-conditioning, testing, and screening. Internal visual (precap) inspection and process-conditioning, testing, and screening shall be in accordance with 4.4 of MIL-S-19500/381(EL).

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:37Z
Check the source to verify that this is the current version before use.

3.1.2 Marking of "TXV" Devices. Marking of devices conforming to "TXV" and all other applicable requirements shall include the prefix "TXV" immediately preceding the type designation.

4. QUALITY ASSURANCE PROVISIONS

4.1 Qualification Testing. The JAN types shall be used for qualification testing. Upon request to the qualifying activity, qualification will be extended to include the "TX" and "TXV" types of the devices.

4.2 Internal Visual (Precap) Inspection and Process-conditioning, Testing and Screening for "TXV" Types. The internal visual inspection shall be performed in accordance with Test Method 2072 of MIL-STD-750 prior to encapsulation on a 100% basis and process-conditioning testing and screening shall be as specified in 4.4.2 through 4.4.7.4 and Figure 2 of MIL-S-19500/381(EL). The manufacturer shall permit the authorized Government representative to witness concurrent with time of manufacturer's performance of these tests, the process-conditioning, testing and screening on the devices. These conditioning and screening tests normally performed by a manufacturer as standard production tests, need not be repeated when these are predesignated and acceptable to the Government as being equal to or more severe than the test specified therein.

Custodian:
Air Force - 17

Review activities:
Air Force - 11, 80

Preparing activity:
Air Force - 17

(Project 5961-F409)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:37Z
Check the source to verify that this is the current version before use.