MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED LOW POWER SCHOTTKY TTL,
OR GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/375(USAF), dated 18 March 1983, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, delete and substitute as printed above.

1.2.3, delete in its entirety and substitute:

"1.2.3 Case outline. The case outline shall be designated as follows:

Outline letter	Case outline (MIL-M-38510, appendix C)
A	F-1 (14-lead, 1/4" x 1/4"), flat package
B	F-3 (14-lead, 3/16" x 1/4"), flat package
C	D-1 (14-lead, 1/4" x 3/4"), dual-in-line package
D	F-2 (14-lead, 1/4" x 3/8"), flat package
2	C-2 (20-terminal, .350" x .350"), square chip carrier package"

1.3, thermal resistance, delete and substitute:

"Thermal resistance, junction-to-case (Θ_{JC}):
Cases A, B, C, D, 2 - - - - - - - - - - - - - (See MIL-M-38510, appendix C)"

1.3, junction temperature (T_J): Add "2/".

1.4, Recommended operating conditions, add "(V_{CC})" after supply voltage.

Add footnote 2/ to bottom of page as follows:

"2/ Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions in accordance with method 5004 of MIL-STD-883".

PAGE 2

3.2.4, delete and substitute:

"3.2.4 Schematic circuits. Schematic circuits shall be submitted to the preparing activity prior to inclusion of a manufacturer's device in the specification and shall be submitted to the qualifying activity and agent activity (DESC-ECS) as a prerequisite for qualification. All qualified manufacturers schematics shall be maintained by the agent activity and will be available upon request."

3.6, Marking: Delete the second sentence.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:31Z
Check the source to verify that this is the current version before use.

PAGE 3

TABLE I, Output current, I_O, minimum limits column: Delete "-30" and substitute "-20".

TABLE I, Propagation delay time, high to low level, t_{PHL}, maximum limits column: Delete "13" and substitute "14.5".

PAGE 4

TABLE II, Interim electrical parameters: Delete "(pre burn-in)".

4.2a(1): Delete "D or E" and substitute "D, E, or F".

4.2c, delete in its entirety and substitute:

"c. The percent defective allowable (PDA) shall be as specified in MIL-M-38510".

PAGE 5

4.4.3c(1): Delete "D or E" and substitute "D, E, or F".

4.4.3c(3): Delete "appendix B of MIL-M-38510" and substitute "method 1005 of MIL-STD-883".

6.1, delete in its entirety.

PAGE 6

FIGURE 1: Delete "Cases X,Y" and substitute "Case 2".

PAGE 8

FIGURE 4, Note 1: Delete "PRR = 1 MHz" and substitute "PRR ≤ 1 MHz".

PAGE 9

TABLE III: Delete "Cases X,Y" and substitute "Case 2".

PAGE 10

TABLE III: Delete "Cases X,Y" and substitute "Case 2".

TABLE III, Subgroup 10, test number column: Delete "67-74" and "75-82".

TABLE III, Subgroup 10, t_{PHL}, maximum limits column: Delete "13" and substitute "14.5".

TABLE III, footnote 4/, delete in its entirety and substitute: "4/ I_O limits shall be -20/-112 mA for circuit A and -30/-110 mA for circuit C".

CONCLUDING MATERIAL

Custodians:
Air Force - 17

Review activities:
Air Force - 19, 85, 99
DLA - ES

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-F721)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:31Z
Check the source to verify that this is the current version before use.