INCH-POUND

MIL-M-38510/385A
AMENDMENT 1
29 October 1992

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, ADVANCED LOW-POWER SCHOTTKY TTL, BUS TRANSCEIVERS WITH THREE-STATE OUTPUTS, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/385A, dated 4 January 1988 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, I_O, device type column: Add "06, 07".

TABLE I, I_O, minimum limits column: Delete "-30" and substitute "-20".

PAGE 4

TABLE I, t_{PLH1}, device types 01 and 05, maximum limits column: Delete "14" and substitute "15".

TABLE I, t_{PZL}, device types 01 and 05, maximum limits column: Delete "27" and substitute "30".

TABLE I, t_{PHZ}, device type 05, maximum limits column: Delete "16" and substitute "18".

TABLE I, t_{PLZ}, device types 01 and 05, maximum limits column: Delete "18" and substitute "20".

PAGE 24

TABLE III, device type 01, footnote 2/: Delete in its entirety and substitute: "2/ I_O limits shall be -20 mA minimum/-112 mA maximum for circuit A and -30 mA minimum/-110 mA maximum for circuit C".

PAGE 37

TABLE III, device type 04, footnote 2/: Delete in its entirety and substitute: "2/ I_O limits shall be -20 mA minimum/-112 mA maximum for circuit A and -30 mA minimum/-110 mA maximum for circuit C".

PAGE 39

TABLE III, device type 05, I_{IH2}, test numbers 103 through 118, $\overline{G}$ column: Add "„".

PAGE 42

TABLE III, device type 05, symbol column: Delete "t_{PHZ}", "t_{PLZ}", "t_{PZH}", and "t_{PZL}" and substitute "t_{PZH}", "t_{PZL}", "t_{PHZ}", and "t_{PLZ}", respectively.

TABLE III, device type 05, footnote 2/: Delete in its entirety and substitute: "2/ I_O limits shall be -20 mA minimum/-112 mA maximum for circuit A and -30 mA minimum/-110 mA maximum for circuit C".

PAGE 45

TABLE III, device type 06, footnote 3/: Delete in its entirety and substitute: "3/ I_O limits shall be -20 mA minimum/-112 mA maximum for circuit A and -30 mA minimum/-110 mA maximum for circuit C".

PAGE 48

TABLE III, device type 07, footnote 3/: Delete in its entirety and substitute: "3/ I_O limits shall be -20 mA minimum/-112 mA maximum for circuit A and -30 mA minimum/-110 mA maximum for circuit C".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:37Z
Check the source to verify that this is the current version before use.

6.5, generic-industry type column: Delete "54ALS645" and substitute "54ALS645/54ALS245".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1299)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:37Z
Check the source to verify that this is the current version before use.