MIL-F- 13376 (ORD)

16 April 1954

SUPERSEDING
PA-PD-53 (Rev 1)
19 January 1954

MILITARY SPECIFICATION

FUZES, DUMMY, M50, M50B1, M50B2, M50B3, M59 M69, M69B1, M69B2, AND M73

1. SCOPE

1.1 This specification covers the following dummy fuzes for use in ammunition used for target practice and drill:

M50	M69
M50B1	M69B1
M50B2	M69B2
M50B3	M73
M59	

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specifications, drawings, and publications, and all specifications, and drawings referenced thereon, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

MILITARY

MIL-G-2550	-General Specification For Ammunition Except Small Arms Ammunition
MIL-P-10025	-Packing And Marking For Domestic Shipment Of Inert Ammunition Components; General Specification For

DRAWINGS

ORDNANCE CORPS

72-5-4	-Fuze, Dummy, M50, M50B1, M50B2, And M50B3
72-5-5	-Fuze, Dummy, M59, Assembly
72-5-9	-Fuze, Dummy, M69, M69B1, And M69B2 (For 40mm
72-5-11	-Fuze, Dummy, M73, Assembly And Details

PUBLICATIONS

ORDNANCE CORPS

ORD-SIP-M7-19	-Fuze, Dummy, M73

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:28Z
Check the source to verify that this is the current version before use.

ORD-SIP-M7-21 -Fuze, Dummy, M59
ORD-SIP-M7-22 -Fuze, Dummy, M50, M50B1, M50B2, M50B3 M69, M69B1, And M69B2

(Copies of specifications, standard, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Material and parts shall be in accordance with applicable specifications and drawings.

3.2 The dummy fuzes shall comply with all requirements specified on Drawings 72-5-4, 72-5-5, 72-5-9 or 72-5-11, as applicable, and all drawings referenced thereon, and with all requirements specified in applicable specifications.

3.3 Fracture test (not applicable to M59 and M73 Fuzes).-The fuzes shall withstand being dropped twice from a height of 60 inches without fracture when tested as specified in 4.4.

3.4 Anchoring of insert (applicable only if insert is used to obtain required weight).-The inserts shall withstand the dead load, computed as specified on the drawing, without evidence of displacement when tested as specified in 4.5. (This test not applicable to M59 and M73 Fuzes.)

3.5 Workmanship.-All parts shall be free from chips, dirt, grease, and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents used.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Lot.-A lot shall consist of all dummy fuzes produced by one manufacturer, under one contract, in one unchanged process, in accordance with the same drawing, same drawing revision, the same specification, and the same specification revision.

4.2 Sampling.-Numbers of samples, acceptance and rejection criteria used for determination of lot acceptance for tests as specified in 4.4 and 4.5 shall be in accordance with Standard Inspection Procedures ORD-SIP-M7-19, ORD-SIP-M7-21, or ORD-SIP-M7-22, as applicable.

4.3 Inspection.-Inspection shall be as specified in Specification MIL-C-2550.

4.4 Fracture test (not applicable to M59 and M73 Fuzes)

4.4.1 Procedure.-Half of the sample fuzes shall be conditioned at 160° ± 2°F and half at -65° ± 2°F for a minimum of 24 hours. Within one minute after removal from the conditioning temperature, each sample fuze shall be assembled and tested as follows: Each fuze shall be threaded into a steel cylinder weighing 16 ± 0.5 ounces, having a diameter of 1-15/16 inches and a length of approximately 3 inches, so that the shoulder of the fuze rests on the cylinder. Each test assembly shall be dropped twice, fuze vertically down, from a height of 60 inches so that the point of the fuze impacts on a concrete test block. Each sample fuze shall be observed for evidence of fracture, to determine compliance with 3.3. Deformation or chipping of the point of the fuze will not be cause for rejection.

4.5 Anchoring of insert test (applicable only if an insert is used to obtain required weight)

4.5.1 Procedure.-A portion of the nose end of the sample fuzes shall be removed so as to expose the end of the inserts. A portion of the fuzes shall be conditioned at 160° ± 2°F, a portion at -65° ± 2°F, and the remaining at 70° ± 2°F for a minimum of 24 hours. Within one minute after removal from exposure to the conditioning temperature, each sample fuze shall be threaded in

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:28Z
Check the source to verify that this is the current version before use.

a fixture satisfactory to the inspector and a load applied against the end of the insert parallel to the longitudinal axis of the fuze, tending to force the insert out of the base end of the fuze. This test shall be performed to assure compliance with 3.4. The total load shall be computed as specified on the drawing.

5. PREPARATION FOR DELIVERY

5. 5.1 Packing, labeling, and marking.-Packing, labeling, and marking shall be as specified in Specification MIL-P-10025.

5.2 Data cards.-Data card information shall be as specified in Specification MIL-G-2550.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, and date of this specification.

Notice.-This specification, together with specifications, drawings, and publications pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Custodian:

Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:28Z
Check the source to verify that this is the current version before use.