INCH-POUND

MIL-P-13392B (AR)
AMENDMENT 4
25 June 1998
SUPERSEDING
AMENDMENT 3
5 November 1987

MILITARY SPECIFICATION

PRIMER, PERCUSION, M54 PARTS FOR AND LOADING, ASSEMBLING AND PACKING

MIL-P-13392 was inactivated after 22 April 1996 for new design.

This amendment forms a part of MIL-P-13392B (AR), dated 21 February 1969, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved for use within the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense."

2.1 Specifications, Military, add:

"MIL-D-14951 – Delay Element M53, Loading, Assembling and Packing."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:29Z
Check the source to verify that this is the current version before use.

4.2.1 Delete in its entirety and substitute the following:

"4.2.1 Submission. The contractor shall submit a first article sample (see 6.1c) as designated by the Contracting Officer for evaluation. The first article sample shall consist of the following:

a. 125 each of every component part, component subassembly, and final assembly for examination (see 4.2.2).

b. 400 each final assemblies for sensitivity testing (see 4.3.3.1.1).

c. 125 each final assemblies for output testing (see 4.3.3.1.2).

d. 300 each final assemblies for dud testing (see 4.3.3.1.3).

All parts, subassemblies and final assemblies shall have been produced by the contractor or furnished by a supplier using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and he shall submit a record of this inspection with the sample, including statements of findings and certification of conformance of materials (see 4.1.1c). A sample containing known defects shall not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:29Z
Check the source to verify that this is the current version before use.

PAGE 5

4.2.2 Delete in its entirety and substitute the following:

"4.2.2 Inspections to be performed. Components parts, component subassemblies and final assemblies will be subjected by the Government to any or all of the examinations specified in 4.3.2 of this specification and any or all requirements of the applicable drawings."

PAGE 7

* 4.3.2.3 Delete "Primer assembly, prior to inserting (see dwg. 8840607)" and substitute "Primer assembly, after composition is loaded (see dwg. 8840607)"

PAGE 8

* 4.3.2.4 Delete "Category major" in its entirety.

* 4.3.2.5 Primer Assembly, Major Defects:

Delete "103. Loose composition on anvil or cup…Visual 05004"

PAGE 14

4.4.1.2 Delete in its entirety and substitute the following:

"4.4.1.2 Output. The primer assembly shall be assembled with the 0.05 second M2 Delay Element. The M2 Delay Element assembly shall be assembled in the firing fixture specified in 4.3.4 and fired by dropping a steel ball weighing 1.94 plus or minus 0.02 ounces on the firing pin from a height of ten (10) inches, maximum. The drop height is the distance between the bottom of the ball and the top of the firing pin. Observations shall be made for compliance with the requirements."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:29Z
Check the source to verify that this is the current version before use.

* 4.4.1.2 Output, add at the end of the paragraph:

"When the M54 primer is to be used in the M53 Delay, the primer is to be seated into the M53 Delay Primer holder and subsequently assembled into M53 Delays and output tested in approved M53 testing fixtures."

6.4.3h:

Line 2: Delete "maximum weight" and substitute "actual weight".

Line 4 and 5: Delete "minimum weight" and substitute "actual weight".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - AR

Preparing activity:
Army – AR

Project (1375-0073)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:29Z
Check the source to verify that this is the current version before use.