MIL-S-13387(MU)
AMENDMENT 1
25 March 1970

MILITARY SPECIFICATION

SIGHT, REFLEX: M18

This amendment forms a part of Military Specification MIL-S-13387(Ord), dated 20 April 1954.

Paragraph 2.1, under Drawings: Add:

"F8565556 Pressure Tester - Two Station: 8565556"

Following paragraph 3.12 add new paragraph 3.13 Sealing:

"3.13 Sealing.- The sight (body assembly) shall withstand an internal pressure of five (5) psi of dry nitrogen gas for one hour without showing a pressure drop in excess of 0.05 psi. Subsequent to the above, the interior atmosphere of the body assembly shall have a dew point of -25°F."

Following paragraph 4.6: Add new paragraph 4.7 Sealing:

"4.7 Sealing.- This test shall be performed using testing equipment the accuracy of which shall conform to the accuracy depicted on Drawing F8565556. The fixture shall be set-up as outlined in set-up instructions shown on Drawing F8565556, Sheet 1. The gas used shall be dry nitrogen having a dew point of -25°F. After connecting the test fixture to the sight (body assembly), adjust testing pressure to the pressure specified in 3.13 and maintain the pressure for time specified. At the completion of this test, connect a dew point tester to the exit port and purge the sight until -25°F is recorded and seal the unit."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A233

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:29Z
Check the source to verify that this is the current version before use.