MIL-S-13448A(WC)
12 March 1968
SUPERSEDING
MIL-S-13448(ORD)
20 May 1954
(See 6.3)

MILITARY SPECIFICATION

SIGHT, RIFLE GRENADE LAUNCHER, M15

1. SCOPE

1.1 This specification covers one type of sight for rifles and carbines when launching grenades.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116 - Preservation, Method of
MIL-W-13855 - Weapons, Samll Arms, General Specification for

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions

DRAWINGS

U. S. Army Weapons Command

F7310089 - Sight, Grenade Launcher, M15
D7311859 - Plate, Mounting

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:33Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

U. S. Army Weapons Command

P7310089 - Packaging Data Sheet for Sight, Grenade Launcher, M15

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings referenced on Drawing F7310089.

3.2 Design. The sight shall be of the design specified on drawings referenced on Drawing F7310089.

3.2.1 Staking. Screws shall be staked to prevent loss. The screws shall be staked in such a manner as to allow the screws to be loosened for final adjustment of horizontal and vertical zero.

3.2.2 Serrations. The serrations on the mounting plate shall be smooth, well formed, and free of burrs to insure proper operation of the sights.

3.2.3 Functioning. Movable parts of the sight shall function smoothly and without undue friction or looseness, but shall give positive clicks in each position.

3.3 Marking. Unless otherwise specified, each sight shall be marked in the positions and sizes specified on the applicable drawings and in accordance with MIL-W-13855.

3.4 Workmanship. Workmanship shall be in accordance with the workmanship requirements of MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspections. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:33Z
Check the source to verify that this is the current version before use.

specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection terms. Inspection terms and definitions used herein shall be in accordance with MIL-STD-109.

4.2 Sampling.

4.2.1 Inspection lots. Unless otherwise specified in the contract or order, a lot shall consist of all sights presented for inspection at one time from one manufacturer.

4.2.2 Sampling for function test. A random sample of sights shall be taken from each lot in accordance with MIL-STD-105, Inspection Level S-3, with an AQL of 0.65 percent defective.

4.2.3 Sampling for inspection of preservation, packaging, and packing. Sampling shall be in accordance with the applicable Inspection Levels of MIL-STD-105, as specified in MIL-P-116.

4.2.4 Sampling for examination. A random sample of sights shall be taken from each lot in accordance with MIL-STD-105, Inspection Level II. The Acceptable Quality Levels should be as specified in Table I.

4.3 Examination.

4.3.1 Each sight taken as specified in 4.2.4 shall be examined to verify compliance with this specification. Examination shall be conducted in accordance with Table I.

Table I Classification of Defects

Categories	Defects	Inspection Method
Critical	None defined	
Major	AQL = 1.5 percent defective	
101	Hardness	SIE *
102	Elevation adjustment	Manual & Visual
103	Serrations	Visual
104	Functioning of moving parts	Manual & Visual
105	Staking of screws	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:33Z
Check the source to verify that this is the current version before use.

Minor		AQL = 4.0 percent defective	
201	Marking		Visual
202	Incorrect or missing part number		Visual
203	Discontinuity or absence of protective coating		Visual
204	Workmanship		Visual
205	Surface roughness		Visual

* - Standard Inspection Equipment

4.4 Tests.

4.4.1 Materials. The contractor shall certify that the materials used in the manufacture of the sights are in accordance with the specifications referenced on the applicable drawings.

4.4.2 Functioning. Each sight selected as specified in 4.2.2 shall be tested manually by operation through the full range of sight adjustment. The sights shall be checked by assembling to a mounting plate (D7311859) and turned through the full range of elevation to insure positive action of all click indents.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking. Preservation, packaging, packing and marking shall be in accordance with the requirements of Packaging Data Sheet P7310089.

6. NOTES

6.1 Intended use. This sight is intended to be used as an aiming device for rifles and carbines when firing grenades.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. List of drawings and specifications.
c. Level of protection (5.1).

6.3 This specification also supersedes U. S. Army Specification 52-5-26 in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:33Z
Check the source to verify that this is the current version before use.

Custodian:
Army - WC

Preparing Activity:
Army - WC

Review activities:
Army - WC

Project No. 1005-A385

User Activities:
None

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:33Z
Check the source to verify that this is the current version before use.