MIL-T-13446D (AR)
AMENDMENT 1
29 May 1988

MILITARY SPECIFICATION

TELESCOPES, ELBOW: M16 SERIES, M116 SERIES AND XM139

This Amendment forms a part of Military Specification MIL-T-13446D (MU), dated 20 Aug 1973 and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

Title: Add "(M139)". Make this addition wherever "XM139" is in specification.

PAGE 4

3.5: Delete and substitute:

"3.5 Sealing. The telescope shall be subjected to an internal pressure of 5.0 ± 0.10 psig using dry nitrogen having a dew point of -25°F. After a period of two hours there shall be no leakage in excess of 0.2 psig."

3.5.1: Add the following paragraph:

"3.5.1 Purging. The telescope shall be purged with dry nitrogen supplied at 5.0 ± 0.25 psig until the dew point of the emergent gas is a maximum of -25°F.

PAGE 7

Table 1:

Critical: Delete "None" and substitute "100% inspection".

Add the following critical examinations:

"1. Sealing	3.5	4.8
2. Purging	3.5.1	4.8.1"

Delete "AQL 1.0" and substitute "AQL .65".

Delete Characteristic 103 and substitute:

"103	Fabrication	3.1	Visual - per applicable drawings and specifications."

AMSC N/A

FSC 1290

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:33Z
Check the source to verify that this is the currentversion before use.

Add the following major examinations:

"112, General Spec Requirements 3.2 Visual - MIL-F-13926 and MIL-O-13830".

PAGE 8

4.4: Delete:

"Fabrication	3.1	Visual - per applicable drawings and specs..
"Gen. Spec. Requirements	3.2	Visual - MIL-F-13926 and MIL-O-13830".

PAGE 9

4.8: Delete and substitute:

"4.8 Sealing. The telescope shall be attached to the pressure testing fixture, Two Station, F8565556 or any approved equivalent. The testing shall be pressurized with dry nitrogen gas to the required pressure and for the period of time specified in paragraph 3.5. Leaks in sealing of the telescope shall be detected on the pressure gage of the fixture to determine compliance with the requirements of paragraph 3.5,".

4.8.1: Delete and substitute:

"4.8.1 Purging - Attach Adapter Assembly, C10552433, or equivalent, to the telescope's purging entrance port. Connect the test equipment to the adapter. Remover the telescope's purging exit port screw. Adjust the dry nitrogen pressure to the pressure specified in 3.5.1. The pressure shall remain constant (5 + .25 psig) until the dew point of the emnergent gas is no higher than -25°F, to meet the requirements of 3.5.1."

4.9, line 10: Delete "A standard target collimator, F7573921, shall....." and substitute "A standard target collimator, F7573291, or a similar device, shall.....".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1290-A416)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:33Z
Check the source to verify that this is the current version before use.