INCH-POUND

MIL-D-16475/79(CG)
16 October 1990

# MILITARY SPECIFICATION SHEET
# DEVICES, METAL, (BREAST AND COLLAR)
# AUXILIARY, AVIATOR (U.S. COAST GUARD)

This specification sheet is approved for use by the United States Coast Guard, Department of Transportation, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the insignia described herein shall consist of this document and the latest issue of Specification MIL-D-16475.



Size: Regular and Miniature

Material: Brass

Design: Government hub

Color: Silver

Guide Sample: Available for finish and workmanship.

| Dimensions (inches) | Regular (overall) | Miniature (overall) |
|---|---|---|
| Width | 2-25/32 | 13/16 |
| Height | 11/16 | 3/8 |
| Tolerance (inches) | ± 1/32 | ± 1/32 |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Officer in Charge, Navy Clothing and Textile Research Facility, P.O. Box 59, Natick, MA 01760-0001, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:09Z
Check the source to verify that this is the current version before use.

| Dimensions (inches) | Regular (overall) | Miniature (overall) |
|---|---|---|
| Thickness: (Minimum) (at thickest point) | 0.085 | 0.065 |
| Tolerance (inches) | ± 0.005 | ± 0.005 |

Finish: Entire device: Nickel plated.

Wings and Anchors: Bright Rhodium finish.

Recessed area (background for lettering): Hard fired blue enamel conforming to TIOH color chip No. 18.

Balance of center design: 24K gold electroplated, bright polished.

Completed insignia: Lacquered with clear synthetic lacquer.

Forcer: No forcer permitted.

Placement of Attachment: Two prongs and two clutch fasteners are required. The prongs shall be centered onto the longest horizontal dimension equidistant from each end and measuring between their centers 1-7/8 (± 1/32) inches for regular and 3/4 (± 1/32) inch for miniature.

Where used: U.S. Coast Guard Auxiliary uniform breast insignia.

Note: 1. The figure is for information purposes only.
2. Preservation and packing shall be standard commercial practice.

Custodian:
Navy - NU

Review activity:
DLA - CT

User activity:
Navy - CG

Preparing activity:
Navy - NU

Project No. 8455-N465



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:09Z
Check the source to verify that this is the current version before use.