INCH-POUND

MIL-E-46717G
AMENDMENT 1
22 February 1990

MILITARY SPECIFICATION

ENGINES, GASOLINE: AIR-COOLED, INDUSTRIAL TYPE,

4-CYCLE, MILITARY-DESIGN

This amendment forms a part of MIL-E-46717G, dated 12 August 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 17

4.6.2.3, line 2, after MIL-L-2104, delete "grade 30," and substitute "grade 15W/40,"; line 4, delete "grade 30.", and substitute "grade 15W/40."

PAGE 34

20.1.1, under FEDERAL SPECIFICATION, delete, "VV-G-1690, Gasoline, Automotive, Leaded or Unleaded."

Add the following new paragraph:

"20.3 Non-Government documents.

ASTM D 439 - Gasoline, Leaded or Unleaded"

PAGE 41

2.2.5 a. in its entirety and substitute:

"a. Fuel for the test shall be in accordance with ASTM D 439 regular grade, class A, lead content 4.23 gm/gal maximum, Reid vapor pressure less than 63 KPa. Lubricating oil for the test shall be in accordance with MIL-L-2104, grade 15W/40. A certified chemical analysis shall be required for each new batch of fuel and lubricating oil."

Custodians:
Army - ME
Navy - YD

Preparing activity:
Army - ME

Project 2805-0557

Review activities:
Army - SM

User activities:
Army - AT, AV, GL
Navy - MC

AMSC N/A FSC 2805

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.