INCH-POUND
MIL-PRF-46720C
AMENDMENT 1
13 February 1998

PERFORMANCE SPECIFICATION

VALVE, SOLENOID

This amendment forms a part of MIL-PRF-46720C, dated 15 December 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Line 3: Delete “9008233” and substitute “9098233”.

PAGE4

3.3.2, line 2: Delete “(1724 kPa)” and substitute “to 3000 psi (1724 kPa to 20685 kPa)”.

PAGE 6

3.4.1, line 3: Delete “9008233” and substitute “9098233”.

PAGE 7

3.6.6, line 2: Delete “3.3.6” and substitute “3.5.1”.

PAGE 8

3.6.8: Delete the entire paragraph and substitute “The valve shall withstand exposure to humidity and subsequent performance conforming to 3.3.5 and 3.3.6”.

PAGE 9

Table I, line 3: Delete “3.4.9” and substitute “3.4.4”.

PAGE 10

Table I: Delete the footnote.

Custodian:
Army - AT

Preparing Activity:
Army - AT

Review Activity:
DLA - CC

(Project 2590-0263)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:47Z
Check the source to verify that this is the current version before use.