MILITARY SPECIFICATION

TRAILER, PIPE; FUEL LINE 25 TON

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a 25-ton load capacity, pipe carrying trailer made up of two dollies, each mounted on two dual wheels and connected in tandem with an adjustable-length reach bar.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-W-3912 - Wood Parts and Wood Substitutes, Fabricated; for Transport Vehicle Bodies and Similar Applications.

STANDARDS

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions.
MIL-STD-281 - Automobiles, Trucks, Truck Tractors, Trailers and Trailer Dollies; Preservation and Packaging of.
MIL-STD-1223 - Nontactical Wheeled Vehicles; Treatment, Painting, Rustproofing, Identification Marking and Data Plate Standards.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

DRAWINGS

NAVAL FACILITIES ENGINEERING COMMAND

1109813 - Ship to Shore Bulk Fuel Delivery System (Bottom Laid) 4" & 6" for Amphibious Operations Pipe Trailer.
1109814 - Ship to Shore Bulk Fuel Delivery System (Bottom Laid) 4" & 6" for Amphibious operations Pipe Trailer Details.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as Department of Defense adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

* 3.1 First production vehicle. When specified (see 6.2), the contractor shall furnish one trailer for first production vehicle inspection (see 4.2.1).

3.2 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.3 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.4 Weight and payload.

3.4.1 Net weight. The net weight of the fully equipped trailer shall be the minimum practicable for the service intended.

3.4.2 Payload. The rated payload capacity of the trailer in the extended and retracted position shall be not less than 50,000 pounds (lb).

3.5 Performance. The fully equipped trailer shall meet the performance requirements specified herein with no evidence of failure, malfunction, or permanent deformation. The trailer shall meet these requirements when operated in either the extended or retracted position, and with or without the rated payload. The payload shall be evenly distributed and shall span between, and be firmly secured to, the two platforms of the trailer.

3.5.1 Towing speed. The trailer shall transport the rated payload over unimproved roads and cross-country terrain (see 6.4), at speeds up to 6 miles per hour (mph).

3.5.2 Turning ability. When coupled to the towing vehicle, operated in its minimum turning circle, the trailer shall follow the towing vehicle without cramping. The trailer shall assume an angle of not less than 90° with the longitudinal axis of the towing vehicle without cramping or damage to the trailer or towing vehicle.

3.5.3 Fording ability. Trailer shall transport the rated payload when fording hard-bottom crossing in fresh or salt water of a sufficient depth to submerge the running gear.

3.6 Construction and components. Trailer shall be constructed in accordance with Drawings 1109813 and 1109814, and as specified herein.

3.6.1 Axles. Axles and axle components shall have a rated capacity at least equal to the load imposed on each axle, measured at the ground, with rated payload distributed on the trailer as specified in 3.5, except that each axle shall have a rated capacity of not less than 30,000 lb.

3.6.2 Wheels, rims, tires, and tubes. Trailer shall be mounted on four dual wheels. Rims and tire ratings shall conform to TRA recommandations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

3.6.2.1 Tires. Tires shall be in accordance with Drawings 1109813 and 1109814. Tires shall be of not less than 100 level quality.

3.6.2.2 Tubes. Tubes shall be heavy-duty type and shall be of proper size for tires furnished. Tire flaps shall be provided in accordance with TRA recommendations.

3.6.2.3 Wheel bearings. Wheel bearings shall be sealed against entry of dust and fresh or salt water.

3.6.2.4 Wheel nut wrench. A wheel nut wrench shall be provided and securely fastened in one of the toolboxes.

3.6.3 Tongue and universal hitch. A tongue and universal hitch shall be provided on the trailer in accordance with Drawing 1109813. When specified (see 6.2), a second identical tongue and universal hitch shall be furnished complete with two hinge bolts.

3.6.4 Flooring. Platforms shall be floored with hardwood of the types of lumber listed in table 1 of MIL-W-3912. Flooring shall be laid lengthwise and shall be full length boards. Floorings shall be finished to size and installed in accordance with Drawings 1109813 and 1109814.

3.6.5 Stake pockets. Stake pockets shall be provided in accordance with Drawings 1109813 and 1109814.

3.6.6 Stakes. When specified (see 6.2), metal stakes; shall be furnished in accordance with Drawings 1109813 and 1109814.

3.6.7 Safety chains. Two safety chains, conforming to SAE J697, shall be furnished. Cables are not acceptable. When a second identical tongue and universal hitch is furnished (see 3.6.3), a second set of safety chains shall also be furnished. A grab hook shall be provided on the free end of each chain. The hook shall be capable of passing through a 2-inch diameter opening.

3.6.8 Toolboxes. Two toolboxes shall be provided in accordance with Drawing 1109813.

* 3.7 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pounds-force per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.8 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

* 3.9 Data plates.

3.9.1 Instruction plates. The trailer shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment, and shall be securely affixed thereto with nonferrous screws or bolts of not less than 1/8-inch diameter.

3.9.2 Identification plate. An identification plate will be furnished by the contracting officer for each trailer. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each trailer in a conspicuous place with brass screws or bolts not less than 1/8 inch in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

3.10 Rustproofing. When specified (see 6.2), the trailer shall be rustproofed in accordance with MIL-STD-1223.

3.11 Wood treatment. Wood, except apitong, shall be treated in accordance with requirements of MIL-STD-1223, except manufacturer's method, which provides equivalent protection, may be substituted with approval of the contracting officer.

3.12 Servicing and adjusting. Prior to acceptance of the trailer by the Government inspector, the contractor shall service and adjust the trailer for immediate operational use. The servicing and adjusting shall include at least the following: Inflation of all tires, and complete lubrication with grades of lubricants recommended for the ambient temperature at the delivery point. The trailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.13 Lifting and tiedown attachments. The trailer shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the trailer. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the trailer on the carrier when shipped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

3.14 Workmanship.

* 3.14.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

* 3.14.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.14.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.14.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

* 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production vehicle inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First production vehicle inspection. The first production vehicle produced under the contract shall be inspected by the contractor at his plant

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

under the direction and in the presence of Government representatives. This inspection shall include the examination of 4.3 and the tests of 4.4. The purpose of the inspection shall be to determine vehicle conformity with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its right under the provisions of the contract (see 3.1 and 6.2).

* 4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4.5, and the packaging inspection of 4.5.

4.3 Examination. Each trailer shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests.

4.4.1 Weight and weight distribution. The trailer shall be weighed to determine curb weight and distribution of curb weight on front and rear axles. The weight distribution shall be computed using the curb weight and payload as specified in 3.4.2 and distributed as specified in 3.5. The calculated imposed loads on the front and rear axles shall be utilized to ascertain that the axles are of adequate capacity to meet requirements of 3.6.1.

4.4.2 Road test. The trailer, fully equipped and loaded with rated payload distributed as specified in 3.5, shall be towed at speeds from 5 to 7 mph for a distance of not less than 50 miles. The road test distance shall consist of 50 miles of cross-country terrain (see 6.4.2). Upon completion of the road test, the trailer shall be examined for any evidence of interference, part failure, damage, or other defects.

4.4.3 Turning ability test. The trailer, with rated payload, shall be tested to verify conformance to the requirements in 3.5.2.

4.4.4 Fording test. The trailer, with rated payload, shall be tested to verify conformance to the requirements in 3.5.3. Upon completion of the fording test, the wheel bearings shall be examined to verify conformance to the requirements in 3.6.2.3.

4.4.5 Production trailer tests. The contractor's testing system shall, as a minimum, assure that the trailer is capable of meeting performance requirements contained herein.

4.5 Packaging inspection. The vehicle shall be inspected to verify conformance to the requirements of section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Vehicle processing. The equipment shall be preserved and packaged in accordance with the contractor's standard practice. When specified (see 6.2), equipment shall be preserved and packaged in accordance with the mobile requirements of MIL-STD-281 with the level of preservation and packaging as specified (see 6.2).

6. NOTES

6.1 Intended use. The trailer covered in this specification is intended for use in transporting fuel line pipes in construction of ship-to-shore bulk fuel delivery systems.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Specifications and standards (see 2.1.1).
c. When a first production vehicle is required for inspection and approval (see 3.1 and 4.2.1).
d. When second tongue and universal hitch is required (see 3.6.3).
e. When metal stakes are required (see 3.6.6).
f. When lubrication shall be other than the manufactures standard practice (see 3.7).
g. Color of finish coat specified (see 3.8).
h. When rustproofing is required (see 3.10).
i. When preservation and packaging in accordance with MIL-STD-281 is required and the level of preservation and packaging required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 Contract Data Requirements List (CDRL) and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 Definitions.

6.4.1 Unimproved road. An unimproved road is an unpaved, unstabilized road with an undulating surface having occasional chuckholes and exposed rocks.

6.4.2 Cross-country terrain. Cross-country terrain consists of open fields, broken ground, and uneven terrain in general.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Navy - YD

Review activity:

Army - AT

Preparing activity:

Navy - YD

(Project 2330-0831)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commander
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side) 2330--0831

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-46715E	TRAILER, PIPE; FUEL LINE 25 TON

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:46Z
Check the source to verify that this is the current version before use.