[INCH-POUND]
A-A-55527
June 9, 1997

COMMERCIAL ITEM DESCRIPTION

FILLERS FOR ROTARY SWEEPER BRUSH: FOR SWEEPER, FRONT MOUNTED OR TOWED TYPE

The General Services Administration has authorized the use of this commercial item description (CID) for al l federal agencies.

1. SCOPE. This CID covers the general requirements for flat ring, tufted, steel fillers for high speed rotary sweepers. Fillers covered by this CID are intended for commercial/industrial applications.

2. CLASSIFICATION. This CID uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see 6.1).

AA55527	-	001
*		*
*		*
CID number		Dash number (see table I)

3. SALIENT CHARACTERISTICS.

3.1 Design and construction. Fillers supplied to this CID shall be as specified herein.

3.2 Environmental conditions. The fillers shall satisfactorily withstand storage temperatures ranging from -60°F to +160°F and operating temperatures ranging from -40°F to +125°F.

3.3 Operating conditions. The fillers shall be for use on sweepers that operate at 0-800 rpm broom core rotational speed.

3.4 Performance. When operated on concrete runways at a sweeping speed of 35 mph, a rotational speed of 500 rpm and with a brush pattern of not less than 2 inches but not greater than 4 inches, a new filler shall be capable of operating satisfactorily for a minimum of 160 hours. The loss of wire 2 inches or longer throughout the life of the filler shall not exceed 2 percent of the overall initial weight of the filler. The fillers shall maintain this performance at any operational temperature in the range specified in 3.2.

3.5 Ring. The ring shall be made of material conforming to Unified Numbering System designation G10180 steel. The ring shall have a thickness through the center of 1 inch ±1/16 inch. The inside diameter of the ring shall be as indicated in table I. Each ring shall have steel drive pin(s)/lug(s) to engage the sweeper core.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Industrial Supply Center, ATTN: DISC-ECA, 700 Robbins Avenue, Philadelphia, PA 19111-5096, or telephone (215) 697-3007, or facsimile (FAX) (215) 697-4534.

AMSC N/A FSC 3825

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.

3.6 Wire bristles. The wire bristles shall be made of material conforming to SAE J403 (1070) steel with regular zinc flash. The bristles shall be 0.018-0.020 inch diameter. The bristles shall be crimped with not less than 3 crimps per inch at a crimp amplitude of 1/16 inch minimum. The regular zinc flash coating shall be applied at not less than 0.01 ounce per square foot. The tensile strength of the wire shall be in the range of 310,000-355,000 pounds per square inch after crimping.

3.7 Tufts. The wire shall be formed into tufts. Each tuft shall consist of not less than 240 sweeping ends. There shall be 16 tufts per 36 inch filler and 28 tufts per 46 inch filler. All tufts shall be mounted with a cup and/or damper ring extending a minimum of 3-1/2 inches up the length of the tuft for support.

3.8 Bristles and tuft attachment. All bristles and tufts shall be secured to the ring so as not to allow for loss of bristles or tuft assemblies during use or storage. The outside diameter of the filler shall be as indicated in table I.

Table I. Filler sizes.

CID dash number AA55527-	Inside diameter (-0 +1/8 inch)	Outside diameter (±1/2 inch)
001	10-3/4 inches	36 inches
002	19-1/2 inches	46 inches

3.9 Marking. Marking shall be permanent and legible and shall include, as a minimum: the manufacturer's (MFGR) Commercial and Government Entity (CAGE) code, a lot number or date of manufacture, and the MFGR's commercial part number on each filler.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4.2 Bid sample criteria. When specified in the contract or purchase order, a bid sample shall be inspected to determine compliance with the requirements specified in section 3.

4.3 Market acceptance. The following market acceptance criteria are necessary to document the quality of the product to be provided under this CID:

4.3.1 The company producing the item must have been producing a product meeting the requirements of this CID for at least 18 months.

4.3.2 The company must have sold 2,500 units meeting the requirements of this CID in the commercial marketplace over the past 12 months.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example.

6.2 Ordering data. The contract or order should specify the following:

a. CID document number and revision.

b. CID PIN.

c. Quality assurance provisions.

d. Packaging requirements.

6.3 Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

MFGR's CAGE	MFGR's Name and Address
0Y6C3	BESTA H F NYBYLAVEGI 18 KOPAVOGUR 202 ICELAND S4801A/SC1002
3AJ66	SWEEPER BRUSHES INC P.O.BOX 344 BARRIE, ON L4M 4T5 CANADA
32157	SWEEPSTER, INC. 2800 N. ZEEB ROAD DEXTER, MICHIGAN 48130-9797
64096	UNITED ROTARY BRUSH CORP. 20078 STATE ROUTE 4 MARYSVILLE, OHIO 43040-9583

6.4 Part number (P/N) supersession data. This CID supersedes the following manufacturer's P/Ns as shown. This information is being provided to assist in reducing proliferation in the government inventory system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.

Dash number (see table I) AA55527-	MFGR CAGE	MFGR P/N
001	0Y6C3 3AJ66 64096	109-1191516 TW103436018 11-103360WWT
002	0Y6C3 3AJ66 64096	109-2011728 TW19546018 11-191460WWT

NOTE: The manufacturer's P/N shall not be used for procurement to the requirements of this CID. At the time of preparation of this CID, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown.

6.5 Government users. To acquire information on obtaining these fillers from the Government inventory system, contact Defense Industrial Supply Center, ATTN: DISC-HCB, 700 Robbins Avenue, Philadelphia, PA 19111-5096, or telephone (215) 697-2323.

6.5.1 NSNs. The following is a list of NSNs assigned which correspond to this CID. The list is for information only and may not be indicative of all possible NSNs associated with the CID. For up-to-date information on assigned NSNs, please contact the Defense Industrial Supply Center, ATTN: DISC-HCB, 700 Robbins Avenue, Philadelphia, PA 19111-5096, or telephone (215) 697-2323.

Dash number (see table I) AA55527-	NSN
001	3825-01-444-3682
002	3825-01-444-3684

MILITARY INTERESTS:

Custodians:
Air Force - 99
Army - ME
DLA - CS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity:

DLA-IS

Project 3825-0240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.