[INCH-POUND]
A-A-55534/3B
28 June 2018
SUPERSEDING
A-A-55534/3A
23 December 2002

COMMERCIAL ITEM DESCRIPTION

RESISTOR, FIXED, WIRE WOUND OR METAL ELEMENT, (POWER TYPE) STYLE VLV3

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

* The complete requirements for procuring of a fixed, wirewound or metal element resistor described herein shall consist of this document and the issue in effect of A-A-55534.

* CLASSIFICATION OR PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the PIN as shown in the following example (see NOTES).

AA55534/03	-	R010	F	B
CID number		Resistance value	Resistance tolerance	Termination finish

NOTE: This PIN has been derived in accordance with A-A-55534.

SALIENT CHARACTERISTICS

* Interface and physical dimensions. Resistors supplied to this CID specification sheet shall be as specified herein (see figure 1).

Resistance value. The resistance value shall be 0.005 ohm to 0.9 ohm.

Resistance tolerance. This style resistor is available in resistance tolerances F, H, and J (±1 percent, ±3 percent, and ±5 percent respectively).

Termination finish. The termination finish shall be identified by a single letter, B for tin/lead (Sn/Pb) (3 percent lead minimum) or T (Sn) for (100 percent tin).

* Power rating. The power rating shall be 1.0 watt at +25°C. The power rating shall be linearly derated to zero at 175°C or 275°C (see Commercial products).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
0.002	0.05	0.210	5.33
0.031	0.79	0.560	14.22
0.032	0.81	1.500	38.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The picturization of the style above is given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope and do not alter the functional aspects of the device, are acceptable.

FIGURE 1. Resistors, fixed, wire wound, or metal element (style VLV3).

Temperature coefficient. The temperature coefficient of resistance shall not exceed ±350 ppm/°C from -55°C to +275°C.

* Marking. Resistors supplied to this CID specification sheet shall be marked with the manufacturers standard commercial PIN. Marking of individual small devices (e.g. chips) is not required but is permitted; however, each unit pack supplied to this CID shall be marked with the commercial item description PIN.

NOTES

* PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See Classification section for PIN format example.

Source of documents.

Commercial Item Description

A-A-55534 - Resistor, Fixed, Power type (Very Low Resistance Values), General Requirements For

* (Copies of commercial item descriptions are available online at http://quicksearch.dla.mil.)

* Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.

MFR's CAGE	MFR's name and address
91637	Vishay Dale Electronics, Inc. 1122 23rd St. PO Box 609 Columbus, NE 68601-0609 PLANT: Vishay Dale Electronics, Inc. Industrial Park PO Box 87 Dimona 86100, Israel Phone: 402-563-6866 Fax: 402-563-6296 Email: business-americas@vishay.com Website: www.vishay.com
15915	TEPRO of Florida, Inc. 2608 Enterprise Rd. Clearwater, FL 34623 Phone: 727-796-1044 Fax: 727-791-7425 Email: tep_sales_service@electrotechnik.com Website: www.tepro-vamistor.com

* Part number (P/N) supersession data. These CID specification sheet PINs supersedes the MFGR's P/Ns as shown. This information is being provided to assist in reducing proliferation in the government inventory system.

CID PIN	MFGR's CAGE	MFGR's P/N 1/	MFGR's SALIENT CHARACTERISTICS
AA55534/03-******	91637	LVR-3	Resistance values 0.005 ohm to 0.2 ohm, resistance tolerances F, H, and J.
AA55534/03-******	15915	TSM2B	Resistance values 0.005 ohm to 0.9 ohm, resistance tolerances F, H, and J.

1/ The manufacturers P/N shall not be used for acquisition to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph of A-A-55534.

* National Stock Number. This section is not applicable to this CID.

* Changes from previous issue. The margins of this CID specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian
Navy - EC
DLA-CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FAS

Preparing Activity:
DLA-CC

Project 5905-2018-024

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.