INCH-POUND
A-A-59440/9C
24 January 2019
SUPERSEDING
A-A-59440/9B
21 May 2012

COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

COCK-VALVE, PLUG, GROUND KEY, THREADED TYPE, BRASS, 125 PSI, STEAM, NPTF-1 THREADS

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring the cock-valve, plug, ground key, threaded type, brass, 125 psi, steam, NPTF-1 threads described herein shall consist of this document and the issue in effect of A-A-59440.

CLASSIFICATION/PART OR IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the PIN as shown in the following example (see NOTES).

AA59440	/09	-	032
CID number	Applicable CID spec sheet (two digits)		Dash number (see figure 1)

SALIENT CHARACTERISTICS.

Interface and physical dimensions. Cock-valves, plug, ground key, threaded type, brass, 125 psi steam, NPTF-1 threads supplied to this CID specification sheet shall be as specified herein (see figure 1).

Size. Nominal sizes of 1/8 inch through 3/8 inch with NPTF-1 threads.

Intended application. This item is for use in steam systems where pressures do not exceed 125 psig (8.62 bar) at 351°F (177°C) and the liquid is compatible with brass.

Permissible variations in dimensions. Figure 1 lists the permissible variations in dimensions for each size. The external dimensions of the cock-valve should not limit procurement unless the end item applications restrict these dimensions.

Optional designs. The illustration is for identification purposes only, it is not intended to restrict designs or shapes not dimensioned.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

Threads. Threads are dryseal NPTF-1 in accordance with A-A-59440.

Materials.

Preferred valve material. Preferred material is brass in accordance with ASTM B61.

Alternate brass. Brass shall be in accordance with the following commercial standards:

ASTM B16/B16M	ASTM B121/B121M	ASTM B369	SAE AMS4845
ASTM B22	ASTM B124/B124M	ASTM B505/B505M	SAE AMS4855
ASTM B30	ASTM B148	ASTM B584	SAE AMS4860
ASTM B36/B36M	ASTM B176	ASTM B763	SAE AMS4862
ASTM B62	ASTM B271/B271M	ASTM B770	SAE AMS4890

Protective coating.


Brass: None.

Caution:
Brass shall not have any lead contents.

Test pressures.

a. Shell: 250 psig (17.2 bar).
b. Seat: 125 psig (8.62 bar).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.



Dash Number	A Pipe thread NPTF-1	B max (mm)	C max (mm)	D across flats ±.020 (0.51 mm)	E diameter min (mm)	F max (mm)	G max (mm)
036	1/8-27	1.75 (44.5)	1.94 (49.3)	.56 or .75 (14.2 or 19.1)	.16 (4.1)	1.38 (35.1)	0.38 (9.7)
037	1/4-18	2.12 (53.8)	2.20 (55.9)	.75 or .88 (19.1 or 22.4)	.16 (.41)	1.38 (35.1)	0.56 (14.2)
038	3/8-18	2.44 (62.0)	2.44 (62.0)	.88 or .94 (22.4 or 23.9)	.18 (4.6)	1.75 (44.5)	0.56 (14.2)

FIGURE 1. Cock-valve, plug, ground, threaded type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.010 inch (0.25 mm).
4. Oval port having same cross sectional area is acceptable.
5. Measurements across flats of hexagonal wrench pad shall be a standard measurement under 1 inch (2.54 mm).

FIGURE 1. Cock-valve, plug, ground, threaded type - Continued.

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source of documents

Commercial Item Description

A-A-59440	-	Cock-Valves and Valves, General Requirements for

(Copies of these documents are available online at https://quicksearch.dla.mil or https://assist.dla.mil).

Other Publications

ASTM INTERNATIONAL

ASTM B16/B16M	-	Free-Cutting Brass Rod, Bar and Shapes for Use in Screw Machines
ASTM B22	-	Bronze Castings for Bridges and Turntables
ASTM B30	-	Copper Alloys in Ingot Form
ASTM B36/B36M	-	Brass Plate, Sheet, Strip, and Rolled Bar
ASTM B61	-	Steam or Valve Bronze Castings
ASTM B62	-	Composition Bronze or Ounce Metal Castings
ASTM B121/B121M	-	Leaded Brass Plate, Sheet, Strip, and Rolled Bar
ASTM B124/B124M	-	Copper and Copper Alloy Forging Rod, Bar, and Shapes
ASTM B148	-	Aluminum-Bronze Sand Castings
ASTM B176	-	Copper-Alloy Die Castings
ASTM B271/B271M	-	Copper-Base Alloy Centrifugal Castings
ASTM B369	-	Copper-Nickel Alloy Castings
ASTM B505/B505M	-	Copper Alloy Continuous Castings
ASTM B584	-	Copper Alloy Sand Castings for General Applications
ASTM B763	-	Copper Alloy Sand Castings for Valve Application
ASTM B770	-	Copper-Beryllium Alloy Sand Castings for General Applications

(Copies of these documents are available online at http://www.astm.org or from the ASTM International, P.O. Box C700, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

SAE INTERNATIONAL

SAE AMS4845	-	Tin Bronze Castings, Sand and Centrifugal 87.5CU - 10SN - 2ZN as Cast
SAE AMS4855	-	Leaded Red Brass, Sand and Centrifugal Castings 85CU - 5.0SN - 5.0PB - 5.0ZN as Cast
SAE AMS4860	-	Manganese Bronze, Sand and Centrifugal Castings 58CU - 39ZN - 1.2FE - 1.0AL - 0.80MN as Cast
SAE AMS4862	-	Manganese Bronze, Sand and Centrifugal Castings 63CU - 24ZN - 6.2AL - 3.8MN - 3.0FE High Strength, as Cast
SAE AMS4890	-	Copper-Beryllium Alloy Castings 97CU - 2.1BE - 0.52CO - 0.28SI Solution Heat Treated (TBOO)

(Copies of these documents are available on line at www.sae.org from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, and Tel: 877-606-7323 [inside USA and Canada] or 724-776-4970 [outside USA], email at CustomerService@sae.org.)

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

MFR's CAGE	MFR's name and address
01276	Eaton Aeroquip Inc. 14615 Lone Oak Rd. Eden Prairie, MN 55344 952-294-2032/888-258-0222 jeffenoe@eaton.com
93061	Parker-Hannifin Corp Brass Products Division 300 Parker Drive Otsego, MI 49708-1472 260-636-2104 dwsanders@Parker.com
20969	Essex Brass Corp 23500 Pinewood Warren, MI 48091-3122 586-757-8200 bpushman@essexbrass.com

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

Military standard (MS) supersession data. This CID replaces the following MS as shown in table I.

TABLE I. MS supersession data.

CID PIN	Superseded MS
AA59440/9-036	MS35931-1
AA59440/9-037	MS35931-2
AA59440/9-038	MS35931-3

Part number P/N supersession data. These CID specification sheet PINs supersede the following MFR's P/N's as shown in table II. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE II. P/N supersession data.

Dash number (see figure 1) AA59440/9	MFR's CAGE	MFR's P/N 1/
036	20969	SC58
037	20969	SC59
038	20969	SC60

1/ The manufacturer's P/N shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see marking paragraph of A-A-59440.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

MILITARY INTERESTS:

Custodians:
Army - AR
Navy - SH
Air Force - 99
DLA - CC

Review activities:
Army - AT, CR4,GL, MI
Navy – AS

CIVIL AGENCY AND COORDINATING ACTIVITIES:

GSA - FSS

Preparing activity:

DLA - CC

(Project 4820-2018-018)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organization and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.