METRIC

A-A-59441/1

16 January 2004

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

VAPOR CORROSION INHIBITORS, TYPE I

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

The complete requirements for procuring Type I vapor corrosion inhibitors (VCIs) described herein shall consist of this document and the latest issue in effect of A-A-59441.

1. SCOPE. This commercial item description covers the requirements for Type I VCIs to provide corrosion protection for metals used in mechanical, electrical and electronic components and equipment that are subjected to corrosive environments inside of enclosures.

2. SALIENT CHARACTERISTICS.

2.1 Physical characteristics. See Table I.

2.2 Performance. VCI emitters shall not interfere with or modify the electrical, optical, or mechanical surface properties of the materials within the enclosure.

TABLE I. Physical characteristics.

VAPOR CORROSION INHIBITORS -- TYPE I							
Item	**Description**	**Protection Volume** m^3 (ft^3)	**Protection Life** (yr)	**Metals Protected**	**Length** cm (in)	**Width or Diameter** cm (in)	**Height** cm (in)
	RANGE of PROTECTED VOLUME 0.35 to .70 ft^3 [0.01-0.02 m^3]						
1	Plastic Strip, thin, rigid, VCI	.01 (0.5)	2	MM	2.5 to 3.3 (1.0 to 1.3)	2.5 to 3.3 (1.0 to 1.3)	.1 to .2 (.04 to .08)
	RANGE of PROTECTED VOLUME 0.7 to 1.5 ft^3 [0.02-0.04 m^3]						
2	Plastic Strip, thin, rigid, VCI	.03 (1)	2	MM	7.0 to 7.8 (2.8 to 3.1)	2.5 to 3.3 (1.0 to 1.3)	.1 to .2 (.04 to .08)
3	VCI Foam, thin	.03 (1)	2	MM	7.0 to 7.8 (2.8 to 3.1)	2.5 to 3.3 (1.0 to 1.3)	.5 to .7 (.20 to .28)
	RANGE of PROTECTED VOLUME 3.5 to 7.0 ft^3 [0.10-0.20 m^3]						
4	VCI Diffuser, short (foam or rigid assembly)	.1 (4)	1	MM	2.5 to 3.3 (1.0 to 1.3)	2.5 to 3.3 (1.0 to 1.3)	1.8 to 1.9 (.70 to .75)
5	VCI Diffuser, short (foam or rigid assembly)	.1 (4)	1	MM	5.1 to 5.8 (2.0 to 2.3)	2.5 to 3.3 (1.0 to 1.3)	1.8 to 1.9 (.70 to .75)
6	VCI Diffuser, short (foam or rigid assembly)	.15 (5)	2	MM	--	5.1 to 5.8 (2.0 to 2.3)	1.8 to 1.9 (.70 to .75)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

TABLE I. Physical characteristics – Continued.

VAPOR CORROSION INHIBITORS -- TYPE I							
Item	**Description**	**Protection Volume** m^3 (ft^3)	**Protection Life** (yr)	**Metals Protected**	**Length** cm (in)	**Width or Diameter** cm (in)	**Height** cm (in)
	RANGE of PROTECTED VOLUME 7 to 14 ft^3 [0.2-0.4 m^3]						
7	VCI Diffuser, round (foam or rigid assembly)	.30 (10)	2	MM	--	6.0 to 6.8 dia (2.4 to 2.6 dia)	4.8 to 5.3 (1.9 to 2.1)
8	VCI Diffuser (foam or rigid assembly)	.31 (11)	2	MM	5.1 to 5.8 (2.0 to 2.3)	2.5 to 3.3 (1.0 to 1.3)	1.2 to 1.4 (.47 to .55)
9	Foam, thick, round	.31 (11)	2	MM	--	5.1 to 5.8 (2.0 to 2.3)	2.5 to 3.3 (1.0 to 1.3)
	RANGE of PROTECTED VOLUME 28 to 57 ft^3 [0.8-1.6 m^3]						
10	VCI Diffuser (foam or rigid assembly)	1.0 (33)	1	MM	5.1 to 5.8 (2.0 to 2.4)	2.5 to 3.3 (1 to 1.3)	2.5 to 3.3 (1.0 to 1.3)
11	VCI Diffuser (foam or rigid assembly)	1.0 (33)	2	MM	7.0 to 8.0 (2.8 to 3.2)	2.5 to 3.3 (1 to 1.3)	2.5 to 3.3 (1.0 to 1.3)
	RANGE of PROTECTED VOLUME 4 to 8 ft^3 per linear foot of tape [0.4 to 0.8 per linear m]						
12	Foam, thin tape	.5 m^3 per m (5 ft^3 per ft)	2	MM	355 to 380 (140 to 150)	1.8 to 2.3 (.7 to .9)	.6 to .8 (.2 to .3)
	RANGE of PROTECTED VOLUME 8 to 16 ft^3 per linear foot of tape [0.8 to 1.6 per linear m]						
13	Foam, thin tape	1.2 m^3 per m (12 ft^3 per ft)	2	MM	600 to 620 (235 to 245)	5.1 to 5.8 (2.0 to 2.4)	.6 to .8 (.2 to .3)
14	Foam, thin tape, VCI	1.0 m^3 per m (10 ft^3 per ft)	2	MM	390 to 410 (150 to 160)	2.5 to 3.3 (1 to 1.3)	.5 to .8 (.2 to .3)

Key: MM = Multi-metal; F = Ferrous; NF = Non-ferrous

3. National stock numbers (NSNs). Table II provides NSNs that correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

TABLE II. National stock numbers.

Item	Standard Package	NSN
1	1000 in resealable bag	TBD
2	100 individually wrapped units per carton	TBD
3	50 individually wrapped units per carton	6850-01-338-1392
4	50 individually wrapped units per carton	6850-01-426-3539
5	50 individually wrapped units per carton	6850-01-338-1393
6	20 individually wrapped units per carton	6850-01-406-2060
7	12 individually wrapped units per carton	6850-01-338-1393
8	25 individually wrapped units per carton	TBD
9	10 individually wrapped units per carton	6850-01-408-9025
10	25 individually wrapped units per carton	6850-01-345-7431

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

TABLE II. National stock numbers – Continued.

Item	Standard Package	NSN
11	10 individually wrapped units per carton	6850-01-133-0373
12	6 rolls in resealable bags per carton	8030-01-208-1769
13	1 roll in resealable bags per carton	8030-00-244-1299
14	6 rolls in resealable bags per carton	TBD

MILITARY INTERESTS

Custodians:
Navy – SH
Air Force – 99

Review Activity:
DLA – CC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

Preparing Activity:
Navy – SH
(Project 2090-0118-001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.