MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, TTL, SCHMITT-TRIGGER NAND GATES, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/151A, dated 30 September 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE II: Delete "Initial electrical parameters (pre burn-in)(method 5004)" and substitute:

"Interim electrical parameters (method 5004)".

TABLE II, Group A test requirements, Class B devices: Add "10, 11".

TABLE II: Delete "Additional electrical subgroups for group C periodic inspections" in its entirety.

PAGE 5

4.2b: Delete "Initial" and "initial" and substitute "Interim" and "interim" respectively.

4.4.3c: Delete in its entirety.

PAGE 11

TABLE III, footnotes 1/ and 2/, delete and substitute the following:

"1/ 2.0 V, then 1.1 V. 0.0 V (verify output = high), 0.2 V, then 1.1 V.

"2/ 0.6 V, then 1.5 V. 5.0 V (verify output = low), 0.6 V, then 1.5 V."

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1090)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-21T13:37Z
Check the source to verify that this is the current version before use.