MIL-C-45491B (AR)
AMENDMENT 1
7 June 1977

MILITARY SPECIFICATION

CARTRIDGE, 90MM, HEAT-T, M431A2
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-45491B (AR), dated 12 May 1975.

PAGE 5

Para. 3.6, delete entire section and substitute: "3.6 Assembly Torque Requirement - Threaded joints shall withstand subsequent reapplication of the minimum assembly torque specified on the applicable drawing, without moving, while thread sealing compounds (if applicable) are wet."

PAGE 12

Para. 4.2.2.8, add the following Critical defects:
"1. Excessive gap at body and chamber joint.....Gage
2. Excessive gap at chamber and boom joint.....Gage"
Change Major 101 to read "Excessive gap at boom and fin joint.... ...Gage"

PAGE 13

Para. 4.2.2.12, change Major defect 102 to read:
"Primer fails to withstand reapplication of min. assembly torque (see 3.6 and 4.3.2....Test"

PAGE 14

Para. 4.2.2.13, Change Major defect 101 to read:
"Loading plug fails to withstand reapplication of min. assembly torque (see 3.6 and 4.3.2).....Test"

PAGE 20

Para. 4.3.2, Line 2; Delete "and in a loosening direction for disassembly torques."

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project No. 1315-A134

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.