MILITARY SPECIFICATION

CANNON, 105MM GUN: M68

CANNON, 105MM GUN: M68A1

This specification is approved for use within the US Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification supports the acquisition of two models of cannon.

1.2 Classification. The two models are:

Type I. Cannon 105MM Gun: M68
Type II. Cannon 105MM Gun: M68A1

1.3 This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements for the purchased cannon have been met.

2. APPLICABLE DOCUMENTS

2.1 Government Documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified in the solicitation, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research and Development Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SAS, Watervliet, N.Y. 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1015

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Military

MIL-C-13931 - Cannon, General Specification for
MIL-P-14232 - Parts, Tools and Equipment for Army Material, Packaging of
MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance, and Disposition of

STANDARDS

Military

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1189 - Standard Department of Defense Bar Code Symbology
MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Government drawings. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified in the solicitation, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. Army Armament, Munitions and Chemical Command

B7309991 - Magnetic Particle Inspection of Breech Rings (Wedge Type)
A7309992 - Magnetic Particle Inspection Criteria for Breechblocks (Wedge Type)
D8773565 - Gage, Tester, Insulation
B8775092 - Gage, Plug, Double End
A8775096 - Gage, Template
F8777451 - Gage, Continuity Tester Special
A8779071 - Instructions
B8769067 - Magnetic Particle Inspection of Cannon and Mount Components
D8765947 - Cannon, 105MM: M68
P8765947 - Special Packaging Instruction, Cannon, 105MM: M68
Master LQAP 8765947 - List of Quality Assurance Provisions for Cannon, 105MM: M68
C11578832 - Inspection Procedures and Criteria, Gun Tube Surface Indications
D11579700 - Cannon, 105MM: M68A1
P11579700 - Special Packaging Instruction, Cannon, 105MM: M68A1
Master LQAP 11579700 - List of Quality Assurance Provisions for Cannon, 105MM: M68A1
QAP-APPENDIX-WVA - General Quality Assurance Provisions

(Copies of specifications, standards, drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified in the solicitation, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified in the solicitation, the issues of the documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM

ASTM D3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. The applicable contract contains an order of precedence clause wherein the specifications are listed last. With respect to this specification, the order of precedence is drawing requirements, followed by the text of this specification, then the other referenced specifications and standards. Nothing in this specification shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. The contractor shall submit a first article unless it is specifically waived in the contract (see 6.2). No first article requirements shall be waived without review and approval by the Procuring Contracting Officer.

3.2 General requirements. Cannon and component parts shall be in accordance with the applicable contract, the applicable general drawing (D8765947 for M68 or D11579700 for M68A1), the requirements of this specification, the provisions of MIL-C-13931, and all referenced documents. Any conflicts are to be resolved by means of the order of precedence (see 2.3).

3.3 Functional characteristics. Each cannon assembly shall perform the firing, pressure sustaining, and projectile launching function of its type gun, 105MM: M68 or M68A1. The breech mechanism, firing mechanism, and other moving parts shall function smoothly without interference, erratic movement or malfunction.

3.3.1 Breech mechanism. Camming of the operating crank during counter-recoil or rearward rotation of the operating lever rotates the breechblock crank rearward to lower the breechblock. When the breechblock nears the opened position, the lips of the extractors rotate sharply rearward to extract the cartridge case. The extractors then lock the breechblock in the opened position until tripped by the insertion of a cartridge. The breech mechanism with the closing spring adjustor set for minimum preload, shall then raise the breechblock to the closed (firing) position. Clockwise rotation of the adjustor shall increase the preload of the closing spring.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

3.3.2 Firing pin retraction. With the initial opening movement of the breechblock, the firing pin retracts and remains behind the front face until the breechblock is returned to the closed position.

3.3.3 Firing pin protrusion. When the breech is closed the protrusion of the firing pin shall be not less than 0.075 inch nor more than 0.115 inch.

3.3.4 Headspace. Headspace, the distance from the front face of the closed and locked breechblock to the breech face of the tube, shall be not less than 0.262 inch nor more than 0.282 inch.

3.3.5 Firing mechanism. The firing mechanism, consisting of the firing plunger, the firing contact, and the firing pin, shall meet the following requirements:

3.3.5.1 Continuity. The firing mechanism shall be capable of passing a current of at least 8 amps, and shall have a resistance of 1 ohm or less when using an applied test voltage of not more than 24 volts.

3.3.5.2 Dielectric strength (leakage). The dielectric strength (leakage) shall be such that no current in excess of 0.5 milliampere shall flow when the firing mechanism is subjected to an electrical potential of not less than 1000 volts, RMS, AC, 50/60 Hz for 30 seconds.

3.3.5.3 Insulation resistance. The firing mechanism shall have a minimum insulation resistance of 1 megohm when a potential of 500 volts DC is applied for 1 minute.

3.4 Performance.

3.4.1 High pressure resistance. The cannon shall be capable of withstanding a chamber pressure of 70,000 + 5700 pounds per square inch when tested as specified in 4.5.6.

3.4.2 Functioning. There shall be no impairment in the functioning of the components during and after the testing specified in 4.5.6.

3.4.3 Bore enlargement. The bore diameters, measured across the rifled lands after firing no more than six rounds, shall not exceed the before firing diameters by more than the amounts shown in TABLE I.

TABLE I. Allowable bore enlargement.

Distance forward of commencement of rifling	0.10 in.	1 in.	1 cal.	2 cals. to muzzle
Amount (in inches)	0.008	0.008	0.006	0.003

NOTE: Interpolate to determine the allowable enlargement between the distances listed.

There shall be no indication of abnormal wear, damage or deformation of the bore surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

3.4.4 Material soundness. The cannon shall meet the requirements specified herein without evidence of cracks or fractures and shall comply with soundness requirements specified on the applicable drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all of the requirements of Sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility for assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. First Article - Initial Production Test, FA-IPT (see 4.4).

c. Quality conformance inspection (see 4.5).

4.3 First article inspection. Unless otherwise specified in the contract, (see 6.2.1), First Article cannon and specified parts thereof shall be inspected by the contractor and submitted to the Government for approval. Inspection shall be in accordance with applicable Quality Assurance Provisions (QAPs) and QAP-APPENDIX-WVA. QAPs are listed in Master LQAP 8765947 or in Master LQAP 11579700, as applicable. First article sample sizes shall be as specified in applicable item QAPs, or the contract, as applicable. First article cannon and parts therof shall be representative of the production processes to be used during quantity production.

4.4 First Article - Initial Production Test (FA-IPT). When specified in the contract, (see 6.2.1), First Article cannon shall be subjected to Initial Production Testing by the Government to assure compliance with the requirements of this specification and any additional requirements listed in the contract. Initial Production Testing procedures and the sample size of First Article cannon shall be as specified in the contract. First Article cannon and parts thereof shall be representative of the production processes to be used during quantity production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection. Quality conformance inspection is listed in Table II.

TABLE II. Quality conformance inspection.

Category/Characteristic	Requirement Paragraph	Inspection Paragraph
Examinations		
Firing pin retraction	3.3.2	4.5.4.1
Firing pin protrusion	3.3.3	4.5.4.1
Headspace	3.3.4	4.5.4.2
Firing mechanism	3.3.5	4.5.4.3
Continuity	3.3.5.1	4.5.4.3.1
Dielectric strength (leakage)	3.3.5.2	4.5.4.3.2
Insulation resistance	3.3.5.3	4.5.4.3.3
Material soundness	3.4.4	4.5.4.4
Packaging	5.	4.5.4.5
Functional inspection	3.3	4.5.5
Breech mechanism	3.3.1	4.5.5.1
Extractors	3.3.1	4.5.5.2
Tests		
Proof acceptance (cannon)	3.4.1 to 3.4.4	4.5.6.1
Proof firing procedures (without sampling)	3.4.1 to 3.4.4	4.5.6.1.1
Proof firing procedures (with sampling)	3.4.1 to 3.4.4	4.5.6.1.2
Proof acceptance (breech mechanism)	3.4.1, 3.4.2, 3.4.4	4.5.6.2
General proof firing procedures	3.4.1 to 3.4.4	4.5.6.3

4.5.1 Inspection provisions. Cannon and parts thereof shall be inspected for conformance to requirements of this specification, MIL-C-13931, QAPs listed in Master LQAP 8765947, Master LQAP 11579700, as applicable, and QAP-APPENDIX-WVA.

4.5.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.5.3 Inspection equipment.

4.5.3.1 Acquisition, maintenance and disposition. Unless otherwise specified (see 6.2.1), responsibility for acquisition, maintenance, and disposition of inspection equipment prescribed in applicable item QAPs, and for all other inspection equipment required to perform inspections prescribed by applicable specifications, shall be in accordance with MIL-I-45607.

4.5.3.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

4.5.4 Examinations.

4.5.4.1 Firing pin protrusion/retraction. Firing pin protrusion shall be inspected on each breech mechanism before assembly to the cannon tube. Inspection shall be performed by means of Gage A8775096 or an approved equivalent to determine compliance with 3.3.3. Firing pin retraction shall be visually observed to determine compliance with 3.3.2. Failure to comply with requirements shall be cause for rejection.

4.5.4.2 Headspace. Headspace shall be inspected on each cannon with Gage B8775092 or an approved equivalent to determine compliance with 3.3.4. Failure to comply with requirements shall be cause for rejection.

4.5.4.3 Firing mechanism. Firing mechanism electrical tests shall be performed on each cannon with the aid of gages F8777451, D8773565, or approved equivalents. For instructions and safety precautions pertaining to the use of these gages, refer to A8779071. Firing mechanism electrical tests shall consist of continuity, dielectric strength (leakage), and insulation resistance tests.

4.5.4.3.1 Continuity. Using gage F8777451 and appropriate test instruments, make connections to the point of the firing pin and to the external end of the firing plunger. An applied test voltage of not more than 24 volts shall be used. The current through the firing mechanism shall be measured and a value of less than 8 amps shall be cause for rejection. The resistance of the firing mechanism shall be calculated (using the actual voltage drop across the firing circuit) or measured (after compensating for lead resistance), and a value of more than 1 ohm shall be cause for rejection.

4.5.4.3.2 Dielectric strength (leakage). After completion of the continuity test, gage D8773565 shall be connected to the external end of the firing plunger and to the breechblock. A 50/60 Hz potential of 1000 volts RMS shall be applied for 30 seconds. Leakage current exceeding 0.5 milliampere shall be cause for rejection.

4.5.4.3.3 Insulation resistance. After completion of the dielectric strength (leakage) test, gage D8773565 shall be connected to the external end of the firing plunger and to the breechblock. A potential of 500 volts DC shall be applied for one minute. Any mechanism having less than 1 megohm insulation resistance shall be cause for rejection.

4.5.4.4 Material soundness. All external and internal surfaces of the tube, breech ring, breechblock, and bore evacuator shall be examined by magnetic particle inspection in accordance with the procedures and acceptance criteria of the applicable General Data Drawings as listed below:

a. C11578832 for tubes.

b. B7309991 for breech rings.

c. A7309992 for breechblocks.

d. B8769067 for bore evacuators (with acceptance criteria of Class IV).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

4.5.4.5 Packaging inspection. Packaging inspection for the level designated in the contract shall be performed in accordance with the applicable packaging data sheets and MIL-P-14232. Packaging failing to comply with the packaging requirements of Section 5 and the contract shall be cause for rejection.

4.5.5 Functional inspection. Functioning tests shall be conducted in accordance with MIL-C-13931 and as specified herein. A minimum of two complete cycles of operation shall be performed on each cannon.

4.5.5.1 Breech mechanism. Each breech mechanism shall be operated manually to determine smoothness of operation in compliance with 3.3.1. Action of the operating lever shall be observed to assure that the lever is locked when in the closed position. Any evidence of interference, erratic movement, or malfunction of any component shall be cause for rejection.

4.5.5.2 Extractors. With the cannon in a horizontal position, extraction and ejection shall be tested with an empty service cartridge case to determine compliance with 3.3.1.

4.5.6 Tests.

4.5.6.1 Proof acceptance of cannon or repair tubes. Each cannon or repair tube shall be proof fired on a non-sampling basis in accordance with 4.5.6.1.1 or on a sampling basis in accordance with 4.5.6.1.2. Proof firing shall be performed under the supervision of the Government at a proofing facility designated by the Government. Inspection before and after proof firing shall be in accordance with this specification and MIL-C-13931.

4.5.6.1.1 Proof firing procedures (without sampling). Unless otherwise specified, proof firing of cannon or repair tubes shall be conducted without sampling and shall consist of the following:

a. The first cannon or repair tube manufactured under a contract shall be subjected to a proof firing sequence consisting of two rounds of ammunition with a specified maximum average pressure of 61,800 psi, followed by four rounds adjusted to produce a chamber pressure of 70,000 + 5,700 psi.

b. Each subsequent cannon or repair tube shall be proof fired with one round adjusted to produce a chamber pressure of 70,000 + 5,700 psi.

c. General proof firing procedures shall be followed in accordance with 4.5.6.3.

4.5.6.1.2 Proof firing procedures (with sampling). When specified (see 6.2.1), proof firing of cannon or repair tubes shall be performed on a sampling basis conducted as follows:

a. Using plan CSP-1 of MIL-STD-1235 and an AQL of 1.0, the Product Assurance Directorate at Watervliet Arsenal will designate the appropriate initial quantity (i) and sampling frequency (f), in the contract (see 6.2.1).

b. The first "i" quantity of cannon or repair tubes produced in a particular buy shall be proof fired. When the "i" quantity has been satisfied,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

sampling shall be put into effect using the "f" sampling frequency.

c. Each cannon or repair tube that is designated to be proof fired, shall be proof fired with one round adjusted to produce a chamber pressure of 70,000 + 5,700 psi. General proof firing procedures shall be followed in accordance with 4.5.6.3.

d. Each cannon not proof fired shall have the breech mechanisms proof tested (see 4.5.6.2) in the Product Assurance weapon test facility at Watervliet Arsenal or in a qualified weapon test facility approved by the Product Assurance Directorate of Watervliet Arsenal.

e. When specified in the contract (see 6.2.1), a weapon simulation test facility shall be qualified as follows: A sample of ten breech mechanisms of cannon to be sent to the proving ground for proof firing shall initially be simulation proof tested at the weapon simulation test facility. Qualification of the weapons test facility shall be determined by the Product Assurance Directorate at Watervliet Arsenal.

f. Proof fired cannon or repair tubes, and proof tested breech mechanisms shall be furnished with applicable data on DA Form 2408-4 (Weapon Record Data), as specified by the Product Assurance Directorate at Watervliet Arsenal.

4.5.6.2 Proof acceptance of breech mechanisms or repair breech mechanisms. The breech mechanism of each cannon not proof fired at a proving ground and each repair breech mechanism shall be proof tested in accordance with the following procedure:

a. Each breech mechanism and repair breech mechanism shall be tested by means of suitable hydrodynamic testing equipment by one application of a pressure within the proof pressure range of 70,000 + 5,700 psi.

b. Cycle time to achieve test pressure and release shall not exceed three minutes. Test pressure shall be immediately released upon its attainment.

(1) When difficulty is encountered in attaining test pressure, the number of attempts in which over 10 percent of the test pressure is attained shall not exceed five.

(2) If the cause of difficulty is not identified and corrected within five pressure cycles, the breech mechanism shall be subjected to proof firing as part of a cannon. A notification of this condition shall be submitted with the breech mechanism to the proving ground.

c. The peak test pressure shall be recorded for each test and attached to inspection records identifiable with the specific breech mechanism undergoing test.

d. After the pressure test, each breech mechanism shall be examined for looseness or interference of fit or other defects of workmanship and function (see 4.5.5).

e. Each breech mechanism shall be disassembled and examined for soundness of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

material. All components shall be visually examined to assure freedom from cracks and fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.5.4.4).

4.5.6.3 General proof firing procedures. Proof firing shall be conducted under Government supervision. The general test procedure shall be as follows:

a. Cannon or repair tubes shall be proof fired in accordance with 4.5.6.1.1 or 4.5.6.1.2 as applicable.

b. A facility mount may be used if necessary.

c. Chamber pressure shall be measured and recorded.

d. After proof firing:

(1) The bore of each tube shall be examined for bore enlargement using an air gage, an electronic gage, or other approved gage. Enlargements exceeding the limits specified in TABLE I shall be cause for rejection (see 3.4.3).

(2) The bore surfaces of each tube shall be examined by means of a borescope (see 4.5.4.4).

(3) Each tube and bore evacuator shall be magnetic particle inspected (see 4.5.4.4).

(4) Each breech mechanism, including the extractors, shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.5.5).

(5) Each firing mechanism group shall be examined for looseness or interference of fit and other defects of workmanship and function (see 4.5.4.3).

(6) Each breech mechanism shall be disassembled and examined for soundness of material. All components shall be visually examined to assure freedom from cracks or fractures. Each breech ring and breechblock shall be magnetic particle inspected (see 4.5.4.4).

(7) Each cannon found to be defective at the proving ground shall be reported to the Product Assurance Directorate, Watervliet Arsenal, Watervliet, NY 12189-4050; and Benet Weapons Lab, Watervliet Arsenal, Watervliet, NY 12189-4050. The test agency shall forward a Test Incident Report (TIR) within 10 working days if incident is classified major, minor, or for information; critical must be reported by telephone within 12 hours.

5. PACKAGING

5.1 Cannon - Levels A, B and C. Cleaning, drying, preserving, unit packaging and packing of the cannon shall be in accordance with Special Packaging Instruction (SPI) P8765947 for Cannon, 105MM Gun M68 and SPI P11579700 for Cannon, 105MM Gun M68A1 for the level of protection specified in the contract (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

5.2 Repair parts.

5.2.1 Levels A, B, and C. Cleaning, drying, preserving, unit packaging, and packing of repair parts shall be in accordance with the applicable repair part SPI and MIL-STD-2073-1 for the level of protection specified in the contract (see 6.2.1).

5.2.2 Level X-commercial packaging. Cleaning, drying, preserving, unit packaging, and packing of repair parts shall be in accordance with ASTM D 3951 when Level X protection is specified in the contract (see 6.2.1).

5.3 Marking.

5.3.1 Levels A, B and C. Marking of unit packages and exterior shipping containers shall be in accordance with MIL-STD-129.

5.3.2 Level X - commercial. Marking shall be in accordance with ASTM D 3951.

5.3.3 Bar code marking. When specified, (see 6.2.1.n) bar code marking shall be in accordance with MIL-STD-129 and MIL-STD-1189.

6. NOTES

6.1 Intended use. The 105MM M68 is intended for use in most M60 series and the M48A5 Tank systems. The 105MM M68A1 is intended for use in most M60 series, M48A5, and M1 Tank systems.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Requirements for and the number of cannon, components thereof, or both to be submitted for first article by the contractor (see 3.1).

c. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

d. All inspection and test data that is required.

e. At whose expense a retest may be performed.

f. Serial numbers for the cannon and repair tube assemblies.

g. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.5.3.1).

h. Availability of inspection equipment from the Government.

i. Extent of supplier's responsibility for Government furnished and for supplier-required final inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

j. Applicable acceptance test procedures.

k. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), and sampling frequency (f) (see 4.5.6.1.2).

l. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

m. The levels of preservation, packaging, and packing required for cannon assemblies (see 5.1) and repair parts (see 5.2).

n. When applicable, bar code marking requirements (see 5.3).

o. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

p. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.410-6 are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements.

Paragraph No.	Data Requirement Title	Applicable DID No.
3.1	First Article Inspection Report	DI-T-4902

(Copies of Data Item Descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the Contracting Officer).

6.5 International interest. Certain provisions of this specification are the subject of international standardization agreements, QSTAG-86. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

6.6 Subject term (key word) listing.

Cannon, 105MM, M68/M68A1

Gun, tank

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

Custodian:

Army-AR

Preparing activity:

Army-AR

Project No. 1015 - A316

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-45504D	CANNON, 105MM GUN: M68 CANNON, 105MM GUN: M68A1

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT , MUNITIONS & CHEMICAL CENTER
ATTN: SMCAR-CCB-SAS
WATERVLIET, NY 12189-4050

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.