INCH-POUND

MIL-D-45495A (AR)
AMENDMENT 2
1 February 1999
SUPERSEDING
AMENDMENT 1
1 February 1983

MILITARY SPECIFICATION

DETONATOR, ELECTRIC, M84
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

MIL-D-45495A WAS INACTIVATED AFTER 18 JULY 1996 FOR NEW DESIGN

This Amendment forms a part of Military Specification MIL D-45495A (AR) dated 5 March 1969, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete the following documents:

"MIL-STD-105
MIL-STD-1235
MIL-STD-109"

and substitute the following:

"MIL-STD-1916 – DOD Preferred Methods for Acceptance of Product"

* 2.2 Non-government publications, add the following:

"ANSI/ISO/ASQC A8402-1994 – Quality Management and Quality Assurance Vocabulary

(Application for copies should be addressed to American Society for Quality Control, 611 East Wisconsin Ave., Milwaukee, WI 53202)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.

PAGE 3

3.4 Delete in its entirety and substitute the following:

"3.4 Porosity. The plug assembly (dwg 9335754) shall show no evidence of porosity as indicated by air bubbles when tested as specified in 4.4.2."

* 4.1 Responsibility for inspection: Delete the sentence referring to MIL-STD-109 in the paragraph, and substitute "Reference shall be made to ASQC A8402 in order to define the terms used herein."

PAGE 6

* 4.3.1 Lot formation, top line of page 6: Delete "as specified in MIL-STD-105." and substitute "as specified in MIL –STD-1916.".

* 4.3.2 Examination, from second sentence to the third line from the bottom:

Delete "Inspection for critical defects (and major…. …)… and documented as part of the contractor's inspection system.", and substitute with the following:

"Unless otherwise specified, sampling inspection for quality conformance characteristics listed in the classification of characteristics paragraphs shall conducted in accordance with MIL-STD-1916 using the attribute sampling plans in MIL-STD-1916 and the verification levels as specified in the classification of characteristics paragraphs. (See MIL-STD-1916 for definitions of critical, major and minor classification of characteristics.) Inspection for critical characteristics (and major characteristics when so specified) shall be 100 percent. Also, continuous sampling plans in accordance with MIL-STD-1916 may be used if approved by the procuring activity."

PAGE 7

* 4.3.2.1, Cup:

Delete "Categories Defects", and substitute with "Classification Characteristics".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.

Delete “AQL 1.00 percent” next to Major, and substitute with “Inspection level III”.

Delete “AQL 1.00 percent” next to minor, and substitute “Inspection Level II”.

* 4.3.2.2, Ferrule:

Delete “Categories Defects”, and substitute with “Classification Characteristics.”

Delete “AQL 0.40 percent” next to Major and delete “AQL 1.50 percent” next to Minor, and substitute with “Inspection level III” and “Inspection level II” respectively.

4.3.2.3 Delete: “Plug (see dwg 8860883 covering a detail of dwg 8838107).” and substitute: “Plug (dwg 9335753 covering a detail of dwg 88388107).”

* 4.3.2.3 Plug:

Delete “Categories Defects”, and substitute with “Classification Characteristics”.

Delete “AQL 0.40 percent” next to major and “AQL 0.65 percent” next to minor, and substitute with “Inspection level III” and “Inspection level II” respectively.

4.3.2.3 Delete: “Plug assembly (see dwg 8860881 … dwg 8838107)”. and substitute: “Plug assembly (dwg 9335754 covering a detail of dwg 8838107)”.

* 4.3.2.4 Plug assembly:

Delete “Categories Defects”, and substitute “Classification Characteristics”.

Delete “AQL 1.00 percent” next to Major, “AQL 1.50 percent” next to minor, and substitute “Inspection level III” and “Inspection level II” respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.

4.2.3.5 Delete in its entirety.

4.2.3.6 Delete in its entirety.

4.2.3.7 Delete: "Bridge and plug assembly (see dwg 8838117 … dwg 8838107)."and substitute: "Bridge and plug assembly (dwg 9335755 covering a detail of dwg 8838107)."

* 4.3.2.7 Bridge and plug assembly:

Delete "Categories Defects", and substitute "Classification Characteristics".

Delete "AQL 0.40 percent" next to major and delete "AQL 0.65 percent" next to Minor, and substitute "Inspection level III" and "Inspection level II" respectively.

* 4.3.2.8 Assembly:

Delete "Categories Defects", and substitute "Classification Characteristics".

Add "100 percent inspection" next to critical.

Delete "AQL 1.00 percent" next to Major, delete "AQL 1.50 percent" next to Minor, and substitute "Inspection level III" and "Inspection level II" respectively.

* 4.3.2.9 Sealed metal container:

Delete "Categories Defects", and substitute "Classification Characteristics".

Delete "AQL 0.40 percent" next to Major and "AQL 1.50 percent" next to Minor, and substitute "Inspection level II" and "Inspection level II" respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.

* 4.3.2.10 Box, Set-up, Packing:

Delete “Categories Defects”, and substitute “Classification Characteristics”.

Delete “AQL 0.40 percent” next to Major and “AQL 1.00 percent” next to Minor, and substitute “Inspection level II” and “Inspection level II” respectively.

* 4.3.2.11 Sealed wood packing box:

Delete “Categories Defects”, and substitute “Classification Characteristics”.

Delete “AQL 0.65 percent” next to Major, and substitute “Inspection level II”.

PAGE 12

* 4.3.3 Testing: Replace “MIL-STD-105” with “MIL-STD-1916” in the sentence. The sentence shall read “Unless otherwise specified herein, the following tests shall be performed using MIL-STD-1916 for sampling plan requirements.

* 4.3.3.2 Porosity: Delete “Major Defect”, “Code Letter H and with an AQL of 0.40 percent”; and substitute with “Major Characteristic”, “Inspection level II” respectively.

PAGE 13

4.3.3.4 Delete in its entirety and substitute the following:

“4.3.3.4 Plug assembly push test (dwg 9335754) – Major defect - Code No. 04010. The sampling plan shall be in accordance with Code Letter L with an AQL of 0.40 percent. The test shall be performed as specified in 4.4.4.

* 4.3.3.4 Plug assembly push test:

Delete “Major defect”, “Code letter L with an AQL of 0.40 percent”; and substitute “Major characteristic” and “Inspection Level III” respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.

4.3.3.5 Delete in its entirety and substitute the following:

"4.3.3.5 Resistance between pin and plug (dwg 9335754 – Major defect – Code No. 04011. The test shall be performed 100 percent in accordance with the procedure specified in 4.4.5. Any assembly that fails to comply with the requirement shall be classed defective and removed from the lot."

* 4.3.3.5 Resistance between pin and plug

Delete "Major defect", and substitute "Major characteristics" .

* 4.3.3.6 Resistance between pin and cup

Delete "Major defect", and substitute "Major characteristic".

4.4.2 Delete "Porosity of plug assembly (see dwg 8860881)" and substitute: "Porosity of plug assembly (see dwg 9335754)."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project:(1330-0411)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:13Z
Check the source to verify that this is the current version before use.