INCH-POUND
MIL-R-45511D(AR)
20 April 1993
SUPERSEDING
MIL-R-45511C(WC)
14 January 1972

MILITARY SPECIFICATION

RIFLE, RECOILLESS, 90MM: M67

This specification is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification supports the acquisition of the Rifle, Recoilless 90MM: M67 consisting of the rifle tube, breech and firing mechanisms. This specification includes the minimum essential Engineering and Packaging Requirements and the necessary Quality Assurance Provisions to determine that these requirements have been met.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-CCB-SC, Watervliet, NY 12189-4050 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1015
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

Military

MIL-C-12166 - Copper Rod for Crusher Cylinders or Pressure Cylinders

MIL-C-13931 - Cannon, General Specification for

MIL-P-14232 - Parts, Equipment and Tools for Army Materiel, Packaging of

MIL-I-45607 - Inspection Equipment Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing and Marking

MIL-STD-2073-1 - DOD Materiel Procedures for Development & Application of Packaging Requirements

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.8)

U.S. Army Armament Research, Development and Engineering Center (ARDEC)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

EPL 8768198 - Engineering Parts List for Rifle, Recoilless, 90MM: M67

PDS P8412892 - Packaging Data Sheet, Rifle, Recoilless, 90MM: M67

QAP-APPENDIX -WVA - General Quality Assurance Provisions

PUBLICATIONS

Master LQAP 8768198 - Master Index of Quality Assurance Provisions for Rifle, Recoilless, 90MM: M67

TM 9-1015-223-12 - Maintenance Manual for Rifle, Recoilless, 90MM: M67

(Copies of drawings, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Procuring Contracting Officer.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)

ASTM D 3951 - Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103-1137.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract, the contractor shall submit a first article/production qualification sample. The definition and inspection of the first article/production qualification sample shall be as specified in 4.4. Unless otherwise specified (see 6.2), the first article sample shall be included in the pilot pack (see 5.1).

3.2 Materials and construction. The recoilless rifle shall conform to this specification, MIL-C-13931 and the drawings listed in EPL 8768198.

3.3 Functioning. All parts shall function without interference, erratic movement, or malfunction.

3.3.1 Breech mechanism. Moving the lock-ring handle clockwise (viewed from the rear), until stopped by the detent, cocks the hammer and unlocks the breech. During this movement, a cam surface on the breech face of the lock-ring forces the hammer actuator inward thereby forcing the hammer rearward to compress the hammer spring. The sear, on the end of the firing-cable assembly, moves rearward under spring pressure, to a position under the hammer actuator and prevents the actuator from moving outward. The lock-ring handle may then be moved counterclockwise to the locked position or it may be swung rearward to open the breech. During the opening of the breech, a tooth on the hinge-block engages a recess in the extractor link and moves the link rearward. The link pulls the extractor rearward to extract the cartridge case, and also rotates the safety (loader's safety) in the hinge-block to the "SAFE" position. As the breech is being closed, the tooth on the hinge-block pushes the extractor link forward, which in turn pushes the extractor forward to allow the cartridge to be seated in the chamber. As the lock-ring handle is moved counter-clockwise to the locked position, the cam surface on the lock ring allows the hammer actuator to move outward until it rests on the sear. The loader's safety must be moved manually to the "FIRE" position.

3.3.2 Firing mechanism. The working length of the firing cable shall be so adjusted, by varying the number of spacers between the cable actuating lever and the cable button, that the rifle may be fired only after depressing the grip safety. This adjustment shall be done in accordance with TM 9-1015-223-12 (see 6.4). With the rifle cocked and the loader's safety in the "FIRE" position, depressing the grip safety unlocks the trigger. Depressing the trigger rotates the cable-actuating lever to pull the firing-cable forward. This forward movement of the cable pulls the sear forward to release the hammer actuator. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

compressed hammer spring then drives the hammer forward to strike the primer in the cartridge.

3.3.3 Bipod legs. The bipod retaining-plate shall be so adjusted that the legs will remain in either the closed or the opened position when the rifle is carried.

3.3.4 Headspace. Headspace, the distance from the cartridge-rim seat to the face of the hammer bushing when the breech is closed, shall be not less than 0.2268 inch nor more than 0.2438 inch.

3.3.5 Firing pin indentation. The indentation of the firing pin shall be not less than 0.011 inch.

3.4 Performance.

3.4.1 High pressure resistance. The rifle shall be capable of withstanding a chamber pressure of 8800 ± 300 pounds per square inch at 70° F when tested as specified in 4.5.6.

3.4.2 Recoil momentum. The average recoil momentum shall be between 0 and 3 pound-seconds rearward when fired with a M371A1 standard pressure HEAT round producing a muzzle velocity of 700 ± 35 fps at a chamber pressure not to exceed 7800 psi.

3.4.3 Material soundness. After proof firing, all parts shall be free of cracks and fractures and shall comply with any soundness requirements specified on the applicable drawings.

3.4.4 Bore enlargement. Enlargement of bore diameters (across lands) after proof firing shall not exceed 0.002 inch.

3.5 Workmanship. Workmanship requirements shall be in accordance with MIL-C-13931.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions shall be as specified in MIL-STD-109.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Production Qualification Test (PQT) (see 4.4).

c. Quality conformance inspection (see 4.5).

4.4 First article.

4.4.1 First article sample. A first article sample shall be submitted by the contractor (in accordance with the contract requirements) for examinations by or for the Government and tests by or for the Government (see 6.2). The sample shall be representative of the production process to be used during quantity production.

4.4.2 First article inspection. The first article sample shall be subjected to a Production Qualification Test (PQT) in accordance with all quality conformance inspections and all examinations and tests described in this specification to assure conformance with the requirements of this specification.

a. Failure of the first article sample to meet the requirements as evidenced by the results of the examinations and tests shall be cause for rejection (see 6.2). The contractor shall determine the cause of failure and shall take corrective action in current and subsequent production. Resubmission and retest shall be at the option of the Government (see 6.2).

b. Disposition of an acceptable first article sample shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

be in accordance with the provisions of the contract (see 6.2).

4.5 Quality conformance inspection.

4.5.1 Inspection provisions. Rifles shall be inspected for conformance to requirements of the provisions of this specification, MIL-C-13931, QAPS listed in Master LQAP 8768198, and QAP-APPENDIX-WVA.

4.5.1.1 Final examination. Final examination of each rifle shall be completed after testing and prior to preservation and packaging to determine compliance with this specification, MIL-C-13931, and as specified in the contract (see 6.2).

4.5.1.2 Inspection approval stamp. The application of the inspection approval stamp shall be as specified in MIL-C-13931.

4.5.2 Inspection equipment. Drawing numbers of Government designed inspection equipment used in the inspection of parts, subassemblies and assemblies are listed in part III of the applicable QAP.

4.5.2.1 Acquisition, maintenance and disposition. Unless otherwise specified (see 6.2), responsibility for acquisition, maintenance and disposition of inspection and test equipment required to perform inspection prescribed by applicable specifications, shall be in accordance with MIL-I-45607.

4.5.2.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it shall be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.5.3 Materials. Materials for use in parts shall be inspected in accordance with MIL-C-13931 and the applicable material specifications referenced on the parts drawings.

4.5.4 Parts. Parts, subassemblies and assembled rifles shall be inspected in accordance with MIL-C-13931 and the applicable Quality Assurance Provisions (QAPs) listed in Master LQAP 8768198.

4.5.5 Examination and tests.

4.5.5.1 Operation. Each assembled rifle shall be manually operated through at least five cycles (close breech, fire, open breech). Evidence of binding, interference, or malfunction at any stage of a cycle shall be cause for rejection. The action of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

the extractor shall be observed for proper functioning. The rifle shall fire only if the safety is in the "FIRE" position and the grip safety is depressed prior to depressing the trigger. Failure to meet the requirements shall be cause for rejection of the rifle.

4.5.5.2 Bipod legs. The legs of each rifle shall be opened and closed at least three times to insure that they will lock securely in either position and that they will rest against the tube when closed.

4.5.5.3 Headspace. Headspace shall be measured using the applicable gage or an approved equivalent gage. Failure to comply with the specified requirements shall be cause for rejection of the rifle.

4.5.5.4 Firing pin indentation. The indentation of the firing pin of each rifle shall be checked by means of a crushed-cylinder conforming to MIL-C-12166. The cylinder shall be 0.2255 + .0010 inch in diameter and 0.400 ± .005 inch in length. The cylinder shall be placed in the fixture shown on the applicable inspection-equipment drawing. Then the fixture shall be placed in the rifle chamber, the breech closed, and the loader's safety set in the "FIRE" position. The rifle shall then be fired by depressing the grip-safety and the trigger. The indentation of the cylinder shall be measured. Rifles showing less than the specified indentation, shall be rejected.

4.5.6 Inspection at the proving ground. Except as specified herein, the rifles shall be inspected in accordance with the applicable requirements of MIL-C-13931.

4.5.6.1 Terms used in the proof firing.

a. A "standard weight projectile" weighs 6.70 pounds plus or minus 0.05 pounds.

b. A "standard pressure round" shall use a "standard weight projectile". The round shall be loaded to produce a muzzle velocity of 700 feet per second, and an average, rearward, recoil momentum for "Standard" rounds (Table I) not to exceed 3.0 pound-second with a chamber pressure less than the weapon upper pressure limit (UPL) at 70° F of 7800 psi.

c. A "specific pressure round" shall use a "standard weight projectile" and the round shall be loaded to develop 8800 ± 300 psi at 70° F.

4.5.6.2 Each rifle shall be proof fired in accordance with Table

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

I, all rounds being fired at zero elevation plus or minus 5° and in the order shown.

Table I

Round number	Number of rounds	Type Round
1	1	Specific (8800 ± 300 psi)
2 to 4	3*	Standard (7800 psi)

* Additional standard rounds may be fired when in the judgment of the test director the result of the preceding round is questionable or inconclusive. Not more than 6 additional rounds shall be fired before bore diameter measurements. Weather conditions, barometric pressure, and relative humidity at the time of proof firing shall be recorded.

4.5.6.3 Velocity. Velocity checks shall be made on 1 in every 24 rifles and when a change occurs in the lot of proof ammunition.

4.5.6.4 Bore diameter. Bore diameters shall be measured with a star gage, an air gage, or other approved gage after proof firing no more than 10 rounds. Enlargement greater than the allowable shall be cause for rejection of the rifle.

4.5.6.5 Mount. The rifles shall be fired on a mount from which recoil momentum may be determined from the following relationship of momentum and deflection.

$$M = \frac{Wd}{12g} \sqrt{\frac{g}{L}} = \frac{Wd}{12g} \times \frac{2}{T}$$

Where: M = recoil momentum of assembly (lb-sec)
W = weight of suspended assembly (lb.)
d = horizontal deflection of suspended assembly (in.)
L = effective length of pendulum suspension (ft.)
g = acceleration of gravity (ft/sec.^{2})
T = period of suspended assembly (sec.)
(time of one complete cycle of oscillation)

4.5.6.6 Inspection after proof firing. In addition to the inspection before and after proof firing specified in MIL-C-13931, the following shall be performed:

a. Determine recoil momentum.

b. Examine the tube and breech assembly using magnetic

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

particle test method to determine compliance with the soundness requirements specified. Suitable liquid penetrant test method may be used in lieu of magnetic particle test.

4.5.6.7 Proof marking. Proof fired rifles shall be marked as proof accepted or positively identified as proof rejected. Proof acceptance marking shall be located near the serial number of the tube.

4.6 Inspection of the preparation for delivery.

4.6.1 Examination. The classifications of defects for preparation for delivery examination shall have a 10% of shipment sample rate and the classifications of defects for preparation for delivery examination are as follows:

Category	Defect
Major	
101	Illegible or incorrect marking
102	Improper level of preservation, packaging or packing
103	Inadequate cleaning and drying
104	Improper preservative application
105	Missing or improper barrier material
106	Improper or inadequate blocking and bracing
107	Improper closure and strapping of containers
Minor	
201	Workmanship of container and packaging

5. PACKAGING

5.1 Pilot pack. On each contract, a pilot pack shall be forwarded in accordance with 3.1. Pilot packs for the rifle shall be packaged to the level of packaging specified in the contract and packed level C in accordance with the requirements of Packaging Data Sheet P8421892.

5.2 Rifle - Levels A, B and C. Cleaning, drying, preservation,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

unit packaging and packing of Rifle shall be in accordance with the requirements of Packaging Data Sheet (PDS) 8412892 and MIL-P-14232 for the level of protection specified in the contract (see 6.2).

5.3 Repair parts - Level A, B and C. Cleaning, drying, preservation, unit packaging and packing of repair parts, shall be in accordance with the applicable repair part PDS and MIL-P-14232 for the level of protection specified in the contract (see 6.2). When Level C requirements are not shown on the PDS, Level C packaging shall be in accordance with MIL-STD-1190.

5.3.1 Level X - Industrial packaging. Cleaning, drying, preservation, unit packaging and packing of repair parts shall be in accordance with ASTM D 3951 when industrial packaging is specified in the contract (see 6.2).

5.3.1.1 Quantity in unit package (QUP). When Level C packaging in accordance with MIL-STD-1190 or industrial packaging of repair parts is specified in the contract, the QUP shall be the same as specified in the contract (see 6.2).

5.4 Marking of packages.

5.4.1 Levels A, B, C and X. Marking (including bar code marking) of the unit package, intermediate packages, and exterior shipping containers shall be in accordance with MIL-STD-129 (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The rifle specified herein is intended for use with the Rifle, 90MM: M67 W/E (WITH EQUIPMENT).

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

c. Requirements for and the number of Rifle, components thereof, or both to be submitted for first article by the contractor (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

d. The examinations and tests to be performed by the contractor and the examinations and tests to be performed by the Government.

e. All inspection and test data that is required.

f. At whose expense a retest may be performed.

g. Any additional or extended examinations and tests beyond the scope of this specification.

h. Serial numbers for the Rifle and repair tube assemblies.

i. Inspection equipment, responsibility for acquisition, maintenance, and disposition thereof, if other than as specified (see 4.5.2).

j. Availability of inspection equipment from the Government.

k. Extent of contractor's responsibility for Government furnished and for contractor-required final inspection equipment.

l. Applicable acceptance test procedures.

m. When a proof firing sampling plan is authorized, the proof firing sampling plan parameters: initial consecutive quantity (i), and sampling frequency (f) (see 4.5.6).

n. Under what conditions simulated firing may be performed, the test equipment available, and the procedures to be followed.

o. The levels of preservation, packaging, and packing required for Rifle assemblies (see 5.2) and repair parts (see 5.3).

p. Marking and bar code marking requirements (see 5.4).

q. When warranted, the application of MIL-Q-9858 or MIL-I-45208, as appropriate.

r. Unless otherwise specified, the application of MIL-I-45607 and MIL-STD-45662.

6.3 Consideration of Data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

(DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title
----------	--------	-------

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DD Form 1423.

6.4 Technical manuals. The requirement for technical manuals should be considered when this specification is applied on a contract. If technical manuals are required, military specifications and standards that have been cleared and listed in DOD 5010.12L, Acquisition Management Systems and Data Requirements Control List (AMSDL) must be listed on a seperate Contract Data Requirements List (DD Form 1423), which is included as an exhibit to the contract. The technical manuals must be acquired under seperate contract line item in the contract.

6.5 First article. When first article inspection is required, the Procuring Contracting Officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first lot of production items, a standard production item from the contractor's current inventory, and the number of items to be tested as specified in 4.4. The Procuring Contracting Officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

6.6 Waivers and deviations. The Procuring Contracting Officer shall coordinate all requests for waiver or deviation to this specification with Benet Laboratories and the Product Assurance Directorate at Watervliet Arsenal.

6.7 Subject term (key word) listing.

Rifle, recoilless 90MM: M67
Rifle, recoilless 90MM: M67 W/E

6.8 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research, Development and Engineering Center" (ARDEC) may also include drawings prepared by, and identified as Watervliet Arsenal, Ordnance Corps, Weapons Command, or U.S. Army Armament Research and Development Command, U.S. Army Armament, Munitions and Chemical Command, etc. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army-AR

Preparing activity:

Army-AR

(Project 1015-A334)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:17Z
Check the source to verify that this is the current version before use.