MIL-B-3865C
20 August 1980
SUPERSEDING
MIL-B-3865B
10 March 1971

MILITARY SPECIFICATION

BLOCKS, ROPE, TACKLE: PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for materials and procedures for the preservation, packing, and marking of tackle blocks for wire rope and nonmetallic rope (manila, sisal, nylon, hemp, fiber, and synthetic rope). It does not cover the requirements for hook blocks for cranes and crane-shovels (see 6.3).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification the extent specified herein:

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| QQ-S-781 | - Strapping, Steel, and Seals. |
| PPP-B-601 | - Boxes, Wood, Cleated-Plywood. |
| PPP-B-621 | - Boxes, Wood, Nailed and Lock-Corner. |
| PPP-B-636 | - Boxes, Shipping, Fiberboard. |
| PPP-B-640 | - Boxes, Fiberboard, Corrugated, Triple-Wall. |

FSC PACK

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

MILITARY

| | |
|---|---|
| MIL-P-116 | - Preservation - Packaging, Methods of. |

STANDARDS

FEDERAL

| | |
|---|---|
| FED-STD-101 | - Preservation, Packaging, and Packing Materials: Test Procedures. |

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - Marking for Shipment and Storage. |
| MIL-STD-147 | - Palletized Unit Loads. |
| MIL-STD-1186 | - Cushioning, Anchoring Bracing, Blocking, and Waterproofing; with Appropriate Test Methods. |
| MIL-STD-1188 | - Commercial Packaging of Supplies and Equipment. |

(Copies of specification and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 6.5).

3.2 Preproduction pack. The contractor shall furnish a preproduction pack for examination and test within the time frame specified (see 6.2) to prove, prior to starting production packaging that the applied preservation, packing and marking comply with requirements of this specification. Examination and test shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The Preproduction pack may be accomplished utilizing either the preproduction model or a production model. If the preproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and the production model.

3.3 Preservation. Preservation shall be level A or commercial as specified (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

3.3.1 Level A.

3.3.1.1 Disassembly. Disassembly shall be confined to the removal of parts and components that would otherwise increase cubage, such as hooks, shackles, swivels that can be removed and reinstalled without the use of special tools.

3.3.1.2 Preservative. Exposed unprotected metal surfaces of the blocks requiring the application of a contact preservative in accordance with MIL-P-116 shall be cleaned, dried, and coated with type P-1 or P-19 preservative conforming to the applicable specification listed in and applied in accordance with MIL-P-116.

3.3.1.3 Application of lubricant. Bearings shall be lubricated with the lubricant required for service as recommended by the contractor. Exterior surfaces of the bearings shall be coated with the same lubricant.

3.3.1.4 Wood blocks and metal blocks not exceeding 40 pounds. Each wood block, and each metal block not exceeding 40 pounds, (except awning pulley blocks and other small blocks used in quantities of more than one), shall be placed in a close fitting box conforming to PPP-B-636, W5c or W6c, as applicable to the weight of the block. Awning pulley blocks, and small blocks used in multiples, shall be placed in the quantity required, in boxes specified herein. Blocking, bracing or cushioning as applicable to prevent movement or damage to the contents shall be provided within the boxes. Box closure and sealing shall be in accordance with method V, of the appendix to the box specification.

3.3.1.5 Metal blocks and wood blocks exceeding 40 pounds. Blocks exceeding 40 pounds shall not require additional protection.

3.3.2 Commercial. Blocks shall be preserved in accordance with MIL-STD-1188.

3.4 Packing. Packing shall be level A, level B, or commercial as specified (see 6.2).

3.4.1 Level A. Tackle blocks of like description, preserved as specified in 3.3 shall be packed together in close fitting boxes conforming PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional, in quantities not to exceed the weight limitation of the container. The contents shall be blocked, braced or anchored, as applicable, in accordance with MIL-STD-1186, to prevent movement or damage. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

3.4.2 Level B. Tackle blocks of like description, preserved as specified in 3.3, shall be packed as specified in 3.4.1 except boxes shall be domestic type or class as applicable. As an alternate, boxes conforming to PPP-B-640, class 2, style optional or PPP-B-636, V3c, V11c, V13c, or V15c, style optional may be used when the quantity to be packed does not exceed the gross weight or size limitation of the box specification. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

3.4.3 Commercial. Blocks shall be packed in accordance with MIL-STD-1188.

3.5 Palletization. When a multiple quantity of blocks are being shipped to the same destination; packed blocks for level A., level B or commercial shall be palletized. Blocks packed for level A or level B shall be palletized in accordance with MIL-STD-147, load type as applicable. Blocks packed for commercial may utilize a commercial type pallet suitable for the weight involved.

3.6 Marking.

3.6.1 Military. Marking for level A or level B shall be in accordance with MIL-STD-129.

3.6.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the tackle blocks by application of the requirements specified herein, to prevent corrosion, deterioration and physical damage during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction pack of boxed blocks, prior to palletization, for level A or level B shall be tested in accordance with 4.3.2.1 or 4.3.2.2 as applicable to the gross weight of the box. Failure of the applicable test shall be cause for rejection.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

4.3.2.1 Packs not exceeding 200 pounds gross weight. The pack shall be subjected to the free-fall drop test in accordance with FED-STD-101 test method 5007, Procedure E.

4.3.2.2 Packs exceeding 200 pounds gross weight. The pack shall be subjected to the pendulum-impact test in accordance with FED-STD-101, test method 5012, except the vertical height of drop shall be 18 inches.

4.3.3 Basis for rejection. Any shifting of contents, loosening or breaking of holddowns, ties, stays, blocking or bracing or any visual damage to the contents shall constitute failure of the preproduction pack test and shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in two stages as follows:

(a) The first stage shall include inspection of materials, containers, and marking within the shipping container.

(b) The second stage shall include inspection of packing materials, the closed shipping container, strapping, and shipment marking.

4.4.2 Unit of product. For the purpose of inspection, a unit of product for the first stage of inspection shall be a completed pack with the shipping container top not in place or not closed. For the second stage of inspection, a unit of product shall be a completed pack prepared for shipment, prior to palletizing.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level of packaging in table I. Acceptable quality level (AQL) shall be 2.5 percent defective.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects.

| Defects | Level | | |
|---|---|---|---|
| | A | B | Commercial |
| 101. Materials and containers not as specified Each incorrect material or container shall constitute one defect (3.1, 3.3, 3.4). | X | X | X |
| 102. Disassembly not as specified (3.3.1.1). | X | - | - |
| 103. Preservative and application not as specified | X | - | - |
| 104. Application of lubricant not as specified (3.3.1.3). | X | - | - |
| 105. Box closure and sealing not as specified (3.3.1.4). | X | - | - |
| 106. Preservation and packing not in accordance with the referenced document (3.3.2, 3.4.3). | - | - | X |
| 107. Blocking, bracing, and anchoring not in accordance with the referenced document (3.4.1, 3.4.2). | X | X | - |
| 108. Strapping not as specified (3.4.1, 3.4.2). | X | X | - |
| 109. Gross weight or size exceeds the box limitations (3.4.1, 3.4.2). | - | X | - |
| 110. Palletization when required not in accordance with the specified requirements (3.5). | X | X | X |
| 111. Marking missing, illegible, incorrect or incomplete (3.6). | X | X | X |

5. PACKAGING

(This section is not applicable to this specification)

6. NOTES

6.1 Intended use. This specification is intended to be used for reference in Section 5 of commodity specifications for tackle blocks, (except hook blocks for cranes and crane shovels (see 6.3) or for direct reference in contracts or orders, and as an aid in preparation of packaging data sheets.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction pack (see 3.2).
(c) Degree of preservation and degree of packing required (see 3.3 and 3.4).
(d) When other than finish B strapping is required (see 3.4.1).

6.3 Preservation, packing, and marking. Preservation, packing, and marking of hook blocks for cranes and crane shovels will be in accordance with MIL-C-3580 - Cranes and Crane Shovels, Truck, Crawler, and Wheel Mounted, Full-Revolving, and their Attachments, Packaging of.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

6.4 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack shall be subject to the approval of the contracting officer. Approval of this preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the tackle blocks in accordance with this specification.

6.5 Recycled materials. It is encouraged that recycled materials be used, when practical, as long as it meets the requirements of this specification (see 3.1).

Custodian:
Army - ME
Navy - YD
Air Force - 99

Review activity:
Army - SM

User activities:
Navy - MC, SH, OS

Preparing activity:
Army - ME

Project PACK-0614



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-B-3865C Blocks, Rope, Tackle: Packaging of

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

| SUBMITTED BY *(Printed or typed name and address — Optional)* | TELEPHONE NO. |
|---|---|
| | DATE |

**DD FORM 1426** 1 OCT 76 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID




OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DE/DS
Fort Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.