INCH-POUND

MIL-B-3865D
30 November 1990
SUPERSEDING
MIL-B-3865C
20 August 1980

MILITARY SPECIFICATION

BLOCKS, ROPE, TACKLE: PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for materials and procedures for the preservation, packing, and marking of tackle blocks for wire rope and nonmetallic rope (manila, sisal, nylon, hemp, fiber, and synthetic rope). It does not cover the requirements for hook blocks for cranes and crane-shovels (see 6.3).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A AREA PACK

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-P-116	-	Preservation, Methods of.

STANDARDS

FEDERAL

FED-STD-101	-	Preservation, Packaging, and Packing Materials: Test Procedures.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized Unit Loads.
MIL-STD-1186	-	Cushioning, Anchoring Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953	-	Strapping, Flat Steel and Seals.
D 4675	-	Selection and use of Flat Strapping Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.1.1 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the blocks may be newly fabricated from recovered materials to the maximum extent practicable, provided the blocks produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the blocks.

3.2 First article pack. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.4) in accordance with 4.3.

3.3 Preservation. Preservation shall be level A or C as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Disassembly. Disassembly shall be confined to the removal of parts and components that would otherwise increase cubage, such as hooks, shackles, swivels that can be removed and reinstalled without the use of special tools.

3.3.1.2 Preservative. Exposed unprotected metal surfaces of the blocks requiring the application of a contact preservative in accordance with MIL-P-116 shall be cleaned, dried, and coated with type P-1 or P-19 preservative conforming to the applicable specification listed in and applied in accordance with MIL-P-116.

3.3.1.3 Application of lubricant. Bearings shall be lubricated with the lubricant required for service as recommended by the contractor. Exterior surfaces of the bearings shall be coated with the same lubricant. Note: Lubricants containing graphite or graphite based lubricants are not allowed.

3.3.1.4 Wood blocks and metal blocks not exceeding 40 pounds. Each wood block, and each metal block not exceeding 40 pounds, (except awning pulley blocks

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

and other small blocks used in quantities of more than one), shall be placed in a close fitting box conforming to PPP-B-636, W5c or W6c, as applicable to the weight of the block. Awning pulley blocks, and small blocks used in multiples, shall be placed in the quantity required, in boxes specified herein. Blocking, bracing or cushioning as applicable to prevent movement or damage to the contents shall be provided within the boxes. Box closure and sealing shall be in accordance with method V, of the appendix to the box specification.

3.3.1.5 Metal blocks and wood blocks exceeding 40 pounds. Blocks exceeding 40 pounds shall not require additional protection.

3.3.2 Level C. Blocks shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage during shipment from the contractor to the initial destination.

3.4 Packing. Packing shall be level A, level B, or C as specified (see 6.2).

3.4.1 Level A. Tackle blocks of like description, preserved as specified in 3.3 shall be packed together in close fitting boxes conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional, in quantities not to exceed the weight limitation of the container. The contents shall be blocked, braced or anchored, as applicable, in accordance with MIL-STD-1186, to prevent movement or damage. Strapping shall conform to ASTM D 3953, type 1 or 2, zinc coated, size as applicable and ASTM D 4675.

3.4.2 Level B. Tackle blocks of like description, preserved as specified in 3.3, shall be packed as specified in 3.4.1 except boxes shall be domestic type or class as applicable. As an alternate, boxes conforming to PPP-B-640, class 2, style optional or PPP-B-636, V3c, V11c, V13c, or V15c, style optional may be used when the quantity to be packed does not exceed the gross weight or size limitation of the box specification. Box closure shall be in accordance with the appendix to the applicable box specification. Strapping shall be as specified for level A.

3.4.3 Level C. Blocks shall be prepared for shipment in a manner which will ensure arrival at destination in a satisfactory condition. Preparation for delivery shall comply with the applicable carrier rules and regulations.

3.5 Palletization. When a multiple quantity of blocks are being shipped to the same destination; packed blocks for level A, level B, or C shall be palletized. Blocks packed for level A or B or C shall be palletized in accordance with MIL-STD-147, load type as applicable.

3.6 Marking. In addition to any special marking specified in the contract or purchase order see (6.2), marking shall be in accordance with MIL-STD-129.

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the tackle blocks by application of the requirements specified herein, to prevent corrosion, deterioration and physical damage during handling, shipment, and storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article pack inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article pack inspection.

4.3.1 Examination. The first article pack shall be examined for the defects specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article pack of boxed blocks, prior to palletization, for level A or level B shall be tested in accordance with 4.3.2.1 or 4.3.2.2 as applicable to the gross weight of the box. Failure of the applicable test shall because for rejection.

4.3.2.1 Packs not exceeding 200 pounds gross weight. The pack shall be subjected to the free-fall drop test in accordance with FED-STD-101 test method 5007, procedure E.

4.3.2.2 Packs exceeding 200 pounds gross weight. The pack shall be subjected to the pendulum-impact test in accordance with FED-STD-101, test method 5012, except the vertical height of drop shall be 18 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

4.3.3 Basis for rejection. Any shifting of contents, loosening or breaking of holddowns, ties, stays, blocking or bracing or any visual damage to the contents shall constitute failure of the first article pack test and shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in two stages as follows:

a. The first stage shall include inspection of materials, containers, and marking within the shipping container.
b. The second stage shall include inspection of packing materials, the closed shipping container, strapping, and shipment marking.

4.4.2 Unit of product. For the purpose of inspection, a unit of product for the first stage of inspection shall be a complete pack with the shipping container top not in place or not closed. For the second stage of inspection, a unit of product shall be a completed pack prepared for shipment, prior to palletizing.

4.4.3 Sampling. Sampling for examination shall be in accordance with table I, and table IIa of MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level of packaging table I. One or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects.

Defects	Level A	Level B	Level C
101. Materials and containers not as specified. Each incorrect material or container shall constitute one defect (3.1, 3.3, 3.4).	X	X	-
102. Disassembly not as specified (3.3.1.1).	X	-	-
103. Preservative and application not as specified (3.3.1.2).	X	-	-
104. Application of lubricant not as specified (3.3.1.3).	X	-	-
105. Box closure and sealing not as specified (3.3.1.4).	X	-	-
106. Blocking, bracing, and anchoring not in accordance with the referenced document (3.4.1, 3.4.2).	X	X	-
107. Strapping not as specified (3.4.1, 3.4.2).	X	X	-
108. Gross weight or size exceeds the box limitations (3.4.1, 3.4.2).	-	X	-
109. Palletization when required not in accordance with the specified requirements (3.5).	X	X	X
110. Marking missing, illegible, incorrect or incomplete (3.6).	X	X	X
111. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the blocks (3.1.1).	X	X	X
112. Workmanship not as specified (3.7).	X	X	X

5. PACKAGING

(This section is not applicable to this specification)

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This specification is intended to be used for reference in section 5 of commodity specifications for tackle blocks, (except hook blocks for cranes and crane shovels (see 6.3) or for direct reference in contracts or orders, and as an aid in preparation of packaging data sheets.

6.2 Acquisition requirements. Acquisition documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2..1.1).
c. Time frame required for submission of first article pack (see 3.2).

d. Level of preservation and packing required (see 3.3 and 3.4).
e. Any special marking (see 3.6).

6.3 Hook blocks for cranes and crane shovels. Hook blocks for cranes and crane shovels shall be preserved, packed, and marked in accordance with MIL-C-3580 - Cranes and Crane Shovels, Truck, Crawler, and Wheel Mounted, Full-Revolving, and their attachments, Packaging of.

6.4 First article. When a first article inspection is required, the item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.6 Subject term (key word) listing.

Marking and packing
Packing
Preservation

Custodian:
Army - ME
Navy - YD
Air Force - 99

Preparing activity:
Army - ME

Project 3940-0187

Review activity:
Army - SM, AT
DLA - GS

User activities:
Navy - MC, SH, OS

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-3865D	901130

3. DOCUMENT TITLE

Blocks, Rope, Tackle: Packaging of

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER	
a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	e. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY	
a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial: (703) 664-5717 (2) AUTOVON: 354-5717
c. ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Ft Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T21:51:27Z
Check the source to verify that this is the current version before use.