MIL-C-3880D
2 December 1982
SUPERSEDING
MIL-C-3880C
17 September 1970

MILITARY SPECIFICATION

CLUB, POLICEMAN'S

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers a policeman's wood club with leather thong.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

KK-L-201	-	Leather, Cattlehide, Lace, and Cut Laces
TT-F-336	-	Filler, Wood, Paste
TT-L-58	-	Lacquer; Spraying, Clear and Pigmented Cellulose Nitrate, (General Interior Use)
TT-S-190	-	Sealers, Sanding, Lacquer-Type (For Wood Furniture)
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment
MIL-STD-1363 - Measurement of Wood Moisture Content

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

1-8-38 - Club, Policeman's, M-1944

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.2, 6.2 and 6.3).

3.2 Materials and components. Materials and components shall be as specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all provisions of this document (see 6.4).

3.2.1 Wood. Wood shall be any of the following species:

Ash (white)
Beech
Birch (sweet or yellow)
Elm (rock)
Pecan
Hickory
Locust
Maple (sugar)
Oak (red or white)

* 3.2.2 Leather. Leather shall conform to type I, type II or type III, class 2, treatment B, color natural of KK-L-201 except that the dimensions shall be as specified on Drawing 1-8-38.

3.2.3 Lacquer. Lacquer shall conform to type II, class 1 of TT-L-58. The color shall be black.

3.2.4 Sealer. The sealer shall conform to TT-S-190.

3.2.5 Wood filler. Filler when used shall conform to TT-F-336.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

3.3 Design and construction. The design and construction of the club shall be as specified herein and as shown on the drawing referenced in 2.1.

3.3.1 Club. The club shall be turned from wood specified in 3.2.1. The moisture content of the wood blanks, at time of turning, shall be not less than 8 nor more than 12 percent when tested as specified in 4.4.1.1. The turned club shall be free from knots, shake, splits, checks, wane, decay, larvae channels and holes except a hole not larger than 3/32 inch diameter by 1/2 inch deep located not less than 1/2 inch from edge at unstamped end of club will be permitted for holding club during lacquer operations. The slope of grain shall not exceed 1 inch in 15 inches, measured parallel to the axis of the club blank when tested as specified in 4.4.1.1. All surfaces of the turned club shall be sanded smooth and shall be free of machine marks, chipped or torn grain, and spur.

3.3.2 Thong. Each club shall be furnished with a thong made from leather specified in 3.2.2. The finished thong shall not be pieced or spliced and shall be free of cut, hole, tear, or crack; boney, stiff, loose or pipey areas; soft spots; and discoloration or mildew. The thong shall be centered and tied around the finished club in the thong groove provided. The ends of the thong shall not be tied or knotted together. In lieu of the plus tolerance shown on Drawing 1-8-38, thong may be supplied up to 32 inches in length.

3.4 Finish. All wood surfaces shall be sanded smooth and free from dust. One coat of sealer specified in 3.2.4, and a minimum of two coats of lacquer specified in 3.2.3 shall be applied to the entire surface of the club. The finish coat shall level out to produce a smooth and uniform appearance on the finished club without brush marks, orange peel, runs, wrinkles, drops, streaks, blushing, area of thin or no film, or wet or tacky finish. There shall be no trace of grit or coarse particles. Wood filler as specified in 3.2.5 may be used and slight irregularity of surface of film over open grain wood will be acceptable. However, finish shall be free of non-uniformity of gloss due to variance in absorption quality of the wood.

3.5 Marking for identification. The letters US shall be legibly indented on the club as shown on Drawing 1-8-38.

3.6 Workmanship. All surfaces shall be smooth and clean, and shall be free of machine gouges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Material testing. In addition to the quality assurance provisions of the subsidiary specifications and drawings, testing shall be performed on materials listed in table I for the test characteristics shown. The inspection level shall be S-1. The acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

TABLE I. Material tests

Material and lot expressed in terms of	Characteristic	Requirement paragraph	Test method	Number determinations per sample unit	Results reported as	Sample unit
Wood (100 blanks)	Moisture content	3.3.1	MIL-STD-1363	3	Average of 3 determinations to nearest 0.5 percent	1 piece prior to turning
	Slope of grain	3.3.1	4.5.1	1	Pass or fail	1 piece prior to turning

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection.

4.4.2.1 Visual examination of clubs prior to finishing. Prior to application of lacquer (or filler, when used) the turned club shall be examined for defects in table II. The lot size shall be expressesd in units of one turned club. The inspection level shall be I. The AQL, expressed in terms of defects per hundred units, shall be 6.5.

TABLE II. Unfinished club defects

Examine	Defect	Classification Major	Classification Minor
Club	Knot, wane or hole	X	
	NOTE: A hole not larger than 3/32 inch diameter by 1/2 inch deep located not less than 1/2 inch from edge at unstamped end of club is allowed.		
	Decay or larvae channel	X	
	Shake, split, surface check, or machine marks	X	
	Spur		X
	Chipped or torn grain	X	

4.4.2.2 Finish in-process examination. Examination shall be made to determine compliance with finish requirements in 3.4. Whenever nonconformance is noted, correction shall be made to affected items and lot in process.

4.4.3 End item visual examination. The end item shall be examined for defects listed in table III. The lot size shall be expressed in units of one club. The sample unit shall be one club. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0 for major defects and 10.0 for total (major and minor combined) defects.

TABLE III. End item defects

Examine	Defect	Classification Major	Classification Minor
Club	Groove missing, misplaced, or not continuous		X
	Not finished or finish is not black	X	
	Discoloration such as streak or blushing		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

TABLE III. End item defects (cont'd)

Examine	Defect	Classification Major	Minor
Club (cont'd)	Area of no film:		
	Bare wood showing in area of 1 square inch or more	X	
	Bare wood showing in area of less than 1 square inch		X
	Area of thin film, i.e., appears starved as if one coat was used in lieu of two coats		X
	Wet or tacky finish		X
	Irregularity of gloss due to absorption of wood or area of rough wood		X
	Coating not smooth and uniform, e.g. brush marks, run, wrinkle, or drop		X
	Grit or coarse particles		X
	Orange peel		X
	Evidence of spur, wane, chipped or split wood		X
Leather thong	Missing	X	
	Cut, hole, tear, crack, boney, stiff, loose, pipey, soft spot, discoloration or mildew		X
	Pieced or spliced	X	
	Not attached as specified		X
Marking	Missing, incomplete, incorrect, illegible, misplaced, not specified size, or not affixed in specified manner		X

4.4.4 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified. Any dimension deviating from the specified requirements or any taper that is not constant, e.g. contains high or low spots, shall be classified as a defect. The lot size shall be expressed in units of one club. The sample unit shall be one club. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with section 5. Defects shall be scored in accordance with table IV. The sample unit shall be one shipping container fully packaged. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE IV. Packaging defects

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as the thong not neatly coiled as required.
Contents	Number per container is more or less than required.

4.5 Methods of inspection.

4.5.1 Slope of wood grain. The slope of wood grain may be determined by combining the grain direction of two adjacent faces of a square or rectangular piece. When one of these faces is straight grained, the true slope of grain is shown on the other face. When there is a slope on both faces, the true or combined slope is greater than the slope on either face. Slope of grain is shown on edge grained faces by the summerwood bands, and on flat grained faces by the direction in which a free flowing ink or dye spreads or by the course taken by a narrow strip lifted by a knife point and torn out. Direction of fiber may also be measured by a slope of grain detector.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. The thong shall be neatly coiled around the tapered portion below the handle, and the ends passed under the last coil and drawn tight.

5.1.2 Commercial. Clubs shall be preserved in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Fifty clubs preserved as specified in 5.1, shall be packed 10 in length, 5 in width, and one in depth in a snug-fitting fiberboard shipping container conforming to style OSC (end opening), grade V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B packing. Fifty clubs preserved as specified in 5.1, shall be packed 10 in length, 5 in width, and one in depth in a snug-fitting fiberboard shipping container conforming to style OSC (end opening), type CF, class domestic, variety optional, grade 275 of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V2s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial packing. Clubs, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The club is intended for use by personnel involved in police activities.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this document.
(b) When a first article is required (see 3.1, 4.2 and 6.3).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of one club. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with repsect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Navy - NU
Air Force - 82

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 8465-0850

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-3880D Club, Policeman's

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:53Z
Check the source to verify that this is the current version before use.