MILITARY SPECIFICATION

HOSE ASSEMBLIES, NON-METALLIC: GREASE GUN HIGH AND LOW PRESSURE

This interim amendment is approved for use within the US Army Belvoir Research, Development, and Engineering Center, Department of the Army, with MIL-H-3868F, dated 9 December 1985.

PAGE 1

1.3, delete in its entirety and substitute the following:

"1.3 Specification part number. The military specification part numbers for the hose assemblies shall be as follows:

M3868 - XX X X XX X XXXX

- XXXX — Length (inches)
- X — Hose inside diameter code (see table Ia)
- XX — Fitting type (see table Ib)
- X — Grade (see 1.2)
- X — Style (see 1.2)
- XX — Type (see 1.2, 3.4.1, 6.1.1, 6.1.2)

Example: M3868I2A11D500

A high pressure hose assembly with female fitting on each end for use at temperatures down to -50 °F, with reuseable swivel type fittings, a 0.500 inch inside diameter (I.D.), and a length of 500 inches."

AMSC N/A FSC 4720
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.

"TABLE Ia. Hose inside diameter code.

SYMBOL	NOM. I.D. (inches)
A	0.1875
B	0.250
C	0.375
D	0.500
E	0.750

TABLE Ib. Fitting type.

CODE	CHARACTERISTIC
11	Reuseable, swivel type
12	Reuseable, rigid type
21	Permanent, swivel type
22	Permanent, rigid type

"

PAGE 2

2.1.1, under STANDARDS, FEDERAL, add:

"FED-STD-595 - Colors."

Under STANDARDS, MILITARY, delete "MIL-STD-130" in its entirety.

PAGE 5

3.4.1.3, line 4, add the following new sentence: "The color shall be sand matte in accordance with FED-STD-595, color chip 30277."

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:51Z
Check the source to verify that this is the current version before use.

3.4.2, delete the last sentence in its entirety and add the following new sentence: "The end fitting shall be the nominal hose inside diameter with tolerances as shown in table II."

PAGE 7

3.8, line 3, delete "in accordance with MIL-STD-130." Add the following new sentences: "The label shall be in contrast to the hose background color. The letters shall be not less than 0.18-inch high. The hose shall be marked with a longitudinal black stripe not less than 0.125-inch wide extending the full length of the hose. The label may be within the longitudinal stripe, provided the width of the stripe is not less than 0.20-inch greater than the height of the letters and the letters are in contrast to the stripe color. The label may substitute for the stripe provided it is continuous for the full length of the hose and is black in color. The label and stripe shall remain clear, distinct and legible for the life of the hose and shall not be adversely affected by handling, bending, water, oil or environmental effects."

PAGE 12

6.2, delete "f" in its entirety.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Preparing activity:
Army - ME

Project 4720-A021

Review activities:
Air Force - 82
DLA - GS

User activities:
Army - AT
Navy - AS, CG, MC, SH

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:51Z
Check the source to verify that this is the current version before use.