MIL-P-3819C(ME)
24 April 1973
SUPERSEDING
MIL-P-3819B(ME)
28 February 1967

MILITARY SPECIFICATION

PNEUMATIC TOOL OUTFIT: 600 CFM, COMPRESSED AIR, PACKAGING OF

1. SCOPE

1.1 This specification covers the requirements for preservation, packaging, packing and marking of the 600 CFM compressed air pneumatic tool outfit, (SC 3820-97-CL-E11).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

Military

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.

FSC 3820

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

MIL-H-775	- Hose, Rubber or Fabric (Including Tubing); and Fittings, Nozzles and Strainers, Packaging of.
MIL-C-3600	- Compressors, Rotary, Power-Driven; and Compressor, Reciprocating, Power-Driven: Air and Gas (Except Oxygen and Refrigerant), Packaging of.
MIL-C-3774	- Crates, Wood; Open, 12,000 and 16,000 Pound Capacity.
MIL-L-21260	- Lubricating Oil, Internal Combustion Engine, Preservative and Break-In.
MIL-C-52078	- Cap-Plug, Cap, and Plug, Protective, Plastic, Dust and Moisture Seal.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC, AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036).

3. REQUIREMENTS

3.1 Preproduction pack. The supplier shall furnish a preproduction pack for examination and test within the time frame specified (see 6.2), to prove prior to starting production packaging and packing that the applied preservation, packaging, packing and marking comply with the requirements of this specification. Examination and test shall be specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.2 Materials. Materials shall be as specified herein and in the applicable specifications and standards. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.3 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

3.3.1 Level A .

3.3.1.1 Cleaning and drying. Prior to the preservation and packaging of the components, all metal surfaces shall be cleaned and dried in accordance with MIL-P-116, cleaning process C-1, drying procedure D-1 through D-5 as applicable.

3.3.1.2 Preservation. Preservatives specified herein shall conform to the applicable specifications listed in, and shall be applied in accordance with MIL-P-116. Methods of preservation specified herein, indicated by symbols, shall conform to the corresponding symbols in MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

3.3.1.3 Wood borer, paving breaker, sinker drill, portable hammer, chain saw, circular saw, tamper and sump pump. Interior surfaces of air motors shall be coated with preservative lubricating oil conforming to MIL-L-21260, type I, grade 30, applied through the lubricating system or by feeding the preservative into the air inlet while operating the motors until the preservative appears at the exhaust ports. Air inlets and outlets shall be closed with plastic caps or plugs conforming to MIL-C-52078 or sealed with tape conforming to PPP-T-60, type IV. Exterior unprotected metal surfaces of the units, subject to corrosion, shall be coated with type P-1 preservative. Chucks and chuck fittings shall be coated with type P-7 preservative and wrapped with barrier material conforming to MIL-B-121, grade A, class 2. The barrier shall be secured in place with tape conforming to PPP-T-60, type IV. Unless otherwise specified (see 6.2), the chain shall be removed from the chain saw and preserved method IA-6 using an oiltight container and preservative lubricating oil conforming to MIL-L-21260, type I, grade 30.

3.3.1.4 Attachments and accessories. All unprotected metal surfaces of attachments and accessories subject to corrosion shall be coated with type P-1 preservative when the attachment or accessory can be used without removing the preservative. When removal of the preservative is required before the attachment or accessory can be used, the preservative shall be type P-7. Attachments and accessories coated with type P-7 preservative shall be wrapped or covered with barrier material conforming to MIL-B-121, type I, grade A, class 2. The barrier material shall be secured with tape conforming to PPP-T-60, type IV. Threaded surfaces of drill rods shall be protected with plastic caps conforming to MIL-C-52078 or wrapped with tape conforming to PPP-T-60, type IV.

3.3.1.5 Auger bit set. All surfaces of the auger bits shall be coated with type P-1 preservative. The bits shall then be placed in the tool box and the tool box lid shall be closed and secured. All lid joints of the box shall be sealed with tape conforming to PPP-T-60, type IV.

3.3.1.6 Air blow gun and inflator gage. The air blow gun and inflator gage shall be individually preserved Method IC-1 using type P-7 preservative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

3.3.1.7 Polyester fiber hose and rubber hose assemblies. The polyester fiber hose and rubber hose assemblies shall be preserved and packaged in accordance with MIL-H-775, level A.

3.3.1.8 Airline oilers. The interior surface of the airline oilers shall be coated with preservative lubricating oil conforming to MIL-L-21260, type I, grade 10. Excess preservative shall be drained. Exterior unprotected metal surfaces subject to corrosion shall be coated with type P-1 preservative. Openings into oilers removed from the hose shall be sealed with tape conforming to PPP-T-60, type IV.

3.3.1.9 Leather gloves, goggles, mask and hose mender. Each pair of gloves, each pair of goggles, each hose mender and the box of air filtering masks shall be preserved individually method IC-1.

3.3.1.10 Lubricating oil. The drum of lubricating oil shall not require additional packaging.

3.3.1.11 Compressor (MAP shipment only). The compressor shall be preserved and packaged in accordance with MIL-C-3600, level A.

3.3.1.12 Maintenance tools. Maintenance tools shall be preserved and packaged in accordance with PPP-P-40, level A.

3.3.1.13 Repair parts. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve and package repair parts.

3.3.1.14 Technical publications. Technical publications shall be preserved method IC-1.

3.3.1.15 Consolidated packaging. The preserved and packaged components of the set shall be consolidated packaged in the chests provided in accordance with the chests loading plans. The chest lids shall be closed and secured and all lid joints shall be sealed with tape conforming to PPP-T-60, type IV. The 4-foot, 6-foot, 8-foot, and 10-foot drill rods shall be bundled together in a flat bundle of two layers depth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

3.3.2 Level C. The components of the pneumatic tool outfit shall be preserved and packaged to afford protection against deterioration and damage during handling and shipment from the supplier to the initial destination for immediate use. The components shall be consolidated packaged in the chest as specified for level A. The compressor (MAP only) shall be preserved and packaged in accordance with MIL-C-3600, level C.

3.4 Packing. Packing shall be level A, B, or C as specified (see 6.2).

3.4.1 Level A. The chests and bundle comprising a complete pneumatic tool outfit shall be packed in a crate conforming to MIL-C-104, type I, class 2, style a. Blocking, bracing and anchoring shall be in accordance with the appendix to the crate specification and MIL-STD-1186. Strapping shall be zinc coated. The compressor, when furnished for MAP shipment, shall be prepared for shipment mobile in accordance with MIL-C-3600, level A.

(Note: Compressor shall be shipped separate but at the same time as the crated outfit components.)

3.4.2 Level B. The chests and bundle comprising a complete pneumatic tool outfit shall be packed in a crate conforming to MIL-C-3774, type I, style A. Blocking, bracing and anchoring shall be in accordance with the appendix to the crate specification and MIL-STD-1186. The contents shall be protected with a waterproof shroud in accordance with the appendix to the crate specification. Strapping will not be required to be zinc coated. The compressor, when furnished for MAP shipment, shall be prepared for shipment mobile in accordance with MIL-C-3600, level B.

(Note: Compressor shall be shipped separate but at the same time as the crated outfit components.)

3.4.3 Level C. The complete pneumatic tool outfit shall be prepared for shipment in a manner to assure carrier acceptance and safe delivery to destination at the lowest rating. Containers and packing shall comply with Uniform Classification rules or National Motor Freight Classification rules.

3.5 Marking. Marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects listed in 4.4.4. Presence of one or more defects shall be cause for rejection of the preproduction pack.

4.3.2 Test. The preproduction pack of crated components shall be subjected to the railroad car guided impact test as specified in Appendix A to MIL-STD-1186. The railcar shall strike a string of five empty cars with draft gear extended and the brakes set. The speed of the car at impact shall be not less than 10 miles per hour or not more than 11 miles per hour. Shifting of contents, loosening or breaking of anchoring, blocking, or bracing within the crate shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers, and packaging marking prior to placing the packages into consolidated containers.
(b) The second stage shall include inspection of closure and marking of consolidated containers, and the arrangement and blocking and bracing of consolidated containers in the shipping containers.
(c) The third stage shall include inspection of the closed, strapped, and marked shipping containers as prepared for shipment.

4.4.2 Unit of Product. For the purpose of inspection, all packages or packs prepared for any applicable inspection stage that will comprise a complete pack shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in table I. Acceptable quality level (AQL) shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects

No.		Level		
		A	B	C
101.	Materials, methods or containers not as specified. Each incorrect material, method or container shall constitute one defect. (3.2, 3.3, and 3.4)	X	X	-
102.	Interior surfaces of air motors not coated and inlets and outlets caped as specified. (3.3.1.3)	X	-	-
103.	Unprotected exterior surfaces of power units not coated with preservative as specified (3.3.1.3)	X	-	-
104.	Chucks and chuck fittings not coated and wrapped as specified (3.3.1.3)	X	-	-
105.	Attachments and accessories not coated with preservative and wrapped as specified. (3.3.1.4)	X	-	-
106.	Threadeded surfaces of drill rods not protected as specified (3.3.1.4)	X	-	-
107.	Auger bit set not preserved, placed in the box and the box lid sealed as specified (3.3.1.5)	X	-	-
108.	Interior of airline oilers not coated and opening sealed as specified. (3.3.1.8)	X	-	-
109.	Unprotected exterior surfaces of airline oilers not coated as specified (3.3.1.8)	X	-	-
110.	Components not preserved and packaged in accordance with referenced documents as specified. (3.3.1.7, 3.3.1.11, 3.3.1.12 and 3.3.2)	X	-	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

No.		Level		
		A	B	C
111.	Compressor not prepared for shipment in accordance with referenced document as specified (3.4.1 and 3.4.2)	X	X	-
112.	Consolidated packaging not as specified (3.3.1.15)	X	-	X
113.	Strapping not zinc coated for level A (3.4.1)	X	-	-
114.	Waterproof shroud not provided. (3.4.2)	-	X	-
115.	Marking illegible, incomplete, incorrect or missing (3.5).	X	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

(This section not applicable to this specification)

6. NOTES

6.1 Intended use. This specification is intended to be used for direct reference in contracts or purchase orders for the preservation, packaging, packing and marking of Pneumatic Tool Outfit, 600 CFM Compressed Air (FSN 3820-595-9536) for MAP (FSN 3820-914-2571).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.1).
(c) When the chain shall not be removed from the chain saw (see 3.3.1.3).
(d) Level of preservation and packaging and level of packing required (see 3.3 and 3.4).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to approval of the contracting Officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the set components in accordance with this specification.

Custodian:

Army - ME

Preparing activity:

Army - ME

Review activity:

Army - SM

Project No. 3820-A140

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.