NOT MEASUREMENT SENSITIVE

MIL-P-3819D(ME)
26 October 1990
SUPERSEDING
MIL-P-3819C(ME)
24 April 1973

MILITARY SPECIFICATION

PNEUMATIC TOOL OUTFIT: 600 CFM, COMPRESSED AIR, PACKAGING OF

This specification is approved for use within the USA Belvoir Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for preservation, packaging, packing, and marking of the 600 CFM compressed air pneumatic tool outfit (SC 3820-98-CL-E11).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-P-40 - Packaging and Packing of Hand Tools.
PPP-T-60 - Tape: Packaging, Waterproof.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC PACK
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-104	- Crates, Wood; Lumber and Plywood.
MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-H-775	- Hose, Rubber or Fabric (Including Tubing); and Fittings, Nozzles and Strainers, Packaging of.
MIL-C-3600	- Compressors, Rotary, Power-Driven; and Compressor, Reciprocating, Power-Driven: Air and Gas (Except Oxygen and Refrigerant), Packaging of.
MIL-C-3774	- Crates, Wood; Open, 12,000 and 16,000 Pound Capacity.
MIL-C-5501	- Cap and Plug, Protective, Dust and Moisture Seal.
MIL-L-21260	- Lubricating Oil, Internal Combustion Engine, Preservative and Break-In.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION (NMFTA)

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, ATTN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM FREIGHT CLASSIFICATION COMMITTEE (UCC)

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article pack. Unless otherwise specified (see 6.2), a sample shall be subjected to first article pack inspection (see 6.3) in accordance with 4.3.

3.2 Materials. Materials shall be as specified herein and in the applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3 Preservation. Preservation shall be level A or C as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Cleaning and drying. Prior to the preservation and packaging of the components, all metal surfaces shall be cleaned and dried in accordance with MIL-P-116, cleaning process C-1, drying procedure D-1 through D-5 as applicable.

3.3.1.2 Preservation. Preservatives specified herein shall conform to the applicable specifications listed in, and shall be applied in accordance with MIL-P-116. Methods of preservation specified herein, indicated by symbols, shall conform to the corresponding symbols in MIL-P-116.

3.3.1.3 Wood borer, pacing breaker, sinker drill, portable hammer, chain saw, circular saw, tamper and sump pump. Interior surfaces of air motors shall be coated with preservative lubricating oil conforming to MIL-L-21260, type I, grade 30, applied through the lubricating system or by feeding the preservative into the air inlet while operating the motors until the preservative appears at the exhaust ports. Air inlets and outlets shall be closed with plastic caps or plugs conforming to MIL-C-5501 or sealed with tape conforming to PPP-T-60, type IV. Exterior unprotected metal surfaces of the units, subject to corrosion shall be coated with type P-1 preservative. Chucks and chuck fittings shall be coated with type P-7 preservative and wrapped with barrier material conforming to MIL-B-121, grade A, class 2. The barrier shall be secured in place with tape conforming to PPP-T-60, type IV. Unless otherwise specified (see 6.2), the chain shall be removed from the chain saw and preserved in accordance with method IA-6 using an oil-tight container and preservative lubricating oil conforming to MIL-L-21260, type I, grade 30.

3.3.1.4 Attachments and accessories. All unprotected metal surfaces of attachments and accessories subject to corrosion shall be coated with type P-1 preservative when the attachment or accessory can be used without removing the preservative. When removal of the preservative is required before the attachment or accessory can be used, the preservative shall be type P-7. Attachments and accessories coated with type P-7 preservative shall be wrapped or covered with barrier material conforming to MIL-B-121, type I, grade A, class 2. The barrier

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

material shall be secured with tape conforming to PPP-T-60, type IV. Threaded surfaces of drill rods shall be protected with plastic caps conforming to MIL-C-5501 or wrapped with tape conforming to PPP-T-60, type IV.

3.3.1.5 Auger bit set. All surfaces of the auger bits shall be coated with type P-1 preservative. The bits shall then be placed in the tool box and the tool box lid shall be closed and secured. All lid joints of the box shall be sealed with tape conforming to PPP-T-60, type IV.

3.3.1.6 Air blow gun and inflator gage. The air blow gun and inflator gage shall be individually preserved in accordance with method IC-1 using P-7 preservative.

3.3.1.7 Polyester fiber hose and rubber hose assemblies. The polyester fiber hose and rubber hose assemblies shall be preserved and packaged in accordance with MIL-H-775, level A.

3.3.1.8 Airline oilers. The interior surface of the airline oilers shall be coated with preservative lubricating oil conforming to MIL-L-21260, type I, grade 10. Excess preservative shall be drained. Exterior unprotected metal surfaces subject to corrosion shall be coated with type P-1 preservative. Openings into oilers removed from the hose shall be sealed with tape conforming to PPP-T-60, type IV.

3.3.1.9 Leather gloves, goggles, mask and hose mender. Each pair of gloves, each pair of goggles, each hose mender and the box of air filtering masks shall be preserved individually in accordance with method IC-1.

3.3.1.10 Lubricating oil. The drum of lubricating oil shall not require additional packaging.;

3.3.1.11 Compressor (MAP shipment only). The compressor shall be preserved and packaged in accordance with MIL-C-3600, level A.

3.3.1.12 Maintenance tools. Maintenance tools shall be preserved and packaged in accordance with PPP-P-40, level A.

3.3.1.13 Repair parts. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve and package repair parts.

3.3.1.14 Technical publications. Technical publications shall be preserved in accordance with method IC-1.

3.3.1.15 Consolidation. The preserved and packaged components of the set shall be consolidated in the chests provided in accordance with the chests loading plans. The chest lids shall be closed and secured and all lid joints shall be sealed with tape conforming to PPP-T-60, type IV. The 4-foot, 6-foot, 8-foot, and 10-foot drill rods shall be bundled together in a flat bundle of two layers depth.

3.3.2 Level C. The components of the pneumatic tool outfit shall be preserved and packaged to afford protection against deterioration and damage during handling and shipment from the contractor to the initial destination for

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

immediate use. The components shall be consolidated in the chest as specified for level A. The compressor (MAP only) shall be preserved in accordance with MIL-C-3600, level C.

3.4 Packing. Packing shall be level A, B, or C as specified (see 6.2).

3.4.1 Level A. The chests and bundle comprising a complete pneumatic tool outfit shall be packed in a crate conforming to MIL-C-104, type I, class 2, style a. Blocking, bracing and anchoring shall be in accordance with the appendix to the crate specification and MIL-STD-1186. Strapping shall be zinc coated. The compressor, when furnished for MAP shipment, shall be prepared for shipment mobile in accordance with MIL-C-3600, level A.

(Note: Compressor shall be shipped separate but at the same time as the crated outfit components.)

3.4.2 Level B. The chest and bundle comprising a complete pneumatic tool outfit shall be packed in a crate conforming to MIL-C-3774, type I, style A. Blocking, bracing and anchoring shall be in accordance with the appendix to the crate specification and MIL-STD-1186. The contents shall be protected with a waterproof shroud in accordance with the appendix to the crate specification. Strapping will not be required to be zinc coated. The compressor, when furnished for MAP shipment, shall be prepared for shipment mobile in accordance with MIL-C-3600, level B.

(Note: Compressor shall be shipped separate but at the same time as the crated outfit components.)

3.4.3 Level C. The complete pneumatic tool outfit shall be prepared for shipment in a manner to assure carrier acceptance and safe delivery to destination at the lowest rating. Containers and packing shall comply with Uniform Classification rules or National Motor Freight Classification rules.

3.5 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

3.6 Workmanship. Cleaning, preserving, packing, and marking requirements specified herein shall give a maximum protection against corrosion, deterioration, and mechanical or physical damage during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Material inspection. The contractor is responsible for insuring that materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article pack inspection.

4.3.1 Examination. The first article pack shall be examined for the defects listed in 4.4.4. Presence or one or more defects shall be cause for rejection of the first article pack.

4.3.2 Test. The first article pack of crated components shall be subjected to the railroad car guided impact test as specified in MIL-STD-1186, appendix A. The railcar shall strike a string of five empty cars with draft gear extended and the brakes set. The speed of the car at impact shall be not less than 10 miles per hour or not more than 11 miles per hour. Shifting of contents, loosening or breaking of anchoring, blocking, or bracing within the crate shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

a. The first stage shall include inspection of procedures, methods, materials, containers, and packaging marking prior to placing the packages into consolidated containers.
b. The second stage shall include inspection of closure and marking of consolidated containers, and the arrangement and blocking and bracing of consolidated containers in the shipping containers.
c. The third stage shall include inspection of the closed, strapped, and marked shipping containers as prepared for shipment.

4.4.2 Unit of product. For the purpose of inspection, all packages or packs prepared for any applicable inspection stage that will comprise a complete pack shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Samples shall be selected using MIL-STD-105, tables I and IIa.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in table I. One or more defects shall be cause for rejection.

TABLE I. Classification of defects.

No.	Defect	Level		
		A	B	C
101.	Materials, methods, or containers not as specified. Each incorrect material, method, or container shall constitute one defect (see 3.2, 3.3, and 3.4).	X	X	-
102.	Interior surfaces of air motors not coated and inlets and outlets capped as specified (see 3.3.1.3).	X	-	-
103.	Unprotected exterior surfaces of power units not coated with preservative as specified (see 3.3.1.3).	X	-	-
104.	Chucks and chuck fittings not coated and wrapped as specified (see 3.3.1.3).	X	-	-
105.	Attachments and accessories not coated with preservative and wrapped as specified (see 3.3.1.4).	X	-	-
106.	Threaded surfaces of drill rods not protected as specified (see 3.3.1.4).	X	-	-
107.	Auger bit set not preserved, placed in the box and the box lid sealed as specified (see 3.3.1.5).	X	-	-
108.	Interior of airline oilers not coated and openings sealed as specified (see 3.3.1.8).	X	-	-
109.	Unprotected exterior surfaces of airline oilers not coated as specified (see 3.3.1.8).	X	-	-
110.	Components not preserved in accordance with referenced documents as specified (see 3.3.1.7, 3.3.1.11, 3.3.1.12, and 3.3.2).	X	-	X
111.	Consolidation not as specified (see 3.3.1.15).	X	-	X
112.	Compressor not prepared for shipment in accordance with referenced document as specified (see 3.4.1 and 3.4.2).	X	X	-
113.	Strapping not zinc coated for level A (see 3.4.1).	X	-	-
114.	Waterproof shroud not provided (see 3.4.2).	-	X	-
115.	Marking illegible, incomplete, incorrect or missing (see 3.5).	X	X	X
116.	Workmanship not as specified (see 3.6).	X	X	X

5. PACKAGING

(This section not applicable to this specification.)

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

6.1 Intended use. This specification is intended to be used for direct reference in contracts or purchase orders for the preservation, packing and marking of pneumatic tool outfit, 600 CFM compressed air (NSN 3820-00-595-9536) for MAP (NSN 3820-00-914-2571).

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Time frame required for submission of the first article pack (see 3.1).
d. When the chain shall not be removed from the chain saw (see 3.3.1.3).
e. Level of preservation and packing required (see 3.3 and 3.4).
f. Any special marking (see 3.5).

6.3 First article pack. Any changes or deviations of production packs from the approved first article pack will be subject to approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, package, pack, and mark the set components in accordance with this specification.

6.4 Subject term (key word) listing.

Pneumatic tool outfit, marking of
Pneumatic tool outfit, packing of
Pneumatic tool outfit, preservation of

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Review activity:
Army - AT, SM

Preparing activity:
Army - ME

Project 3820-A192

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-3819D(ME)	901026

3. DOCUMENT TITLE
Pneumatic Tool Outfit: 600 CFM, Compressed Air, Packaging Of

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
	(703) 664-5717	354-5717
c. ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Ft. Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2020-07-15T14:57:52Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:45Z
Check the source to verify that this is the current version before use.