MIL-C-11997B(CR)
Amendment 1
22 April 1987

MILITARY SPECIFICATION

CORD ASSEMBLY, ELECTRICAL; CX-2151( )/U (RETRACTILE)

This amendment forms a part of Military Specification MIL-C-11997(EL), dated 12 Jun 72, and is approved for use by the Communications-Electronics Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under **SPECIFICATIONS/MILITARY**, delete "MIL-C-45662 Calibration System Requirements"

Under **STANDARDS/MILITARY**, add "MIL-STD-45662 Calibration System Requirements"

PAGE 3

Paragraph 3.2.1, line 7: Add "As an optional construction, the finished cord may have a right-hand lay in its helical section, provided that the cabling direction of 3.3.4 is the optional left-hand lay".

PAGE 4

Paragraph 3.3.4, line 3: Add "As an option, six of the insulated conductors may be twisted with a left-hand lay around the remaining conductor, with a maximum length of lay of 1 5/8 inches. If this option is used, the finished cord construction of 3.2.1 must be a right-hand lay helix direction".

CUSTODIAN:
ARMY-CR

PREPARING ACTIVITY:
ARMY-CR

PROJECT 5995-A123

AMSC N/A

FSC 5995

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:12Z
Check the source to verify that this is the current version before use.