022282

PROCUREMENT DATA DIVISION
PRODUCTION AND SPECIFICATION ENGINEERING DEPARTMENT
U.S. ARMY ELECTRONICS MATERIEL SUPPORT AGENCY
FORT MONMOUTH, NEW JERSEY

Date: 1 March 1953

ADDENDUM NUMBER 3

To Accompany: Specification MIL-G-11994A

For: GENERATOR, RINGING, HAND, G-42( )/PT

---

1. Paragraph 3.5.1.2 Open circuit voltage: Replace "100 ± 5 volts" with "100 ± 10 volts."

2. Paragraph 3.5.2.3 Starting torque: Replace "2-1/2 inch pounds" with "3 inch pounds."

3. Paragraph 3.5.2.4 Switch operation: Delete the second sentence, "The switch shall operate when the generator handle attains a crank speed of between 110 and 125 r.p.m."

4. Paragraph 3.6.2(a) Temperature: Delete and replace with the following:

"(a) Temperature.- Full requirements at any ambient temperature in the range of + 125° F to - 40° F. (See 4.6.1.)".

5. Paragraph 4.5.1.3 Open circuit voltage test: Replace "5 volts" with "10 volts."

6. Paragraph 4.6.4 Immersion test: Replace "2 hours" and "2-hour period" with "10 minutes" and "10-minute period" respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:11Z
Check the source to verify that this is the current version before use.