INCH-POUND

MIL-S-12030B
30 June 1989
SUPERSEDING
MIL-P-12030A
12 August 1953

MILITARY SPECIFICATION

SMOKE POT, HC, M1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of smoke pot.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

STANDARDS

MILITARY

MIL-STD-147 - Palletized Unit Loads
MIL-STD-1167 - Ammunition Data Card
MIL-STD-1168 - Ammunition Lot Numbering

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-SPT-S, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1365

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. ARMY CHEMICAL RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

DRAWINGS

36-1-1	-	Smoke Pot, HC, M1
36-1-97	-	Cover, Inner Assembly
36-3-29	-	Packing and Marking for Smoke Pot, HC, M1
36-4-1	-	Card, Instruction

(Copies are available from Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-SPT-O, Aberdeen Proving Ground, MD 21010-5423.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing 36-1-1 and on subsidiary drawings shall conform to the specifications thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components shall conform to the specifications and drawings listed on Drawing 36-1-1 and subsidiary drawings.

3.2 Assembly. The smoke pot shall be assembled as shown on Drawing 36-1-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

3.3 Functioning.

3.3.1 Ignition and smoke production. The smoke pot shall be ignited using the scratcher block and shall produce smoke under audible pressure in accordance with specified requirements when tested as specified in 4.4.5.1.

3.3.2 Delay time. The delay time shall be no greater than 30 seconds when tested as specified in 4.4.5.1 (see 6.3).

3.3.3 Smoke emission. Total burn time shall be no less than 5 minutes (excluding delay time) nor more than 8 minutes when tested as specified in 4.4.5.1 (see 6.3).

3.4 First article. Prior to the start of regular production, a first article sample of smoke pots shall be produced in accordance with this specification for examination and tests (see 4.3).

3.5 Workmanship. The smoke pot shall be free from foreign matter (oil or grease), damage such as cracks, breaks, or deformation which could effect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Sample. A first article sample of 50 smoke pots or production from one 8 hour shift, whichever is greater, shall be produced using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components, and test specimens may be subjected to any or all of the examinations and tests specified in this detail specification and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection criteria. If any assembly, component, or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of any assembly, component, or test specimen to comply with any of the requirements.

4.4 Quality conformance inspection.

4.4.1 Lotting. Lotting shall be in accordance with MIL-STD-1168. A lot shall consist of the smoke pots of one interfix number, produced by one manufacturer, from the same materials and under the same manufacturing conditions. Ammunition data cards in accordance with MIL-STD-1167 shall be furnished for each production lot.

4.4.2 Sampling. Sampling shall be as specified in the contract (see 6.2 and 6.5).

4.4.3 Inspection procedure. Sample smoke pots shall be inspected for the defects listed in 4.4.4 and shall be tested in accordance with 4.4.5. Duds shall not be assessed against burning time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

4.4.4 Classification of defects.

(a) Smoke pot, HC, M1 - assembly (Drawing 36-1-1)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Inner cover seam incorrect	Visual/radiographic
102	Envelope scratcher assembly missing or incorrect	Visual/radiographic
103	Filling missing or incorrect	Visual/radiographic
104	Clamp, strap, and cover assembled incorrectly	Visual
105	Dud during functioning test	4.4.5.1 (Visual)
106	Delay time incorrect during functioning test	4.4.5.1 (Visual/stopwatch)
107	Smoke emission time incorrect during functioning test	4.4.5.1 (Visual/stopwatch)
Minor:		
201	Marking missing or incorrect	Visual
202	Workmanship (3.5)	Visual

(b) Cover, inner assembly (Drawing 36-1-97)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Component missing, damaged, or incorrectly assembled	Visual
102	Workmanship (3.5)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

(c) Packaging (section 5 and Drawings 36-3-29 and 36-4-1)

Categories	Defects	Inspection method
Critical:	None defined	
Major:		
101	Component missing or incorrectly assembled	Visual
102	Marking missing, incorrect or illegible	Visual
103	Box dimensions incorrect	SME*
104	Instruction card missing	Visual

*SME - Standard measuring equipment

4.4.5 Tests.

4.4.5.1 Functioning. The smoke pot shall be immersed in water at 25° ± 5°C to a depth of 2 inches (measured from the top surface of the smoke pot) for a minimum of 2 hours. The smoke pot temperature shall be between 20° and 25°C at the time of immersion. After being removed from the water, the smoke pot shall be ignited by removing the scratcher from the envelope and drawing it against the match-head.

5. PACKAGING

5.1 Packing, level A. Three smoke pots and one instruction card (Drawing 36-4-1) shall be unit packed together in accordance with Drawing 36-3-29.

5.2 Marking. Marking of the shipping container shall be as specified on Drawing 36-3-29.

5.3 Palletization. When specified in the contract, shipping containers shall be palletized in accordance with the applicable load method of MIL-STD-147.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The smoke pot is intended to produce smoke screens.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1)

(c) First article instructions:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract

(2) Name and address of test facility and shipping instructions when testing is performed by the Government

(3) Time required for the Government to notify the contractor whether or not to proceed with production

(d) Sampling for quality conformance inspection (see 4.4.2 and 6.5)

6.3 Definitions.

(a) Dud. A malfunction due to a mechanical or pyrotechnic failure.

(b) Smoke emission time. The period of time during the burning of the smoke mixture when smoke is emitted under audible pressure.

6.4 Caution. Due to the hazard involved in filling items with flammable mixtures, contractors are advised to exercise all necessary precautions to protect personnel from injury during filling and testing operations.

6.5 Recommended sampling.

6.5.1 For nondestructive tests. For lot sizes of 1,200 or less, it is recommended that 32 samples be taken and the acceptance/rejection numbers be 0/1, respectively. For lot sizes over 1,200, it is recommended that 125 samples be taken and the acceptance/rejection numbers be 0/1, respectively.

6.5.2 For destructive tests. For lot sizes up to 3000, it is recommended that 32 samples be taken and the acceptance/rejection numbers be 0/1, respectively.

6.6 Component specification. MIL-S-51547 covers the components required for the complete assembly of the smoke pot.

6.7 Subject term (key word) listing.

Delay time
Dud
Match-Head
Scratcher
Smoke emission time

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

Custodians:

Army - EA
Navy - OS

User activity:

Navy - MC

Preparing activity:

Army - EA

Project No. 1365-0247

☆U.S. GOVERNMENT PRINTING OFFICE: 1989 - 604-033/13909

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
U.S. Army Chemical Research, Development
and Engineering Center
ATTN: SMCCR-SPT-S
Aberdeen Proving Ground, MD 21010-5423

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-12030B	SMOKE POT, HC, M1

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:14Z
Check the source to verify that this is the current version before use.