MILITARY SPECIFICATION SHEET

MICROPHONE M-94B/A

This amendment forms part of MIL-M-26542/7A, dated 29 March 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

MIL-M-26542/7A remains inactive for new design.

PAGE 3

FIGURE 2: Delete notes 2 and 3 and substitute:

"2. Material: Inner sleeve: Beryllium copper, Alloy 25, in accordance with ASTM B 196/B 196M.
Outer sleeve: H02 (Half-hard) brass, in accordance with ASTM B 36/B 36M.
3. Finish: (Outer sleeve only)
Tin, .0002 inch minimum, in accordance with ASTM B 545, B 339."

PAGE 5

FIGURE 4: Add the following table:

"

Frequency points	300 Hz	500 Hz	2,000 Hz	2,500 Hz	3,000 Hz	4,000 Hz
Upper limits (dB)	49.0	54.0	54.0	56.2 1/	58.0	54.0
Lower limits(dB)	44.0	47.0	47.0	47.0	45.1 1/	42.0

1/ dB limits between key break point are calculated."

PAGE 6

REQUIREMENTS: Delete the last sentence and substitute:

"The microphone assembly shall be tested in accordance with the tests listed in table I. The requirement for qualification and group C testing are deleted and replaced by First Article test (see table I)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:54Z
Check the source to verify that this is the current version before use.

PAGE 7

TABLE I: Delete and substitute:

"TABLE I. Parameter applicability.

Inspection	First article	Group A	Group B
Group I			
Visual and mechanical inspection	X	X	
Sensitivity at ground level	X	X	
Sensitivity at altitude	X		
Frequency response at ground level	X	X	
Frequency response at altitude			
Impedance	X	X	
Noise cancellation characteristics			
Effect of external magnetic field			
Stray magnetic field	X		X
Linearity	X		X
Talk-out			
Dielectric withstanding voltage			
Signal-to-noise	X		
Distortion	X		
Interchangeability			
Group II			
Thermal shock	X		
Humidity	X		
Drop	X		
Pressure equalization	X		
Explosive decompression	N/A		
Salt fog	X		
Group III			
Vibration	X		
Bounce	N/A		
Altitude	X		
Moisture barrier seal	X		
Immersion	N/A		

"

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5965-0366)

Review activities:
Army - AR, AT, AV, CR4
Navy - AS, OS
Air Force - 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:54Z
Check the source to verify that this is the current version before use.